PREMIUM MATTE LABEL

Premium matte coated inkjet labels for high-quality photo-level printing with pigmented inks. The smooth, bright white surface with a matte finish, in combination with Epson DURABrite Ultra pigment inks, ensures fast drying, scratch, water and heat resistance. The universal permanent acrylic adhesive enables trouble free performance and good adhesion on variety of surfaces, also on low temperatures.

Suggested applications

- Barcode labels
- Box labels for consumer products
- Parts assembly labels
- Shelf-edge labels in Retail

- Pharmaceutical labels
- Sample labels in Healthcare
- Shipping labels

MATERIAL	
Facestock	88g/m² (113µm) premium coated inkjet paper with matte finish
Adhesive	Acrylic, water borne permanent adhesive
Liner	51g/m² (54µm) white kraft paper
Total calliper	186µm
TEMPERATURE RANGE	
Printing temperature	10 to 35°C
Printing humidity	20 to 80% RH (No condensation)
Minimum application temperature	5°C
Service temperature	-20 to 100°C
Storage (in original package)	Up to one year in dry and dark conditions at a constant temperature (20°C, RH 50%)
RECOMMENDED DRIVER SETTINGS	
Media Type	Matte Label
Media Layout	Full-page Label / Die-cut Label
Print Quality	Speed / Quality

Since all dyes, pigments and paper change over time, Epson does not warrant this product against colour changes and fading. Epson's liability for any defects in manufacturing and packaging is limited to the replacement cost of this product.



AVAILABLE SKUS							PRINTER COMPATIBILITY								
Туре	SKU	EAN	Width	Length	Labels	Rolls	ColorWorks								
			(mm)	(mm)	per roll	per box	C3400	C3500	C4000	C831	C6000 AE 4in	C6000 PE 4in	C6500 AE 8in	C6500 PE 8in	C7500
	C33S045739	8715946688411	203	60	1	4							✓		
Roll, Continuous Label	C33S045741	8715946688435	102	60	1	8					√		√		√
Roll, Die-cut Label	C33S045533	8715946537207	102	152	225	18	√	√	✓						
	C33S045534	8715946537214	76	51	650	18	√	√	✓						
	C33S045535	8715946537221	76	127	265	18	√	√	✓						
	C33S045738	8715946688404	210	297	200	4							✓	✓	
	C33S045740	8715946688428	105	210	282	8					✓	✓	✓	✓	✓
	C33S045722	8715946547282	102	51	2,310	4					✓	✓			✓
	C33S045723	8715946547299	102	76	1,570	4					✓	✓			✓
	C33S045724	8715946547305	102	152	800	4					✓	✓			✓
	C33S045725	8715946547312	76	51	2,310	6					✓	✓			✓
	C33S045726	8715946547329	76	127	960	6					✓	✓			✓
Coil, Continuous Label	C33S045528	8715946537412	220	750lm	1	1	✓	✓	✓	✓	✓	✓			✓