Full detailed report

(ISO/IEC 24734 Office Category Test)

Model: Epson WorkForce Pro WF-8590 Series

Printing device and test setting

| I THICKING GOVICE AND LESS SECURING | |
|-------------------------------------|-----------------------|
| Test Start Date and Time | 2014/4/14 . 14:30 |
| Tester | S.Marumo |
| Color or B/W | Color Printing device |
| Configuration (Option) | Option wasn't used |
| Temperature and Humidity | 26.0°C / 20% |
| Voltage | Within Rating voltage |
| Test End Date and Time | 2014/4/14 . 17:00 |

| Modes and Settings | Print Quality mode | Default | | | | |
|--------------------|-------------------------|--|--|--|--|--|
| | B&W settings | Activated (Driver, select"Grayscale") | | | | |
| | Setting N set count | Activated (Application, select "count up" or "count down") | | | | |
| | Collating function | Activated (Application, select "collate") | | | | |
| Paper | Paper sending direction | Default | | | | |
| | Paper type setting | Default | | | | |
| Paper path | Paper feeding | Standard cassette | | | | |
| | Paper exit | Output tray | | | | |
| | Output orientation | Default (face up) | | | | |
| | Duplexing unit | Default | | | | |

| Paper | Manufacturer | Fuji Xerox |
|-------|-----------------|------------|
| | Weight | 64g/m2 |
| | Size | A3 |
| | Paper type/Name | PPC/V603 |

Test system parameters

| l est system parameters | | | | | | | |
|----------------------------|--------------------------|--|--|--|--|--|--|
| Test system | Computer | EPSON Direct Endeavor Pro4300 | | | | | |
| | Processor | Intel Core2Duo E6850 | | | | | |
| | System Chip Set | Intel P35 Express chipset | | | | | |
| | System Board | ASUSTeK: IPIBL-CH BIOS: AMI Version 0121 | | | | | |
| | System Memory | 2GB, 800MHz, DDR2, SanMaxTechnologies p/n (SMD-1G48H1P-8E) × 2 | | | | | |
| | Hard Drive and Subsystem | 320GB, (Samsung HD161HJ 160GB 7200rpm)×2 SATA/3000 | | | | | |
| | Video system | Sapphire Radeon HD2400L/P/RW 256MB dedicated video memory. | | | | | |
| | Optical Drive | PLDS DH-48C2S SATA | | | | | |
| | I/O Subsystem | USB keyboard and mouse | | | | | |
| | USB Subsystem | System board USB controller , USB2.0 | | | | | |
| Software | Operating System | Microsoft Windows Vista Home Premium Edition | | | | | |
| | Printing Application | Adobe Reader 9.0.0 | | | | | |
| | | Microsoft Office Excel2007 | | | | | |
| | | Microsoft Office Word2007 | | | | | |
| | Print Driver | Ver.2.40 | | | | | |
| | Test Files Location | Office Category files, hard drive | | | | | |
| Printing Device Connection | USB | USB 2.0 Keyboard and mouse were connected. | | | | | |

Application setting deviations from default.

| Changing from default. | Excel and Word | "Scale Content for A4 or 8.5 x 11" Paper size" set to off. |
|------------------------|----------------|--|
| | Adobe Reader | "Paper Scaling" set to "None". |

Summary Report

| Office Category Te | FSOT [seconds] | ESAT [ppm/ipm] | | |
|--------------------|--------------------|-------------------|-------|--|
| Color | Simplex Average | 22.44 | 13.15 | |
| (Default) | Duplex Average | 24.93 | 11.34 | |
| B&W mode | Simplex Average | 22.05 | 13.37 | |
| D&W mode | Duplex Average | 24.49 | 11.49 | |

Notes

-All printing device and print driver setting were default mode.

-For the B&W result, the print driver was set to "Grayscale"

-For the duplex result, the print driver was set to "Auto(Long-edge binding)" in "2-sided printing"

| Full Report | | | | | | | | | | | | | | | |
|----------------------|---------|-----------|-----------|--------------------------------|--------------------------------|-------------------|----------------------|----------|-----------|----------------|--------------------------------|--------------------------------|------------------|-------------------|-------|
| Office Category Test | | FSOT | | EFTP [ppm/ipm] | | ESAT | Office Category Test | | FSOT | EFTP [ppm/ipm] | | | ESAT | | |
| | | [seconds] | 1set test | 1set+30 seconds (# sets) | 1 set+4 minutes (# sets) | [ppm/ipm] | | | [seconds] | 1set test | 1set+30 seconds (# sets) | 1 set+4 minutes (# sets) | [ppm/ipm] | | |
| Color (Default) | Simplex | PDF | 22.99 | 10.43 | 11.65 (3 set) | 12.31 (14 set) | 12.56 | B&W mode | Simplex - | PDF | 21.77 | 11.01 | 12.43 (3 set) | 13.12 (15 set) | 13.39 |
| | | Word | 20.23 | | | | 14.22 | | | Word | 20.06 | | | | 14.26 |
| | | Excel | 24.09 | | | | 12.67 | | | Excel | 24.31 | | | | 12.48 |
| | | Average | 22.44 | | | | 13.15 | | | Average | 22.05 | | | | 13.37 |
| | Duplex | PDF | 26.26 | 9.13 | 10.07 (3 set) | | 10.76 | | Duplex - | PDF | 25.79 | 9.30 | 10.27 (3 set) | | 10.89 |
| | | Word | 22.18 | | | | 12.65 | | | Word | 21.78 | | | | 12.79 |
| | | Excel | 26.33 | | | | 10.63 | | | Excel | 25.90 | | | | 10.79 |
| | | | Average | 24.93 | | | | 11.34 | | | Average | 24.49 | | | |

Notes

All printing device and print driver setting were default mode.
-For the B&W result, the print driver was set to "Grayscale"
-For the duplex result, the print driver was set to "Auto(Long-edge binding)" in "2-sided printing"