

Supported Media Glossy label, Glossy Film label, High Glossy label, Glossy Film label, High Glossy label Glossy label, Glossy Film label, High Glossy label Standard Printing Direction Bi-directional or Unidirectional Unidirectiona	Model	CW-C6000AE	CW-C6000PE	CW-C6500AE	CW-C6500PE
Ink Colours 4 colours 80 ml Matte label, Matte film label, Glossy label, Glossy Film label, High Glossy label, Glossy Film label, High Glossy label, Glosy	Print Head	μTFP4	μTFP4	μTFP4	μTFP4
Ink Capacity 80 ml Matte label, Matte film label, Glossy Jabel, Glossy Film label, High Glossy Iabel, High Glossy Iabel, Glossy Iabel, Glossy Iabel, High Glossy Iabel, Glossy Iabel, High Glossy Iabel, Glossy Iabel, High Glossy Iabel, Glosy Iabel, Glosy Iabel, Glossy Iabel, Glossy Iabel, Glosy Iab	Resolution (dpi)	1200 x 1200dpi	1200 x 1200dpi	1200 x 1200dpi	1200 x 1200dpi
Matte label, Matte film label, Glossy label, Glossy Film label, High Glossy label, Glossy Film label, High Glossy label, Glossy Film label, High Glossy label, Glossy label, Glossy label, High Glossy label,	Ink Colours	4 colours	4 colours	4 colours	4 colours
Supported Media Glossy label, Glossy Film label, High Glossy label, Glossy Film label, High Glossy label Glossy label, Glossy Film label, High Glossy label Standard Printing Direction Bi-directional or Unidirectional Unidirectiona	Ink Capacity	80 ml	80 ml	80 ml	80 ml
Printing Direction Bi-directional or Unidirectional Label Length 609.6 mm 609.6 mm 609.6 mm 609.6 mm 609.6 mm Size (W x D x H) 340 x 565 x 326 mm 340 x 565 x 326 mm 444 x 512 x 326 mm 444 x 512 x 326 mm 119 mm/s (Max Speed 300 x 600dpi) 75 mm/s (Speed 600 x 600dpi) (Speed 600 x 600dpi) (Speed 600 x 600dpi) 49 mm/s (Speed 600 x 600dpi) Print speed (in full-width) 48 mm/s (Normal 600 x 600dpi) 48 mm/s (Normal 600 x 600dpi) 34 mm/s (Normal 600 x 600dpi) 18 mm/s 18 mm/s 13 mm/s 13 mm/s	Supported Media	Glossy label, Glossy Film	Glossy label, Glossy Film	Glossy label, Glossy Film	Matte label, Matte film label Glossy label, Glossy Film label, High Glossy label
Printing Direction Unidirectional Unidirectional Unidirectional Unidirectional Label Length 609.6 mm 609.6 mm 609.6 mm 609.6 mm 609.6 mm Size (W x D x H) 340 x 565 x 326 mm 340 x 565 x 326 mm 444 x 512 x 326 mm 444 x 512 x 326 mm 119 mm/s (Max Speed 300 x 600dpi) 119 mm/s (Max Speed 300 x 600dpi) 85 mm/s (Max Speed 300 x 600dpi) 85 mm/s (Max Speed 300 x 600dpi) 49 mm/s (Speed 600 x 600dpi) Print speed (in full-width) 48 mm/s (Speed 600 x 600dpi) 48 mm/s (Normal 600 x 600dpi) 34 mm/s (Normal 600 x 600dpi) 34 mm/s (Normal 600 x 600dpi) B mm/s 18 mm/s 18 mm/s 13 mm/s 13 mm/s	IO Port	Standard	Standard	Standard	Standard
Size (W x D x H) 340 x 565 x 326 mm 340 x 565 x 326 mm 444 x 512 x 326 mm 444 x 512 x 326 mm 119 mm/s (Max Speed 300 x 600dpi) 119 mm/s (Max Speed 300 x 600dpi) 85 mm/s (Max Speed 300 x 600dpi) 85 mm/s (Max Speed 300 x 600dpi) 75 mm/s (Speed 600 x 600dpi) 75 mm/s (Speed 600 x 600dpi) 49 mm/s (Speed 600 x 600dpi) 49 mm/s (Speed 600 x 600dpi) Print speed (in full-width) 48 mm/s (Normal 600 x 600dpi) 34 mm/s (Normal 600 x 600dpi) 34 mm/s (Normal 600 x 600dpi) 18 mm/s 18 mm/s 13 mm/s 13 mm/s	Printing Direction				
119 mm/s (Max Speed 300 x 600dpi) 119 mm/s (Max Speed 300 x 600dpi) 49 mm/s (Speed 600 x 600dpi) (Speed 600 x 600dpi) (Speed 600 x 600dpi) 48 mm/s (Normal 600 x 600dpi) (Normal 600 x 600dpi) 18 mm/s 18 mm/s 13 mm/s 13 mm/s 13 mm/s	Label Length	609.6 mm	609.6 mm	609.6 mm	609.6 mm
(Max Speed 300 x 600dpi) (Speed 600 x 600dpi) (Normal 600 x 600dpi) (Normal 600 x 600dpi) (Normal 600 x 600dpi) (Normal 600 x 600dpi) (Speed 600 x 600dpi	Size (W x D x H)	340 x 565 x 326 mm	340 x 565 x 326 mm	444 x 512 x 326 mm	444 x 512 x 326 mm
Capeed 600 x 600dpi					85 mm/s (Max Speed 300 x 600dpi
(Normal 600 x 600dpi) 18 mm/s 13 mm/s 13 mm/s					49 mm/s (Speed 600 x 600dpi)
					34 mm/s (Normal 600 x 600dpi)
					13 mm/s (Quality 600 x 1200dpi)
8 mm/s (Max Quality 1200 x 1200dpi) 8 mm/s 6 mm/s 6 mm/s (Max Quality 1200 x 1200dpi)					6 mm/s (Max Quality 1200 x 1200c
Paper Roll Diameter 203.2 mm / 8" 203.2 mm / 8" 152.4 mm / 6" 152.4 mm / 6"	Paper Roll Diameter	203.2 mm / 8"	203.2 mm / 8"	152.4 mm / 6"	152.4 mm / 6"
Paper Width 25.4 to 112 mm 50 to 112 mm 25.4 to 215.9 mm 50 to 215.9 mm	Paper Width	25.4 to 112 mm	50 to 112 mm	25.4 to 215.9 mm	50 to 215.9 mm
Print Width Up to 108 mm Up to 211.9 mm Up to 211.9 mm	Print Width	Up to 108 mm	Up to 108 mm	Up to 211.9 mm	Up to 211.9 mm
Peeler / Autocutter Auto-cutter Peeler Auto-cutter Peeler	Peeler / Autocutter	Auto-cutter	Peeler	Auto-cutter	Peeler

C6000 series colour label printer Inspired labelling to take your business further EXTRA VIRGIN

Clive Oil

Hand-Picked **EPSON**°









On-demand colour labelling up to 8 inches wide

Developed as a result of direct feedback from customers, the ColorWorks C6000 series offers speed, control, efficiency and flexibility, allowing you to produce high quality, custom labels time after time.

The C6000 series comes in either 4" or 8" print-widths, and each size model is also available with an optional, built-in peeler to optimise workflows.





Glossy, matte and textured substrate support

Sizes from 25mm - 215mm

Unique movable sensor allows printing on any shape, without a second die cut

Remote configuration and maintenance

Intelligent web interface for management of printer fleets

Tool to push changes to a fleet of

Achieve smooth gradations and fine lines with variable size droplet technology

durable labels

BS 5609 certified when printing onto PE matt media

Easy operation

Load media from two different sides Remove paper jams easily with the front and rear hoods

One-step variable data processing Large (2.7") intuitive LCD display

Service support

Complete peace of mind

No caveats – everything is covered

CoverPlus is available as an optional extra to provide cover for the lifetime of the printer

ESC/Label

Applications



Pet food

Non-food







High-quality printing

1200x1200dpi resolution

Match solid colours to ICC profiles and spot brand colours

Durable Inks

Ultrachrome DL pigment inks for

under warranty, even the printhead

Exclusive built-in peeler

One-by-one functionality, unique amongst inkjet printers

Time-saving feature that automatically removes label backing paper

Simple integration with Print & Apply applications



Software drivers

Compatible with Windows, Linux and Mac/iOS

Integrates with SAP

ESC/Label, BarTender, CodeSoft, NiceLabel native drivers











