

High brightness

Exceptional projectors for installation, rental and staging



Model	EB-PU1006W	EB-PU1007W EB-PU1007B	EB-PU1008W EB-PU1008B	EB-PU2010W EB-PU2010B	EB-PU2113W EB-PU2213B	EB-PU2116W EB-PU2216B	EB-PU2120W EB-PU2220B	EB-PQ2008W EB-PQ2008B	EB-PQ2010W EB-PQ2010B	EB-PQ2213B	EB-PQ2216W EB-PQ2216B	EB-PQ2220B	EB-XQ2030B
Colour Light Output (lumens) normal / eco	6000 / 4200	7000 / 4900	8500 / 5950	10000 / 7000	13000 / 9100	16000 / 11200	20000 / 14000	8000 / 5600	10000 / 7000	13000 / 9100	16000 / 11200	20000 / 14000	30000 / 21000
Resolution	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	WUXGA / 4K-Enhancement	4K ³	4K ³	4K ³	4K ³	4K ³	4K ³
Noise (dB) normal / eco	30 / 28	33 / 29	35 / 30	37 / 30	34 / 29	38 / 34	45 / 37	35 / 29	39 / 29	37 / 34	44 / 36	48 / 39	47 / 37
Throw ratio in native aspect	1.44 - 2.32:1 ¹	1.44 - 2.32:1 ¹	1.44 - 2.32:1 ¹	1.57 - 2.56:1 ²	1.57 - 2.56:1 ²	1.57 - 2.56:1 ²	1.57 - 2.56:1 ²	1.52 - 2.47:1 ²	1.52 - 2.47:1 ²	1.52 - 2.47:1 ²	1.52 - 2.47:1 ²	1.52 - 2.47:1 ²	1.52 - 2.47:1 ²
Dimensions (W x D x H mm) ⁶	545 x 436 x 164	545 x 436 x 164	545 x 436 x 164	545 x 436 x 164	586 x 492 x 185	586 x 492 x 185	586 x 492 x 185	545 x 436 x 164	545 x 436 x 164	586 x 492 x 185	586 x 492 x 185	586 x 492 x 185	620 x 530 x 205
Weight (Kg)	15.4	16.3	16.3	16.8	23.8 23.7	24.3 24.2	24.4	18.6	18.8	28.8	29.2	29.2	34.4
Power consumption (W) normal / eco	367 / 310	431 / 366	535 / 452	535 / 452	864 / 633	1083 / 773	1301 / 899	502 / 410	613 / 483	925 / 666	1114 / 784	1431 / 975	2073 / 1324
Dust resistance	–	–	–	–	IP5X ⁴	IP5X ⁴	IP5X ⁴	–	–	IP5X ⁴	IP5X ⁴	IP5X ⁴	IP6X ⁴



ELPEC01 Camera unit

Optional external camera module designed for the EB-PU and EB-PQ Series and ELPLX Series ultra-short-throw lenses. Included with the EB-XQ2030B.

Unlock advanced features such as colour calibration, simple stacking, simple blending and the camera assist function for curved surfaces.

¹ With ELPLM08 - not supplied.

² With ELPLM15H - not supplied.

³ Maximum physical resolution using 4K Crystal Motion technology.

⁴ IP5X and IP6X certified in accordance with IEC Standard 60529. The IP5X and IP6X certification is applied to the optical engine and light source module. IP6X certification pending.

⁵ 2001 to 2025, 500-lumen and above, excluding screenless TVs, Futuresource Consulting – Quarterly Projector Market Insights – Worldwide Analyser CY26Q1.

⁶ Excluding protruding parts.

EPSON®

High brightness

Lens options for installation, rental and staging



Model			ELPLX01WS ELPLX01S	ELPLX02WS ¹ ELPLX02S ¹	ELPLX04H	ELPLU06H	ELPLU03S ¹	ELPLU07H	ELPLU04 ¹	ELPLU04H	ELPLW05 ²
EB-PU1000 Series EB-PU1006 to EB-PU1008	WUXGA 16:10	Throw ratio Lens shift V/H	0.35:1 + 17% / ± 10%	–	–	–	0.65 - 0.78:1 ± 67% / ± 30%	0.64 - 0.87:1 ± 67% / ± 30%	0.87 - 1.05:1 ± 67% / ± 30%	0.86 - 1.22:1 ± 67% / ± 30%	1.04 - 1.46:1 ± 67% / ± 30%
EB-PU2000 Series EB-PU2010 to EB-PU2220	WUXGA 16:10	Throw ratio Lens shift V/H	–	0.35:1 + 25% / ± 15%	0.40 - 0.51:1 ± 60% / ± 18%	0.40 - 0.51:1 ± 60% / ± 18%	0.48 - 0.57:1 ± 24% / ± 10%	0.47 - 0.64:1 ± 60% / ± 18%	0.64 - 0.77:1 ± 60 / ± 18%	0.64 - 0.90:1 ± 60 / ± 18%	0.77 - 1.07:1 ± 24% / ± 10%
EB-PQ2000 Series EB-PQ2008 to EB-PQ2220	4K 16:9	Throw ratio Lens shift V/H	–	0.34:1 + 30% / ± 13%	0.39 - 0.49:1 ± 64% / ± 16%	0.39 - 0.49:1 ± 64% / ± 16%	0.46 - 0.56:1 ± 25% / ± 8%	0.46 - 0.62:1 ± 64% / ± 16%	0.62 - 0.75:1 ± 64% / ± 16%	0.62 - 0.87:1 ± 64% / ± 16%	0.74 - 1.04:1 ± 25% / ± 8%
EB-XQ2030B	4K 16:9	Throw ratio Lens shift V/H	–	0.34:1 + 30% / ± 13%	0.39 - 0.49:1 ± 64% / ± 16%	0.39 - 0.49:1 ± 64% / ± 16%	0.46 - 0.56:1 ± 25% / ± 8%	0.46 - 0.62:1 ± 64% / ± 16%	0.62 - 0.75:1 ± 64% / ± 16%	0.62 - 0.87:1 ± 64% / ± 16%	–
		Weight	3.5kg	5kg	4.3kg	4.1kg	2.3kg	3.22kg	3.1kg	3.3kg	1.45kg



Model			ELPLW08 ¹ ELPLW08H	ELPLW06 ¹ ELPLW06H	ELPLM08	ELPLM15 ¹ ELPLM15H	ELPLM10 ¹ ELPLM10H	ELPLM11 ¹ ELPLM11H	ELPLL08	ELPLL11H
EB-PU1000 Series EB-PU1006 to EB-PU1008	WUXGA 16:10	Throw ratio Lens shift V/H	1.18 - 1.66:1 ± 67% / ± 30%	1.62 - 2.22:1 ± 67% / ± 30%	1.44 - 2.32:1 ± 67% / ± 30%	2.16 - 3.48:1 ± 67% / ± 30%	3.32 - 5.06:1 ± 67% / ± 30%	4.85 - 7.38:1 ± 67% / ± 30%	7.21 - 10.11:1 ± 67% / ± 30%	9.90 - 15.52:1 ± 67% / ± 30%
EB-PU2000 Series EB-PU2010 to EB-PU2220	WUXGA 16:10	Throw ratio Lens shift V/H	0.86 - 1.21:1 ± 60% / ± 18%	1.19 - 1.62:1 ± 60% / ± 18%	–	1.57 - 2.56:1 ± 60% / ± 18%	2.42 - 3.71:1 ± 60% / ± 18%	3.54 - 5.41:1 ± 60% / ± 18%	5.27 - 7.41:1 ± 60% / ± 18%	7.23 - 11.38:1 ± 60% / ± 18%
EB-PQ2000 Series EB-PQ2008 to EB-PQ2220	4K 16:9	Throw ratio Lens shift V/H	0.83 - 1.17:1 ± 64% / ± 16%	1.15 - 1.57:1 ± 64% / ± 16%	–	1.52 - 2.47:1 ± 64% / ± 16%	2.34 - 3.59:1 ± 64% / ± 16%	3.42 - 5.23:1 ± 64% / ± 16%	5.09 - 7.16:1 ± 64% / ± 16%	6.99 - 11.00:1 ± 64% / ± 16%
EB-XQ2030B	4K 16:9	Throw ratio Lens shift V/H	0.83 - 1.17:1 ± 64% / ± 16%	1.15 - 1.57:1 ± 64% / ± 16%	–	1.52 - 2.47:1 ± 64% / ± 16%	2.34 - 3.59:1 ± 64% / ± 16%	3.42 - 5.23:1 ± 64% / ± 16%	5.09 - 7.16:1 ± 64% / ± 16%	6.99 - 11.00:1 ± 64% / ± 16%
		Weight	3.1kg	2.95kg	1.2kg	1.9kg	2.2kg	2.2kg	2.2kg	3.5kg

¹ Brightness limited to 20,000lm with EB-XQ2030B.

² ELPLW05 brightness is limited to 12,000lm.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.