

# ISO/IEC 19752 Yield Test Report

EPSON EPL-6200

Cartridge Code:

Developer Cartridge (C13S050166)

Declaration of yield:

Toner cartridge yield: Average Cartridge Yield 6,000 standard pages Declared yield value in accordance with ISO/IEC 19752
--

Average: 6116  
Standard Deviation: 185  
90% Lower Confidence: 6001

Date Tested: 2005/03/28 - 2005/03/29

For questions concerning testing contact:

SEIKO EPSON CORPORATION  
80 Harashinden, Hirooka, Shiojiri-shi, Nagano-ken 399-0785 JAPAN  
Attn: IJP·LP Sales & Marketing Department

Number of cartridges used in testing: 9  
Number of cartridges used in calculations: 9  
Shake procedure used? No  
Print mode: Continuous (500pages/job)  
Number of engines used in testing: 3  
Media used: ASKUL multi paper (super economy)  
Paper size: A4  
Paper feed orientation: Short edge feed  
Computer model: Dell OPTIPLEX GX260  
Driver version: Version. 3.13.0 f m  
Operating system: Microsoft Windows XP  
Application software: Acrobat version 5.0.5  
Test page version: Version 2.1  
Power (off/ on) everyday? Yes

## Cartridge Testing Data

Cartridge	Engine	Temperature			Humidity			Cartridge Yield	Cart Used in Calculatio
		Avg	Max	Min	Avg	Max	Min		
1K8325106A-1	330712	23.7	24.9	22.0	52.8	57.0	48.0	6001	Y
1K8325106A-2	330712	24.1	24.9	22.7	45.0	49.0	39.0	6064	Y
1K8313804A-1	330712	24.8	26.4	23.0	43.5	49.0	36.0	6162	Y
1K8325106A-3	330713	23.6	24.9	21.1	52.5	57.0	47.0	6231	Y
1K8325106A-4	330713	24.2	24.9	22.7	45.6	49.0	40.0	6059	Y
1K8325106A-5	330713	24.8	26.4	23.0	43.9	49.0	36.0	6145	Y
1K8325106A-6	FGHZ061777	24.1	24.9	22.7	45.5	49.0	38.0	6200	Y
1K8325106A-7	FGHZ061777	23.7	25.3	21.8	46.0	50.0	41.0	6430	Y
1K8325106A-8	FGHZ061777	24.4	26.4	22.4	44.0	49.0	38.0	5750	Y

Comments: