

Projector product guide 2024

- Ultra portable/huddle room
- Portable
- Meeting room
- Agile/collaboration space (short throw)
- Agile/collaboration space
- Agile/collaboration space (interactive)
- Large meeting room
- Lighting & Signage
- Installation
- Home

EPSON[®]

Adding collaboration and connectivity to meeting spaces

In business, productivity and efficiency are the keys to success. Epson's display solutions redefine corporate presenting, ensuring efficient and productive meetings in any working environment.

The choice is clear

The right display size for your room maximises audience engagement. Unlike fixed flat panel displays, Epson's scalable solutions project incredible quality displays up to 1000", in multiple aspect ratios. You can also connect multiple projectors to create one large seamless image. And with our more mobile projectors, you are not restricted to one room, one venue, one setting.



Unrestricted viewing

A relaxed viewing environment helps the audience concentrate on the information presented. Epson display solutions are easier on the eye and avoid the glare, blind spots and fingerprints associated with flat panels. They can be viewed without obstruction, from anywhere in the room.



Outstanding quality

Project vivid, engaging images in high resolution, even in brightly lit rooms, with Epson 3LCD technology. The 3LCD panel optical engine at the heart of every Epson projector combines high resolution and high contrast ratios that deliver rich colours and brightness up to three times that of 1-chip DLP projectors².



Hassle-free connectivity

Epson display solutions have comprehensive support and connectivity to match any set up or situation. Our dedicated apps and software are extremely versatile and make it easy for people to make contributions from their own devices.



Minimise maintenance cycles

Epson's fit-and-forget display solutions combine performance with reliability, meaning lower costs, longer life cycles and impressive warranties of up to five years. You can count on up to 17,000 hours life for lamps and up to 30,000 hours for laser light sources³.



Make the sustainable choice

Unlike flat panels, many Epson business projectors are TCO Certified⁴, meeting the world's most comprehensive sustainability certification for IT products. To achieve that, we set the highest standards in our supply chains and factories. This helps your organisation to meet your own social responsibility goals.



Leading the way in visual technology excellence

Your success in the world of visual communications means having the freedom to project brighter, bolder, more creative images in every environment. That's why we work so hard to develop innovative, versatile solutions that take projected visuals to new dimensions.

Exceptional quality


Every Epson projector is the result of our commitment to research and development. We manufacture with superb image quality, ease of operation and total reliability in mind. Our solutions combine high brightness, improved texture and exceptional sharpness to produce powerful, vivid images that can cut through high levels of ambient light, even in large spaces.

Cutting-edge technology

Our projectors add flexibility, quality and creativity in almost every setting. Versatile set-up and connectivity, including 360° installation and easy networking, make great projection simple. Our 3LCD technology produces images up to three times brighter than conventional 1-chip DLP projectors². We have created the world's first 30,000 lumen 3LCD laser projector, the EB-L30000U, using inorganic materials to produce key components in our laser light engine.

A wide range of lenses

Choose from extensive lens options with unparalleled compatibility across our range, each featuring motorised optics, memory function and excellent clarity for images up to 1,000 inches. Find the perfect solution for your installation environment with the same range of 4K quality lenses for projectors with 6,000 to 20,000 lumen brightness. Furthermore, our unique LX series of lenses offer ultra-short throw ratios with zero offset for projectors with brightness levels from 6,000 to 30,000 lumens.





Comprehensive support

As well as building robust products that last, we offer a range of service and support options for our projectors that free you to concentrate on being creative for your customers and audiences. From pre-sales advice to ongoing assistance and access to our experts, our standard and CoverPlus warranties give you extensive ongoing backup that works whenever you need it.

Exceeding audience demands

Modern audiences have high expectations, so expand your creativity at big events and attractions with features including portrait projections and split-screens, 360° installation and projection onto floors, ceilings, corners and curved surfaces. From education and art galleries to digital signage and corporate events, from in-house projector fleets to the rental market, Epson projectors are the smart, effective solution.

Easy maintenance

Dramatically reduce running costs with our highly reliable, heat-resistant projectors. Epson installation projectors are built with long-lasting light sources and filters, offering up to 20,000 hours of maintenance-free performance, and even longer in our extended modes.

Key technologies



Equal White (WLO) and Colour Light Output (CLO)

White brightness alone cannot bring the true colours you see everyday to life. That's why the 3LCD technology found in Epson's projectors delivers an equally high WLO and CLO.

CLO is a metric that measures a projector's ability to deliver colour. Developed by colour scientists using the same approach as WLO (Brightness) measurement, CLO provides a simple, accurate and easy-to-understand way to evaluate projector colour performance.

Epson projectors deliver consistently true-to-life images and rich colours that are up to three times brighter than 1-chip DLP projectors².



Laser light source

Experience astonishing quality and reliability with Epson's new laser light source projectors. The newly developed phosphor wheel and LCD panels are made of inorganic materials with superior light and heat-resistance to deliver excellent reliability. Combining an inorganic phosphor wheel with inorganic LCD panels in a laser projector results in bright, vibrant images for extremely long periods.



4K PRO-UHD

4K PRO-UHD⁵ delivers a bright, amazingly sharp lifelike picture by combining advanced Epson technologies with the ability to accept native 4K content and upscale non-4K content exceeding Full HD resolution.



sound by  YAMAHA

Sound by YAMAHA

Enhance your home entertainment experience with premium sound featuring Yamaha's unique and powerful DSP processing technology AudioEngine™, that delivers stunning 3D surround sound to match the immersive screen size.

(EF-12, EH-LS650B/W and EH-LS800B/W only)

Stream, share and collaborate

Wirelessly stream and share

iProjection for PC / Mac

Wireless Screen Mirroring solution that utilises the built-in Wi-Fi connection of the presenter's device to stream and share content to the projector. Up to 50 devices can be connected to the same projector and up to four can present their content at the same time. The built-in moderator mode allows one user to take control of incoming content from the connected devices.

iProjection App for iOS / Android

Feature-rich BYOD solution for smartphones and tablets allows users to stream and share content, annotate and even control the projector, all directly from their devices. There is also a multi device mode for group collaboration. The built-in moderator mode allows one user to take control of incoming content from the connected devices.

iProjection App for Chromebooks

Supports fully mirrored display of all your Chromebook content including Google Docs, Slides, Sheets and Chrome browser.

Screen Mirroring (Miracast)

Industry-wide standard that enables Screen Mirroring from compatible smartphones, tablets and PCs to enhance BYOD flexibility and provide the freedom of wireless connectivity.

Interactivity and collaboration

Easy Interactive Tools

Gives you annotation and drawing capability on projected images or a whiteboard. You can also perform simple control of your document camera and projector.

Projector management solutions

Monitoring and control

Epson Projector Management

The free-to-download centralised management utility lets IT, facilities and network managers efficiently monitor, control and manage their Epson display solution fleet. The software is also compatible with PLink certified devices. Functions include operation status, error reporting and input source switching. The scheduling feature can power down all the projectors in a building, while error monitoring helps avoid delays and downtime.

Epson Projector Management Connected

Alternatively, there is Epson Projector Management Connected, which offers similar functionality to Epson Projector Management with the added convenience of accessing and managing all of your projectors via a browser rather than an app.

For more information, please visit www.projection-service.epson.com/epm-connected

Epson Projector Professional Tool

You can quickly and easily create perfectly aligned images with the Epson Projector Professional Tool. Our free, downloadable software utility improves the speed of set-up for multi-projector installations. It also gives you access to more advanced settings straight out of the box.

Epson Projector Configuration Tool

This free application for smart devices makes setting up and configuring multiple projectors easy. Simply register the projector's data using NFC connectivity, read and edit the settings in the app and then upload the settings to a fleet of projectors without even needing to power the projectors on.




Content management

Epson Projector Content Manager

Create playlists using photos, videos, shape filters and effects, which can be scheduled and saved to an external storage device for cableless content playback directly on the projector.

Epson Creative Projection

Create custom content on your smartphone or tablet, with ease. Enliven rooms and product displays by combining your photos and movies with the app's built-in templates and stamps.

| | Ultra portable/huddle room | | Portable |
|---|--|---|--|
| Model | EB-1780W | EB-1795F | CO-W01 |
| |  |  |  |
| Resolution | WXGA (1280 x 800) | Full HD (1920 x 1080) | WXGA (1280 x 800) |
| Native aspect | 16:10 | 16:9 | 16:10 |
| Colour Light Output (lumens) normal / eco | 3,000 / 1,900 | 3,200 / 1,900 | 3,000 / 2,000 |
| Contrast ratio | 10,000:1 | 10,000:1 | - |
| Lightsource | Lamp | Lamp | Lamp |
| Lightsource life (hours) normal / eco | 4,000 / 7,000 | 4,000 / 7,000 | 6,000 / 12,000 |
| Throw ratio in native aspect | 1.0 - 1.26:1 | 1.02 - 1.23:1 | 1.27 - 1.71:1 |
| Scalable image size (diagonal) | 30 - 300" | 30 - 300" | 25 - 378" |
| Zoom | Optical x1.2 | Optical x1.2 | Digital x1.35 |
| Vertical keystone | Automatic ±30° | Automatic ±30° | Manual ±30° |
| Horizontal keystone | Manual ±30° | Automatic ±20° | Manual ±30° |
| Lens shift | N/A | N/A | N/A |
| Speaker output | 1W | 1W | 5W Mono |
| Connectivity | VGA in, Composite RCA, USB Type B, USB Type A, HDMI | VGA in, Composite RCA, USB Type B, USB Type A, HDMI, Screen Mirroring (Miracast) | USB Type B, USB Type A, HDMI |
| Audio connectivity | Stereo mini in | Stereo mini in | N/A |
| Networking | Wireless LAN | Wireless LAN | Wireless LAN adapter - sold separately |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook | N/A |
| Other features | 3-in-1 USB display, A/V mute slide, DICOM SIM colour mode, Split screen, PC-free presentation, Kensington lock, Wireless LAN security, Password protection, Carry case | 3-in-1 USB display, A/V mute slide, DICOM SIM colour mode, Split screen, PC-free presentation, Auto screen fit and Auto focus, Real time keystone correction, Gesture Presenter, NFC, Kensington lock, Wireless LAN security, Password protection, Carry case | A/V mute, Built-in speaker, Horizontal and vertical keystone correction, MHL audio/video interface, Quick Corner |
| Noise (dB) normal / eco | 39 / 30 | 39 / 30 | 38 / 29 |
| Weight (kg) | 1.8 | 1.8 | 2.4 |
| Dimensions exc. feet (W x D x H mm) | 292 x 213 x 44 | 292 x 213 x 44 | 295 x 211 x 87 |
| Power consumption normal / eco | 277W / 200W | 295W / 208W | 270W / 214W |
| Power consumption standby, comm. off | 0.34W | 0.34W | 0.5W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | Projector - 5 years Lamp - 5 years / 1,000hrs | Projector - 5 years Lamp - 5 years / 1,000hrs | Projector - 2 years |

| | Portable | | |
|---|--|--|--|
| Model | EB-W06 | EB-FH06 | EB-W51 |
| |  |  |  |
| Resolution | WXGA (1280 x 800) | Full HD (1920 x 1080) | WXGA (1280 x 800) |
| Native aspect | 16:10 | 16:9 | 16:10 |
| Colour Light Output (lumens) normal / eco | 3,700 / 2,400 | 3,500 / 2,300 | 4,000 / 2,600 |
| Contrast ratio | 16,000:1 | 16,000:1 | 16,000:1 |
| Lightsource | Lamp | Lamp | Lamp |
| Lightsource life (hours) normal / eco | 12,000 / 6,000 | 12,000 / 6,000 | 12,000 / 6,000 |
| Throw ratio in native aspect | 1.30 - 1.56:1 | 1.22 - 1.47:1 | 1.30 - 1.56:1 |
| Scalable image size (diagonal) | 33 - 320* | 34 - 332* | 33 - 320* |
| Zoom | Optical x1.2 | Optical x1.2 | Optical x1.2 |
| Vertical keystone Horizontal keystone | Automatic ±30° Manual ±30° | Automatic ±30° Manual ±30° | Automatic ±30° Manual ±30° |
| Lens shift | N/A | N/A | N/A |
| Speaker output | 2W Mono | 2W Mono | 2W Mono |
| Connectivity | HDMI in, VGA in, USB 2.0 Type A, 2.0 Type Mini-B | HDMI in, VGA in, USB 2.0 Type B | HDMI in, VGA in, USB 2.0 Type A, 2.0 Type Mini-B |
| Audio connectivity | RCA pair in | RCA pair in | RCA pair in |
| Networking | Wireless LAN adapter - sold separately | Wireless LAN adapter - sold separately | Wireless LAN adapter - sold separately |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management |
| Other features | A/V mute slide, Horizontal keystone slider, Quick corner correction, Split screen, Auto source search, Kensington lock, Padlock, Security cable hole, Password protection, Optional carry case | A/V mute slide, Horizontal keystone slider, Quick corner correction, Split screen, Auto source search, Kensington lock, Padlock, Security cable hole, Password protection, Optional carry case | A/V mute slide, Horizontal keystone slider, Quick corner correction, Split screen, Auto source search, QR code function, Kensington lock, Padlock, Security cable hole, Stream and share features, Password protection, Carry case |
| Noise (dB) normal / eco | 37 / 28 | 37 / 28 | 37 / 28 |
| Weight (kg) | 2.5 | 2.7 | 2.5 |
| Dimensions exc. feet (W x D x H mm) | 302 x 237 x 82 | 302 x 252 x 92 | 302 x 237 x 82 |
| Power consumption normal / eco | 327W / 225W | 327W / 225W | 327W / 225W |
| Power consumption standby, comm. off | 0.3W | 0.3W | 0.3W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | Projector - 2 years Lamp - 1 year / 1,000hrs | Projector - 2 years Lamp - 1 year / 1,000hrs | Projector - 2 years Lamp - 1 year / 1,000hrs |

Portable

EB-FH52




CO-FH01

CO-FH02

EB-E20






| | | | |
|--|--|---|---|
| Full HD (1920 x 1080) | Full HD (1920 x 1080) | Full HD (1920 x 1080) | XGA (1024 x 768) |
| 16:9 | 16:9 | 16:9 | 4:3 |
| 4,000 / 2,400 | 3,000 / 2,000 | 3,000 / 2,000 | 3,400 / 2,200 |
| 16,000:1 | - | - | 15,000:1 |
| Lamp | Lamp | Lamp | Lamp |
| 5,500 / 12,000 | 6,000 / 12,000 | 6,000 / 12,000 | 6,000 / 12,000 |
| 1.32 - 2.14:1 | 1.19 - 1.61:1 | 1.19-1.61:1 | 1.44 - 1.95:1 |
| 30 - 300° | 26 - 391° | 26 - 391° | 30 - 350° |
| Optical x1.6 | Digital x1.35 | Digital x1.35 | Digital x1.35 |
| Automatic ±30° Manual ±30° | Manual ±30° Manual ±30° | Automatic ±30° Manual ±30° | Manual ±30° Manual ±30° |
| N/A | N/A | N/A | N/A |
| 16W | 5W Mono | 5W Mono | 5W |
| VGA in, HDMI in x2, Composite in, USB 2.0 Type A, USB 2.0 Type B, Screen Mirroring (Miracast) | USB Type B, USB Type A, HDMI | USB Type B, USB Type A, HDMI | VGA in x2, VGA out, HDMI in, Composite in, USB 2.0 Type B, RS-232C |
| RCA pair in | N/A | N/A | Stereo mini out, Stereo mini in (2x), RCA pair in |
| Wireless LAN unit | Wireless LAN adapter - sold separately | Wireless LAN adapter - sold separately | N/A |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | N/A | N/A | N/A |
| A/V mute slide, Horizontal keystone slider, Quick corner correction, Split screen, Auto source search, QR code function, Kensington lock, Padlock, Security cable hole, Stream and share features, Password protection, Carry case | A/V mute, Built-in speaker, Horizontal and vertical keystone correction, MHL audio/video interface, Quick Corner | Android TV, A/V mute, Automatic keystone correction, Built-in speaker, Horizontal and vertical keystone correction, MHL audio/video interface, Quick Corner | A/V mute slide, Horizontal keystone slider, Quick corner correction, Split screen, Auto source search, Kensington lock, Padlock, Security cable hole, Password protection, Optional carry case |
| 37 / 28 | 38 / 29 | 37 / 29 | 37 / 28 |
| 3.1 | 2.4 | 2.6 | 2.7 |
| 309 x 282 x 90 | 295 x 211 x 87 | 320 x 211 x 87 | 302 x 249 x 87 |
| 327W / 225W | 270W / 214W | 270W / 214W | 327W / 225W |
| 0.3W | 0.5W | 0.3W | 0.3W |
| N/A | N/A | N/A | N/A |
| Projector - 3 years Lamp - 3 years / 1,000hrs | Projector - 2 years | Projector - 2 years | Projector - 3 years Lamp - 3 years / 1,000hrs |

| | Meeting room | | |
|---|--|--|--|
| Model | EB-X49 | EB-W49 | EB-982W |
| |  |  |  |
| Resolution | XGA (1024 x 768) | WXGA (1280 x 800) | WXGA (1280 x 800) |
| Native aspect | 4:3 | 16:10 | 16:10 |
| Colour Light Output (lumens) normal / eco | 3,600 / 2,400 | 3,800 / 2,600 | 4,200 / 2,600 |
| Contrast ratio | 16,000:1 | 16,000:1 | 16,000:1 |
| Lightsource | Lamp | Lamp | Lamp |
| Lightsource life (hours) normal / eco / eco2 | 6,000 / 12,000 / N/A | 8,000 / 17,000 / N/A | 6,500 / 17,000 / N/A |
| Throw ratio in native aspect | 1.48 - 1.77:1 | 1.30 - 1.56:1 | 1.38 - 2.24:1 |
| Scalable image size (diagonal) | 30 - 300" | 33 - 320" | 29 - 280" |
| Zoom | Optical x1.2 | Optical x1.2 | Optical x1.6 |
| Vertical keystone Horizontal keystone | Automatic ±30° Manual ±30° | Automatic ±30° Manual ±30° | Automatic ±30° Manual ±30° |
| Lens shift | N/A | N/A | N/A |
| Speaker output | 5W | 5W | 16W |
| Connectivity | VGA in x2, VGA out, HDMI in, Composite in, USB 2.0 Type A, USB 2.0 Type B, RS-232C | VGA in x2, VGA out, HDMI in x2, Composite in, USB 2.0 Type A, USB 2.0 Type B, RS-232C, RJ45 | VGA in x2, VGA out, HDMI in x2, Composite in, USB 2.0 Type A, USB 2.0 Type B, RS-232C |
| Audio connectivity | Stereo mini out, Stereo mini in (2x), RCA pair in | Stereo mini out, Stereo mini in (2x), RCA pair in | Stereo mini out, Stereo mini in (2x), RCA pair in, Microphone input |
| Networking | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management |
| Other features | A/V mute slide, Horizontal keystone slider, Quick corner correction, Split screen, Auto source search, QR code function, Kensington lock, Padlock, Security cable hole, Password protection, Optional carry case | A/V mute slide, Horizontal keystone slider, Quick corner correction, Split screen, Auto source search, QR code function, Kensington lock, Padlock, Security cable hole, Password protection, Optional carry case | A/V mute slide, Horizontal keystone slider, Quick corner correction, Split screen, Auto source search, QR code function, Kensington lock, Padlock, Security cable hole, Password protection, Optional carry case |
| Noise (dB) normal / eco / eco2 | 37 / 28 / N/A | 37 / 28 / N/A | 37 / 28 / N/A |
| Weight (kg) | 2.7 | 2.7 | 3.1 |
| Dimensions exc. feet (W x D x H mm) | 302 x 249 x 87 | 302 x 249 x 87 | 309 x 282 x 90 |
| Power consumption normal / eco / eco2 | 327W / 225W / N/A | 327W / 225W / N/A | 327W / 225W / N/A |
| Power consumption standby, comm. off | 0.3W | 0.3W | 0.3W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | Projector - 3 years Lamp - 3 years / 1,000hrs | Projector - 3 years Lamp - 3 years / 1,000hrs | Projector - 5 years Lamp - 5 years / 1,000hrs |

| Meeting room | Agile/collaboration space (short throw) | | Agile/collaboration space |
|---|--|--|--|
| EB-992F | EB-L210SW | EB-L210SF | EB-685W |
|  |  |  |  |
| Full HD (1920 x 1080) | WXGA (1280 x 800) | Full HD (1920 x 1080) | WXGA (1280 x 800) |
| 16:9 | 16:10 | 16:9 | 16:10 |
| 4,000 / 2,400 | 4,000 / 2,800 | 4,000 / 2,800 | 3,500 / 2,900 |
| 16,000:1 | 2,500,000:1 | 2,500,000:1 | 14,000:1 |
| Lamp | Laser | Laser | Lamp |
| 6,500 / 17,000 / N/A | 20,000 / 30,000 / N/A | 20,000 / 30,000 / N/A | 5,000 / 10,000 / 9,000 |
| 1.32 - 2.14:1 | 0.48 - 0.65:1 | 0.45 - 0.61:1 | 0.28:1 |
| 30 - 300° | 53 - 120° | 56 - 132° | 60 - 100° |
| Optical x1.6 | Digital x1.35 | Digital x1.35 | Digital x1.35 |
| Automatic ±30° Manual ±30° | Manual ±15° Manual ±15° | Manual ±15° Manual ±15° | Manual ±3° Manual ±3° |
| N/A | N/A | N/A | N/A |
| 16W | 16W | 16W | 16W |
| VGA in x2, VGA out, HDMI in x2, Composite in, Screen Mirroring (Miracast), USB 2.0 Type A, USB 2.0 Type B, RS-232C | VGA in x2, VGA out, HDMI x2, USB Type A, USB Type B, Composite RCA, RS-232C, Screen Mirroring (Miracast) | VGA in x2, VGA out, HDMI x2, USB Type A, USB Type B, Composite RCA, RS-232C, Screen Mirroring (Miracast) | VGA in, VGA out (switchable), HDMI x3, Composite RCA, S-Video, USB Type A x2, USB Type B, MHL (via HDMI 1), RS-232C |
| Stereo mini out, Stereo mini in (2x), RCA pair in, Microphone input | Stereo mini in x2, Microphone stereo mini in, Stereo mini out, RCA pair in | Stereo mini in x2, Microphone stereo mini in, Stereo mini out, RCA pair in | Stereo mini in x3, Microphone stereo mini in, Stereo mini out |
| LAN (RJ45) and Wireless LAN unit | LAN (RJ45) and wireless LAN unit | LAN (RJ45) and wireless LAN unit | LAN (RJ45) and optional wireless LAN unit |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management |
| A/V mute slide, Horizontal keystone slider, Quick corner correction, Split screen, Auto source search, QR code function, Kensington lock, Padlock, Security cable hole, Stream and share features, Password protection, Optional carry case | Stream and share features, A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection, optional carry case, Optional wall mount or ceiling mount | Stream and share features, A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection, optional carry case, Optional wall mount or ceiling mount | Home screen, Multi-screen interactivity, Auto source search, A/V mute, Split screen up to 2 sources, 3-in-1 USB display, Copy OSD settings, Auto lamp dimming, PC-free presentation, Padlock, Security cable hole, Kensington lock |
| 37 / 28 / N/A | 37 / 27 / N/A | 37 / 27 / N/A | 35 / 30 / 29 |
| 3.1 | 4.6 | 4.6 | 5.7 |
| 309 x 282 x 90 | 325 x 337 x 90 | 325 x 337 x 90 | 367 x 400 x 149 |
| 327W / 225W / N/A | 260W / 191W / N/A | 260W / 191W / N/A | 354W / 309W / 309W |
| 0.3W | 0.5W | 0.5W | 0.37W |
| N/A | N/A | N/A | N/A |
| Projector - 5 years Lamp - 5 years / 1,000hrs | 5 years / 12,000hrs | 5 years / 12,000hrs | Projector - 5 years Lamp - 5 years / 1,000hrs |

Agile/collaboration space

| Model | EB-760W | EB-770F | EB-810E |
|--|---|--|--|
| |  |  |  |
| Resolution | WXGA (1280 x 800) | Full HD (1920 x 1080) | 4KE (1080p) |
| Native aspect | 16:10 | 16:9 | 16:9 |
| Colour Light Output (lumens) normal / eco | 4,100 / 2,800 | 4,100 / 2,800 | 5,000 / 3,500 |
| Contrast ratio | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Lightsource | Laser | Laser | Laser |
| Lightsource life (hours) normal / eco / eco2 | 20,000 / 30,000 / N/A | 20,000 / 30,000 / N/A | 20,000 / 30,000 / N/A |
| Throw ratio in native aspect | 0.25 - 0.35:1 | 0.25 - 0.35:1 | 0.16:1 |
| Scalable image size (diagonal) | 68 - 138" 16:10 wall mount 60 - 150" 16:10 table mount | 71 - 143" 16:9 wall mount 60 - 150" 16:9 table mount | 80 - 150" wall mount 80 - 160" table mount |
| Zoom | Digital x1.35 | Digital x1.35 | Digital x1.35 |
| Vertical keystone | Manual ±3° | Manual ±3° | N/A |
| Horizontal keystone | Manual ±3° | Manual ±3° | N/A |
| Lens shift | N/A | N/A | N/A |
| Speaker output | 16W | 16W | 2 x 8W |
| Connectivity | VGA in x2, VGA out, HDMI x3, Composite, USB Type A x2, USB Type B, RS-232C, Screen Mirroring (Miracast) | VGA in x2, VGA out, HDMI x3, Composite, USB Type A x2, USB Type B, RS-232C, Screen Mirroring (Miracast) | HDMI In x2, out x1 (HDCP2.3), HDBaseT 1 (HDCP2.3), RS-232C, USB Type-A x2 (1x for data and ELPAP11, 1x for data and 2A power), USB Type B x1, RJ45, Screen Mirroring (Miracast) |
| Audio connectivity | Stereo mini in x3, Microphone stereo mini in, Stereo mini out | Stereo mini in x3, Microphone stereo mini in, Stereo mini out | Digital using HDMI |
| Networking | LAN (RJ45) and wireless LAN unit | LAN (RJ45) and wireless LAN unit | LAN (RJ45) and wireless LAN |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management, Epson Projector Content Manager (Windows/macOS), Epson Creative Projection (iOS), Epson Setting Assistant |
| Other features | Optional mount, Stream and share features, Screen sharing function (client), A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Split screen up to 4 sources, Auto source search, Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection | Optional mount, Edge blending, 16:6 display, Stream and share features, Screen sharing function (client), A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Split screen up to 4 sources, Auto source search, Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection | Optional wall and ceiling mounts, 21:9 optional output, Improved audio chamber for improved bass and overall sound quality. Automated screen distortion correction via app. and share features, Screen sharing function (client), A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Split screen up to 2 sources, Auto source search, Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection |
| Noise (dB) normal / eco / eco2 | 37 / 27 / N/A | 37 / 27 / N/A | 38 / 27 / N/A |
| Weight (kg) | 6.0 | 6.0 | 12.2 |
| Dimensions exc. feet (W x D x H mm) | 359 x 395 x 133 | 359 x 395 x 133 | 695 x 341 x 145 |
| Power consumption normal / eco / eco2 | 263W / 199W / N/A | 263W / 199W / N/A | 440W / N/A / N/A |
| Power consumption standby, comm. off | 0.5W | 0.5W | 0.5W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | 5 years / 12,000hrs | 5 years / 12,000hrs | 5 years / 12,000hrs |

EB-815E



4KE (1080p)
16:9
5,000 / 3,500
2,500,000:1
Laser
20,000 / 30,000 / N/A
0.16:1
80 - 150" wall mount
80 - 160" table mount

Digital x1.35

N/A

N/A

N/A

2 x 8W

HDMI In x2, out x1 (HDCP2.3),
HDBaseT 1 (HDCP2.3), RS-232C, USB
Type-A x2 (1x for data and ELPAP11,
1x for data and 2A power), USB Type
B x1, Screen Mirroring (Miracast)
Wireless LAN

Digital using HDMI

LAN (RJ45) and wireless LAN

Epson iProjection (Windows/Mac),
Epson iProjection App for iOS, Android
and Chromebook, Epson Projector
Management, Epson Projector Content
Manager (Windows/macOS), Epson
Creative Projection (iOS), Epson Setting
Assistant

Optional wall and ceiling mounts,
21:9 optional output, Improved audio
chamber for improved bass and
overall sound quality. Automated
screen distortion correction via app.
and share features, Screen sharing
function (client), A/V mute, Copy OSD
settings, Quick corner correction, PC-
free presentation, Split screen up to 2
sources, Auto source search, Padlock,
Security cable hole, Kensington lock,
Wireless LAN unit lock, Password
protection

38 / 27 / N/A

12.2

695 x 341 x 145

440W / N/A / N/A

0.5W

N/A

5 years / 12,000hrs

EB-685Wi



WXGA (1280 x 800)
16:10
3,500 / 2,900
14,000:1
Lamp
5,000 / 10,000 / 9,000
0.28:1
60 - 100"

Digital x1.35

Manual ±3°

Manual ±3°

N/A

16W

VGA in x2, VGA out (switchable), HDMI
x3, Composite RCA, S-Video, USB
Type A, USB Type B, MHL (via HDMI 1),
RS-232C, Sync in, Sync out

Stereo mini in x3, Microphone stereo
mini in, Stereo mini outLAN (RJ45) and optional wireless
LAN unit

Epson iProjection (Windows/Mac),
Epson iProjection App for iOS, Android
and Chromebook, various collaboration
software tools, Epson Projector
Management

Home screen, Multi-screen
interactivity, Auto source search,
A/V mute, Split screen, 3-in-1 USB
display, Copy OSD settings, Auto
lamp dimming, Pen and touch
interactivity, Auto calibration, PC-free
presentation, Padlock, Security cable
hole, Kensington lock

35 / 30 / 29

5.8

367 x 400 x 149

354W / 309W / 309W

0.37W

N/A

Projector - 5 years
Lamp - 5 years / 1,000hrs

EB-695Wi



WXGA (1280 x 800)
16:10
3,500 / 2,900
14,000:1
Lamp
5,000 / 10,000 / 9,000
0.28:1
60 - 100"

Digital x1.35

Manual ±3°

Manual ±3°

N/A

16W

VGA in x2, VGA out (switchable), HDMI
x3, Composite RCA, S-Video, USB
Type A, USB Type B, MHL (via HDMI 1),
RS-232C, Sync in, Sync out

Stereo mini in x3, Microphone stereo
mini in, Stereo mini outLAN (RJ45) and optional wireless
LAN unit

Epson iProjection (Windows/Mac),
Epson iProjection App for iOS, Android
and Chromebook, various collaboration
software tools, Epson Projector
Management

Home screen, Multi-screen
interactivity, Auto source search,
A/V mute, Split screen, 3-in-1 USB
display, Copy OSD settings, Auto
lamp dimming, Pen and touch
interactivity, Auto calibration, PC-free
presentation, Padlock, Security cable
hole, Kensington lock

35 / 30 / 29

5.8

367 x 400 x 149




354W / 309W / 309W

0.37W

N/A

Projector - 5 years
Lamp - 5 years / 1,000hrs

Agile/collaboration space (interactive)

| Model | EB-760Wi | EB-770Fi | EB-1485Fi |
|---|--|---|---|
| |  |  |  |
| Resolution | WXGA (1280 x 800) | Full HD (1920 x 1080) | Full HD (1366 x 768 x 2) |
| Native aspect | 16:10 | 16:9 | 16:9 |
| Colour Light Output (lumens) normal / eco | 4,100 / 2,800 | 4,100 / 2,800 | 5,000 / 3,500 |
| Contrast ratio | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Lightsource | Laser | Laser | Laser |
| Lightsource life (hours) normal / eco | 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 |
| Throw ratio in native aspect | 0.27 - 0.37:1 | 0.25 - 0.35:1 | 0.27:1 |
| Scalable image size (diagonal) | 65 - 100" | 65 - 100" / 16:9 aspect 60 - 110" / 16:6 aspect | 65 - 100" / 16:9 aspect 61 - 120" / 16:6 aspect |
| Zoom | Digital x1.35 | Digital x1.35 | Digital x1.35 |
| Vertical keystone | Manual ±3° | Manual ±3° | Manual ±3° |
| Horizontal keystone | Manual ±3° | Manual ±3° | Manual ±3° |
| Lens shift | N/A | N/A | N/A |
| Speaker output | 16W | 16W | 2 x 8W |
| Connectivity | VGA in x2, VGA out, HDMI x3, Composite, USB Type A x2, USB Type B x2, RS-232C, Sync in, Sync out, Touch unit control, Screen Mirroring (Miracast) | VGA in x2, VGA out, HDMI x3, Composite, USB Type A x2, USB Type B x2, RS-232C, Sync in, Sync out, Touch unit control, Screen Mirroring (Miracast) | VGA in, VGA out, HDMI x3, USB Type A x2, USB Type B, HDMI-out, RS-232C, Sync in, Sync out, Touch unit control, Screen Mirroring (Miracast), HDBaseT |
| Audio connectivity | Stereo mini in x3, Microphone stereo mini in, Stereo mini out | Stereo mini in x3, Microphone stereo mini in, Stereo mini out | Stereo mini in x3, Microphone stereo mini in, Stereo mini out |
| Networking | LAN (RJ45) and wireless LAN unit | LAN (RJ45) and wireless LAN unit | LAN (RJ45) and wireless LAN unit |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, various collaboration software tools, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, various collaboration software tools, Epson Projector Management | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, various collaboration software tools, Epson Projector Management |
| Other features | Pen interactivity and optional touch, Optional mount, Interactive home screen, Stream and share features, Screen sharing function (client), Whiteboard mode with document export support, Sliding split screen, split screen up to 4 sources, A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Auto source search, Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection | Pen interactivity and optional touch, Optional mount, edge-blending, 16:6 display, Interactive home screen, Stream and share features, Screen sharing function (client), Whiteboard mode with document export support, Sliding split screen, split screen up to 4 sources, A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Auto source search, Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection | Constant brightness mode, 16:6 display, Interactive home screen, Stream and share features, DuoLink interactivity, Screen sharing function (server/client), Whiteboard mode with document export support, Multiple display via Daisy chain, Auto power on, Auto source search, A/V mute, Sliding split screen, split screen up to 4 sources, Copy OSD settings, Pen and touch interactivity, Auto calibration, DICOM SIM colour mode, HDBaseT external control pad, Set-up wizard |
| Noise (dB) normal / eco | 37 / 27 | 37 / 27 | 36 / 27 |
| Weight (kg) | 6.0 | 6.0 | 9.7 |
| Dimensions exc. feet (W x D x H mm) | 359 x 395 x 133 | 357 x 395 x 165 | 458 x 209.5 x 375 |
| Power consumption normal / eco | 263W / 199W | 263W / 199W | 366W / 262W |
| Power consumption standby, comm. off | 0.5W | 0.5W | 0.5W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | 5 years / 12,000hrs | 5 years / 12,000hrs | 5 years / 12,000hrs |

Large meeting room

EB-2250U



WUXGA (1920 x 1200)
 16:10
 5,000 / 3,800

 15,000:1
 Lamp
 5,000 / 10,000
 1.38 - 2.28:1
 50 - 300°

 Optical x1.6
 Automatic ±30°
 Automatic ±20°
 N/A
 16W
 VGA in x2, VGA out,
 HDMI x2, Composite RCA,
 USB Type A, USB Type B,
 RS-232C, MHL (via HDMI 1)

 RCA pair in, Stereo mini
 in x2, Stereo mini out

 LAN (RJ45) and optional wireless
 LAN unit

 Epson iProjection (Windows/Mac),
 Epson iProjection App for iOS, Android
 and Chromebook, Epson Projector
 Management

 Home Screen, Gesture Presenter,
 A/V mute, screen fit, Split screen,
 Auto power on, DICOM colour mode,
 DCDi by Faroudja, Schedule function,
 Focus help,
 Real time keystone correction, Quick
 corner, PC-free presentation, 3-in-1
 USB display, Padlock, Security bar,
 Kensington lock

 39 / 29
 4.6
 377 x 291.5 x 110
 405W / 323W
 0.31W
 N/A
 Projector - 5 years
 Lamp - 5 years / 1,000hrs

EB-L210W



WXGA (1280 x 800)
 16:10
 4,500 / 3,100

 2,500,000:1
 Laser
 20,000 / 30,000
 1.41 - 2.26:1
 30 - 300°

 Optical x1.62
 Automatic ±30°
 Automatic ±30°
 N/A
 16W
 VGA in (2x), VGA out, Composite in,
 HDMI in x2, USB Type A (2A), USB
 Type B, RS-232C, Screen Mirroring
 (Miracast)

 Stereo mini out, Stereo mini in (2x),
 RCA pair in,
 Microphone input

 LAN (RJ45) and wireless LAN unit

 Epson Projector Management, Epson
 iProjection (Windows/Mac/Chrome/
 iOS/Android), USB Display (Windows/
 Mac), Epson Wireless Transmitter
 Settings (Windows/Mac)

 A/V mute slide, Horizontal keystone
 slider, Quick corner correction, PC-
 free, Split screen - up to 4 sources,
 Auto source search, QR code function,
 Kensington lock, Padlock, Security
 cable hole, Wireless LAN security,
 Password protection, VESA mount,
 Optional carry case,

 37 / 27
 4.2
 325 x 299 x 90
 260W / 191W
 0.5W
 N/A
 5 years / 12,000hrs

EB-L260F



Full HD (1920 x 1080)
 16:9
 4,600 / 3,200

 2,500,000:1
 Laser
 20,000 / 30,000
 1.32 - 2.12:1
 31 - 310°

 Optical x1.62
 Automatic ±30°
 Automatic ±30°
 N/A
 16W
 VGA in x2, VGA out, Composite in,
 HDMI in x2, USB Type A (2A), USB
 Type B, RS-232C, Screen Mirroring
 (Miracast)




 Stereo mini in x2, Stereo mini out

 LAN (RJ45), built-in wireless LAN unit

 Epson Projector Management, Epson
 iProjection (Windows/Mac/Chrome/iOS/
 Android), USB Display (Windows/Mac),
 Epson Projector Content Manager
 (Windows/Mac), Epson Creative
 Projection (iOS), Epson Wireless
 Transmitter Settings (Windows/Mac)

 Edge-blending, 16:6 display, 21:9
 display, PC-free, A/V mute slide,
 Horizontal keystone slider, Quick
 corner correction, PC-free, Split screen
 - up to 4 sources, Auto source search,
 QR code function, Kensington lock,
 Padlock, Security cable hole, Wireless
 LAN security, Content playback,
 Password protection, DICOM SIM,
 includes cable cover, VESA mount,
 Optional carry case

 37 / 27
 4.2
 325 x 299 x 90
 260W / 191W
 0.5W
 N/A
 5 years / 12,000hrs

| | Large meeting room | | |
|---|---|---|---|
| Model | EB-L520U | EB-L720U | EB-L530U |
| |  |  |  |
| Resolution | WUXGA (1920 x 1200) | WUXGA (1920 x 1200) | WUXGA (1920 x 1200) |
| Native aspect | 16:10 | 16:10 | 16:10 |
| Colour Light Output (lumens) normal / eco | 5,200 / 3,640 | 7,000 / 4,900 | 5,200 / 3,640 |
| Contrast ratio | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Lightsource | Laser | Laser | Laser |
| Lightsource life (hours) normal / eco | 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 |
| Throw ratio in native aspect | 1.35 - 2.20:1 | 1.35 - 2.20:1 | 1.35 - 2.20:1 |
| Scalable image size (diagonal) | 50 - 500" | 50 - 500" | 50 - 500" |
| Zoom | Optical x1.6 | Optical x1.6 | Optical x1.6 |
| Vertical keystone | Manual $\pm 30^\circ$ | Manual $\pm 30^\circ$ | Manual $\pm 30^\circ$ |
| Horizontal keystone | Manual $\pm 30^\circ$ | Manual $\pm 30^\circ$ | Manual $\pm 30^\circ$ |
| Lens shift | N/A | N/A | $\pm 50\%$ Vertical $\pm 20\%$ Horizontal |
| Speaker output | 10W | 10W | 10W |
| Connectivity | VGA in x2, VGA out, HDMI in x2, HDBaseT, Miracast (when use ELPAP11), USB Type A, USB Type B, RS-232C | VGA in x2, VGA out, HDMI in x2, HDBaseT, Miracast (when use ELPAP11), USB Type A, USB Type B, RS-232C | HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast) |
| Audio connectivity | Stereo mini out, Stereo mini in (2x) | Stereo mini out, Stereo mini in (2x) | Stereo mini in x2, Stereo mini out |
| Networking | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45), built-in wireless LAN unit |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management, Epson Projector Content Manager | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management, Epson Projector Content Manager | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection |
| Other features | A/V mute, Arc correction, Edge blending, PC Free, Quick corner, Screen share, Source function, Ultra-wide display (16:6), Home Screen, A/V mute, Split screen - up to 4 sources, Auto power on, Auto source search, Quick startup, Padlock, Security cable hole, Kensington lock, 360° installation, Wireless LAN unit lock | A/V mute, Arc correction, Edge blending, PC Free, Quick corner, Screen share, Source function, Ultra-wide display (16:6), Home Screen, A/V mute, Split screen - up to 4 sources, Auto power on, Auto source search, Quick startup, Padlock, Security cable hole, Kensington lock, 360° installation, Wireless LAN unit lock | A/V mute, USB content playback for source-free signage, Edge blending, Daisy chain multi-projection, Point and Arc correction, Schedule function, Split screen, Auto source search, Copy OSD settings, Padlock, Security cable hole, Kensington lock, 360° installation, Cable cover included |
| Noise (dB) normal / eco | 31 / 23 | 39 / 27 | 31 / 23 |
| Weight (kg) | 7.7 | 7.8 | 8.2 |
| Dimensions exc. feet (W x D x H mm) | 440 x 304 x 122 | 440 x 304 x 122 | 440 x 304 x 122 |
| Power consumption normal / eco | 293W / 223W | 345W / 258W | 293W / 223W |
| Power consumption standby, comm. off | 0.3W | 0.3W | 0.3W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | 3 years | 3 years | 3 years |

Large meeting room

EB-L630U




EB-L730U

EB-L735U

EB-L630SU



| | | | |
|--|--|---|--|
| WUXGA (1920 x 1200) | WUXGA (1920 x 1200) | WUXGA (1920 x 1200) | WUXGA (1920 x 1200) |
| 16:10 | 16:10 | 16:10 | 16:10 |
| 6,200 / 4,340 | 7,000 / 4,900 | 7,000 / 4,900 | 6,000 / 4,200 |
| 2,500,000:1 | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Laser | Laser | Laser | Laser |
| 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 |
| 1.35 - 2.20:1 | 1.35 - 2.20:1 | 1.35 - 2.20:1 | 0.8:1 |
| 50 - 500* | 50 - 500* | 50 - 500* | 50 - 200* |
| Optical x1.6 | Optical x1.6 | Optical x1.6 | Digital x1.35 |
| Manual ±30° Manual ±30° | Manual ±30° Manual ±30° | Manual ±30° Manual ±30° | Manual ±30° Manual ±30° |
| ± 50% Vertical ± 20% Horizontal | ± 50% Vertical ± 20% Horizontal | ± 50% Vertical ± 20% Horizontal | ± 50% Vertical ± 20% Horizontal |
| 10W | 10W | 10W | 10W |
| HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast) | HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast) | HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast) | HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast) |
| Stereo mini in x2, Stereo mini out | Stereo mini in x2, Stereo mini out | Stereo mini in x2, Stereo mini out | Stereo mini in x2, Stereo mini out |
| LAN (RJ45), built-in wireless LAN unit | LAN (RJ45), built-in wireless LAN unit | LAN (RJ45), built-in wireless LAN unit | LAN (RJ45), built-in wireless LAN unit |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection |
| A/V mute, USB content playback for source-free signage, Edge blending, Daisy chain multi-projection, Point and Arc correction, Schedule function, Split screen, Auto source search, Copy OSD settings, Padlock, Security cable hole, Kensington lock, 360° installation, Cable cover included | A/V mute, USB content playback for source-free signage, Edge blending, Daisy chain multi-projection, Point and Arc correction, Schedule function, Split screen, Auto source search, Copy OSD settings, Padlock, Security cable hole, Kensington lock, 360° installation, Cable cover included | A/V mute, USB content playback for source-free signage, Edge blending, Daisy chain multi- projection, Point and Arc correction, Schedule function, Split screen, Auto source search, Copy OSD settings, Padlock, Security cable hole, Kensington lock, 360° installation, Cable cover included | A/V mute, USB content playback for source-free signage, Edge blending, Daisy chain multi-projection, Point and Arc correction, Schedule function, Split screen, Auto source search, Copy OSD settings, Padlock, Security cable hole, Kensington lock, 360° installation, Cable cover included |
| 38 / 27 | 38 / 27 | 38 / 27 | 38 / 27 |
| 8.4 | 8.4 | 8.4 | 8.4 |
| 440 x 304 x 122 | 440 x 304 x 122 | 440 x 304 x 122 | 440 x 304 x 122 |
| 345W / 258W | 345W / 258W | 345W / 258W | 345W / 258W |
| 0.3W | 0.3W | 0.3W | 0.3W |
| N/A | N/A | N/A | N/A |
| 3 years | 3 years | 3 years | 3 years |

| | Large meeting room | | |
|---|---|--|--|
| Model | EB-L635SU | EB-L570U | EB-L770U |
| |  |  |  |
| Resolution | WUXGA (1920 x 1200) | 4KE (WUXGA) | 4KE (WUXGA) |
| Native aspect | 16:10 | 16:10 | 16:10 |
| Colour Light Output (lumens) normal / eco | 6,000 / 4,200 | 5,200 / 3,640 | 7,000 / 4,900 |
| Contrast ratio | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Lightsources | Laser | Laser | Laser |
| Lightsources life (hours) normal / eco | 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 |
| Throw ratio in native aspect | 0.8:1 | 1.35 - 2.20:1 | 1.35 - 2.20:1 |
| Scalable image size (diagonal) | 50 - 200" | 50 - 500" | 50 - 500" |
| Zoom | Digital x1.35 | Optical x1.6 | Optical x1.6 |
| Vertical keystone | Manual ±30° | Manual ±30° | Manual ±30° |
| Horizontal keystone | Manual ±30° | Manual ±30° | Manual ±30° |
| Lens shift | ± 50% Vertical ± 20% Horizontal | ± 50% Vertical ± 20% Horizontal | ± 50% Vertical ± 20% Horizontal |
| Speaker output | 10W | 10W | 10W |
| Connectivity | HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast) | HDMI in x2, HDMI out, HDBaseT, RS-232C, USB Type A (2A), USB Type B | HDMI in x2, HDMI out, HDBaseT, RS-232C, USB Type A (2A), USB Type B |
| Audio connectivity | Stereo mini in x2, Stereo mini out | Stereo mini out | Stereo mini out |
| Networking | LAN (RJ45), built-in wireless LAN unit | LAN (RJ45), optional wireless LAN unit | LAN (RJ45), optional wireless LAN unit |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection | Epson Projector Management (Windows), Epson iProjection (Windows/Mac/iOS/Android/Chrome), Epson Projector Professional Tool (Windows/ Mac), Epson Projector Content Manager (Windows/Mac), Epson Creative Projection (iOS) | Epson Projector Management (Windows), Epson iProjection (Windows/Mac/iOS/Android/Chrome), Epson Projector Professional Tool (Windows/ Mac), Epson Projector Content Manager (Windows/Mac), Epson Creative Projection (iOS) |
| Other features | A/V mute, USB content playback for source-free signage, Edge blending, Daisy chain multi-projection, Point and Arc correction, Schedule function, Split screen, Auto source search, Copy OSD settings, Padlock, Security cable hole, Kensington lock, 360° installation, Cable cover included | 4K enhancement, A/V mute, Edge blending, Point correction, Quick Corner, Curved surface correction, Corner wall, Geometry correction memory, Schedule setting, Split screen, Source search, Padlock & Security Cable Hole, Kensington Lock, Wireless LAN Unit Lock, PC Free (Still image/ Movie), Copy OSD settings, Projector Control and Management, 360° installation, Cable cover included, Optional camera for simple stacking and blending | 4K enhancement, A/V mute, Edge blending, Point correction, Quick Corner, Curved surface correction, Corner wall, Geometry correction memory, Schedule setting, Split screen, Source search, Padlock & Security Cable Hole, Kensington Lock, Wireless LAN Unit Lock, PC Free (Still image/ Movie), Copy OSD settings, Projector Control and Management, 360° installation, Cable cover included, Optional camera for simple stacking and blending |
| Noise (dB) normal / eco | 38 / 27 | 31 / 23 | 38 / 27 |
| Weight (kg) | 8.4 | 8.5 | 8.7 |
| Dimensions exc. feet (W x D x H mm) | 440 x 304 x 122 | 440 x 304 x 122 | 440 x 304 x 122 |
| Power consumption normal / eco | 345W / 258W | 312W / 234W | 366W / 268W |
| Power consumption standby, comm. off | 0.3W | 0.5W | 0.5W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | 3 years | 3 years | 3 years |

EB-L775U



| |
|--|
| 4KE (WUXGA) |
| 16:10 |
| 7,000 / 4,900 |
| 2,500,000:1 |
| Laser |
| 20,000 / 30,000 |
| 1.35 - 2.20:1 |
| 50 - 500° |
| Optical x1.6 |
| Manual ±30° Manual ±30° |
| ± 50% Vertical ± 20% Horizontal |
| 10W |
| HDMI in x2, HDMI out, HDBaseT, RS-232C, USB Type A (2A), USB Type B |
| Stereo mini out |
| LAN (RJ45), optional wireless LAN unit |
| Epson Projector Management (Windows), Epson iProjection (Windows/Mac/iOS/ Android/Chrome), Epson Projector Professional Tool (Windows/ Mac), Epson Projector Content Manager (Windows/Mac), Epson Creative Projection (iOS) |
| 4K enhancement, A/V mute, Edge blending, Point correction, Quick Corner, Curved surface correction, Corner wall, Geometry correction memory, Schedule setting, Split screen, Source search, Padlock & Security Cable Hole, Kensington Lock, Wireless LAN Unit Lock, PC Free (Still image/ Movie), Copy OSD settings, Projector Control and Management, 360° installation, Cable cover included, Optional camera for simple stacking and blending |
| 38 / 27 |
| 8.7 |
| 440 x 304 x 122 |
| 366W / 268W |
| 0.5W |
| N/A |
| 3 years |

EV-110



| |
|---|
| WXGA (1280 x 800) |
| 16:10 |
| 2,200 / 1,100 |
| 2,500,000:1 |
| Laser |
| 20,000 / 30,000 |
| 1.38 - 2.19:1 |
| 30 - 150° |
| Optical x1.6 |
| Manual ±45° Manual ±40° |
| N/A |
| N/A |
| SD card, HDMI in, USB Type A (for GPI function or 5V/2A power supply), USB Type B (for firmware updates) |
| Stereo mini out, Bluetooth |
| LAN (RJ45) and wireless LAN |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS and Android, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection |
| Constant brightness mode, Home screen, Schedule function, Auto source search, A/V mute, SD card playback for source free signage, Optional lighting track mount and floor stand, Edge blending, 360° installation, Built-in media player, GPI function |
| 34 / 22 |
| 5.0 |
| Projection unit 175 x 260 x 175 Power supply 361 x 110 x 65 |
| 149W / 122W |
| 0.4W |
| N/A |
| 5 years / 12,000hrs |

EV-115






| |
|---|
| WXGA (1280 x 800) |
| 16:10 |
| 2,200 / 1,100 |
| 2,500,000:1 |
| Laser |
| 20,000 / 30,000 |
| 1.38 - 2.19:1 |
| 30 - 150° |
| Optical x1.6 |
| Manual ±45° Manual ±40° |
| N/A |
| N/A |
| SD card, HDMI in, USB Type A (for GPI function or 5V/2A power supply), USB Type B (for firmware updates) |
| Stereo mini out, Bluetooth |
| LAN (RJ45) and wireless LAN |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS and Android, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection |
| Constant brightness mode, Home screen, Schedule function, Auto source search, A/V mute, SD card playback for source free signage, Optional lighting track mount and floor stand, Edge blending, 360° installation, Built-in media player, GPI function |
| 34 / 22 |
| 5.0 |
| Projection unit 175 x 260 x 175 Power supply 361 x 110 x 65 |
| 149W / 122W |
| 0.4W |
| N/A |
| 5 years / 12,000hrs |

EB-L260F



| |
|---|
| Full HD (1920 x 1080) |
| 16:9 (supports 16:6 and 21:9) |
| 4,600 / 3,200 |
| 2,500,000:1 |
| Laser |
| 20,000 / 30,000 |
| 1.32 - 2.12:1 |
| 31 - 310° |
| Optical x1.62 |
| Manual ±30° Manual ±30° |
| N/A |
| 16W |
| VGA in, VGA out, HDMI x2, Composite, USB Type A x1, USB Type B, RS-232C, Screen Mirroring (Miracast) |
| Stereo mini in x2, Stereo mini out |
| LAN (RJ45), built-in wireless LAN unit |
| Epson iProjection (Windows/ Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection for iOS |
| Optional mount, Edge blending, 16:6 display, Stream and share features, Screen sharing function (client), A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Split screen up to 4 sources, Auto source search, Padlock, Security cable hole, Kensington lock, Password protection, Content playback, Floor & ceiling installation, lighting track installation |
| 37 / 27 |
| 4.2 |
| 325 x 299 x 90 |
| 260W / 191W |
| 0.5W |
| N/A |
| 5 years / 12,000hrs |

| | Lighting & Signage | | |
|---|---|---|---|
| Model | EB-L265F | EB-770F | EB-775F |
| |  |  |  |
| Resolution | Full HD (1920 x 1080) | Full HD (1920 x 1080) | Full HD (1920 x 1080) |
| Native aspect | 16:9 (supports 16:6 and 21:9) | 16:9 | 16:9 |
| Colour Light Output (lumens) normal / eco | 4,600 / 3,200 | 4,100 / 2,800 | 4,100 / 2,800 |
| Contrast ratio | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Lightsource | Laser | Laser | Laser |
| Lightsource life (hours) normal / eco | 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 |
| Throw ratio in native aspect | 1.32 - 2.12:1 | 0.25 - 0.35:1 | 0.25 - 0.35:1 |
| Scalable image size (diagonal) | 31 - 310" | 66 - 143" / 16:9 aspect 66 - 134" / 16:6 aspect | 66 - 143" / 16:9 aspect 66 - 134" / 16:6 aspect |
| Zoom | Optical x1.62 | Digital x1.35 | Digital x1.35 |
| Vertical keystone Horizontal keystone | Manual ±30° Manual ±30° | Manual ±3° Manual ±3° | Manual ±3° Manual ±3° |
| Lens shift | N/A | N/A | N/A |
| Speaker output | 16W | 16W | 16W |
| Connectivity | VGA in, VGA out, HDMI x2, Composite, USB Type A x1, USB Type B, RS-232C, Screen Mirroring (Miracast) | VGA in x2, VGA out, HDMI x3, Composite, USB Type A x2, USB Type B, RS-232C, Screen Mirroring (Miracast) | VGA in x2, VGA out, HDMI x3, Composite, USB Type A x2, USB Type B, RS-232C, Screen Mirroring (Miracast), Wireless LAN |
| Audio connectivity | Stereo mini in x2, Stereo mini out | Stereo mini in x3, Microphone stereo mini in, Stereo mini out | Stereo mini in x3, Microphone stereo mini in, Stereo mini out |
| Networking | LAN (RJ45), built-in wireless LAN unit | LAN (RJ45) and wireless LAN unit | LAN (RJ45) and wireless LAN unit |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection for iOS | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management, Epson Content Manager, Epson Creative Projection for iOS | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Management, Epson Content Manager, Epson Creative Projection for iOS |
| Other features | Optional mount, Edge blending, 16:6 display, Stream and share features, Screen sharing function (client), A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Split screen up to 4 sources, Auto source search, Padlock, Security cable hole, Kensington lock, Password protection, Content playback, Floor & ceiling installation, lighting track installation | Optional mount, Edge blending, 16:6 display, Stream and share features, Screen sharing function (client), A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Split screen up to 4 sources, Auto source search, Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection, Content playback, Ceiling install | Optional mount, Edge blending, 16:6 display, Stream and share features, Screen sharing function (client), A/V mute, Copy OSD settings, Quick corner correction, PC-free presentation, Split screen up to 4 sources, Auto source search, Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection, Content playback, Ceiling install |
| Noise (dB) normal / eco | 37 / 27 | 37 / 27 | 37 / 27 |
| Weight (kg) | 4.2 | 6.0 | 6.0 |
| Dimensions exc. feet (W x D x H mm) | 325 x 299 x 90 | 359 x 395 x 133 | 359 x 395 x 133 |
| Power consumption normal / eco | 260W / 191W | 263W / 199W | 263W / 199W |
| Power consumption standby, comm. off | 0.5W | 0.5W | 0.5W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | 5 years / 12,000hrs | 5 years / 12,000hrs | 5 years / 12,000hrs |

Lighting & Signage

Installation

EB-800F



EB-805F



EB-PU1006W



EB-PU1007W



Full HD (1366 x 768 x 2)

Full HD (1366 x 768 x 2)

WUXGA (1920 x 1200)

WUXGA (1920 x 1200)

16:9

16:9

16:10

16:10

5,000 / 3,500

5,000 / 3,500

6,000 / 4,200

7,000 / 4,900

2,500,000:1

2,500,000:1

2,500,000:1

2,500,000:1

Laser

Laser

Laser

Laser

20,000 / 30,000

20,000 / 30,000

20,000 / 30,000

20,000 / 30,000

0.27 - 0.37:1

0.27 - 0.37:1

1.44 - 2.32:1

1.44 - 2.32:1

65 - 130° / 16:9 aspect
61 - 120° / 16:6 aspect65 - 130° / 16:9 aspect
61 - 120° / 16:6 aspect

50 - 1,000°

50 - 1,000°

Digital x1.35

Digital x1.35

Optical x1.6

Optical x1.6

Manual ±3°

Manual ±3°

Manual ±45°

Manual ±45°

Manual ±3°

Manual ±3°

Manual ±30°

Manual ±30°

N/A

N/A

± 67% Vertical
± 30% Horizontal± 67% Vertical
± 30% Horizontal

2x 8W

2x 8W

N/A

N/A

VGA in x2, VGA out, HDMI
in x3, HDMI out, Composite
in, HDBaseT, RS-232, USB
Type A x2, USB Type BVGA in x2, VGA out, HDMI
in x3, HDMI out, Composite
in, HDBaseT, RS-232, USB
Type A x2, USB Type BHDMI in (HDCP 2.3), DVI in,
HDBaseT, VGA in, RS-232C,
USB Type A, USB Type B
(Service only), Remote, NFCHDMI in (HDCP 2.3), DVI in,
HDBaseT, VGA in, RS-232C,
USB Type A, USB Type B
(Service only), Remote, NFCStereo mini in x2,
Stereo mini outStereo mini in x2,
Stereo mini out

Stereo mini out

Stereo mini out

LAN (RJ45) and optional
wireless LAN unitLAN (RJ45) and optional
wireless LAN unitLAN (RJ45) and optional
wireless LAN unitLAN (RJ45) and optional
wireless LAN unitEpson iProjection (Windows/
Mac), Epson iProjection
App for iOS, Android and
Chromebook, Epson
Projector Management,
Epson Projector Content
Manager, Epson Creative
ProjectionEpson iProjection (Windows/
Mac), Epson iProjection
App for iOS, Android and
Chromebook, Epson
Projector Management,
Epson Projector Content
Manager, Epson Creative
ProjectionEpson iProjection
(Windows/Mac), Epson
iProjection App for iOS,
Android and Chromebook,
Epson Projector
Professional Tool, Epson
Projector Management,
Epson Projector Content
Manager, Epson Creative
Projection, Epson Projector
Config ToolEpson iProjection
(Windows/Mac), Epson
iProjection App for iOS,
Android and Chromebook,
Epson Projector
Professional Tool, Epson
Projector Management,
Epson Projector Content
Manager, Epson Creative
Projection, Epson Projector
Config Tool16:6 display,
Multi-projection via daisy
chain, A/V mute, USB
content playback for source-
free signage, Edge blending,
Point and Arc correction,
Schedule function, Auto
source search, Copy OSD
settings, DICOM colour
mode, Padlock, Security
cable hole, Kensington lock,
360° installation, Optional
wall mount16:6 display,
Multi-projection via daisy
chain, A/V mute, USB
content playback for source-
free signage, Edge blending,
Point and Arc correction,
Schedule function, Auto
source search, Copy OSD
settings, DICOM colour
mode, Padlock, Security
cable hole, Kensington lock,
360° installation, Optional
wall mount4K enhancement, HDR
support, Powered zoom,
Focus and lens shift, Lens
memory, Interchangeable
lens options including zero
offset UST lens, Optional
camera, Portrait projection,
21:9 display, A/V mute,
USB content playback for
source-free signage, Edge
blending, Point correction,
Curved surface and corner
wall correction, 360°
installation4K enhancement, HDR
support, Powered zoom,
Focus and lens shift, Lens
memory, Interchangeable
lens options including zero
offset UST lens, Optional
camera, Portrait projection,
21:9 display, A/V mute,
USB content playback for
source-free signage, Edge
blending, Point correction,
Curved surface and corner
wall correction, 360°
installation

36 / 27

36 / 27

30 / 28

33 / 29

9.2

9.2

15.4

16.3

458 x 210 x 375

458 x 210 x 375

545 x 436 x 164

545 x 436 x 164

366W / 262W

366W / 262W

367W / 310W

431W / 366W

0.5W

0.5W

0.5W

0.5W

N/A

N/A

N/A




N/A

5 years / 12,000hrs

5 years / 12,000hrs

3 years

3 years

| | Installation | | |
|---|--|--|--|
| Model | EB-PU1007B | EB-PU1008W | EB-PU1008B |
| |  |  |  |
| Resolution | WUXGA (1920 x 1200) | WUXGA (1920 x 1200) | WUXGA (1920 x 1200) |
| Native aspect | 16:10 | 16:10 | 16:10 |
| Colour Light Output (lumens) normal / eco | 7,000 / 4,900 | 8,500 / 5,950 | 8,500 / 5,950 |
| Contrast ratio | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Lightsource | Laser | Laser | Laser |
| Lightsource life (hours) normal / eco | 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 |
| Throw ratio in native aspect | 1.44 - 2.32:1 | 1.44 - 2.32:1 | 1.44 - 2.32:1 |
| Scalable image size (diagonal) | 50 - 1,000" | 50 - 1,000" | 50 - 1,000" |
| Zoom | Optical x1.6 | Optical x1.6 | Optical x1.6 |
| Vertical keystone Horizontal keystone | Manual $\pm 45^\circ$ Manual $\pm 30^\circ$ | Manual $\pm 45^\circ$ Manual $\pm 30^\circ$ | Manual $\pm 45^\circ$ Manual $\pm 30^\circ$ |
| Lens shift | $\pm 67\%$ Vertical $\pm 30\%$ Horizontal | $\pm 67\%$ Vertical $\pm 30\%$ Horizontal | $\pm 67\%$ Vertical $\pm 30\%$ Horizontal |
| Speaker output | N/A | N/A | N/A |
| Connectivity | HDMI in (HDCP 2.3), DVI in, HDBaseT, VGA in, RS-232C, USB Type A, USB Type B (Service only), Remote, NFC | HDMI in (HDCP 2.3), DVI in, HDBaseT, VGA in, RS-232C, USB Type A, USB Type B (Service only), Remote, NFC | HDMI in (HDCP 2.3), DVI in, HDBaseT, VGA in, RS-232C, USB Type A, USB Type B (Service only), Remote, NFC |
| Audio connectivity | Stereo mini out | Stereo mini out | Stereo mini out |
| Networking | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool |
| Other features | 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation | 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation | 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation |
| Noise (dB) normal / eco | 33 / 29 | 35 / 30 | 35 / 30 |
| Weight (kg) | 16.3 | 16.3 | 16.3 |
| Dimensions exc. feet (W x D x H mm) | 545 x 436 x 164 | 545 x 436 x 164 | 545 x 436 x 164 |
| Power consumption normal / eco | 431W / 366W | 535W / 452W | 535W / 452W |
| Power consumption standby, comm. off | 0.5W | 0.5W | 0.5W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | 3 years | 3 years | 3 years |

Installation

EB-PQ2008W



EB-PQ2008B



EB-PU2010W






EB-PU2010B



| | | | |
|---|---|--|--|
| 4K (3840 x 2160) ¹ | 4K (3840 x 2160) ¹ | WUXGA (1920 x 1200) | WUXGA (1920 x 1200) |
| 16:9 | 16:9 | 16:10 | 16:10 |
| 8,000 / 5,600 | 8,000 / 5,600 | 10,000 / 7,000 | 10,000 / 7,000 |
| 2,500,000:1 | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Laser | Laser | Laser | Laser |
| 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 |
| 1.52 - 2.47:1 | 1.52 - 2.47:1 | 1.57 - 2.56:1 | 1.57 - 2.56:1 |
| 60 - 1,000° | 60 - 1,000° | 60 - 1,000° | 60 - 1,000° |
| Optical x1.6 | Optical x1.6 | Optical x1.6 | Optical x1.6 |
| Manual ±45° Manual ±30° | Manual ±45° Manual ±30° | Manual ±45° Manual ±30° | Manual ±45° Manual ±30° |
| ± 58% Vertical ± 16% Horizontal | ± 58% Vertical ± 16% Horizontal | ± 60% Vertical ± 18% Horizontal | ± 60% Vertical ± 18% Horizontal |
| N/A | N/A | N/A | N/A |
| HDMI in x2, HDMI out, HDBaseT, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC | HDMI in x2, HDMI out, HDBaseT, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC | HDMI in (HDCP 2.3), DVI in, HDBaseT, SDI in, SDI out, VGA in, RS-232C, USB Type A, USB Type B (Service only), Remote, NFC | HDMI in (HDCP 2.3), DVI in, HDBaseT, SDI in, SDI out, VGA in, RS-232C, USB Type A, USB Type B (Service only), Remote, NFC |
| Stereo mini out | Stereo mini out | Stereo mini out | Stereo mini out |
| LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool |
| 4K Crystal Motion, HDR support, Powered zoom, focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, Back up source function, 120Hz support | 4K Crystal Motion, HDR support, Powered zoom, focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, Back up source function, 120Hz support | 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation | 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation |
| 37 / 30 | 37 / 30 | 37 / 30 | 37 / 30 |
| Less than 20 | Less than 20 | 16.8 | 16.8 |
| 545 x 436 x 164 | 545 x 436 x 164 | 545 x 436 x 164 | 545 x 436 x 164 |
| 515W / 385W | 515W / 385W | 535W / 452W | 535W / 452W |
| 0.5W | 0.5W | 0.5W | 0.5W |
| N/A | N/A | N/A | N/A |
| 3 years | 3 years | 3 years | 3 years |

¹ Maximum physical resolution using 4K Crystal Motion technology.

Specifications vary by lens, please refer to lens specifications. **EB-PQ model specifications are preliminary and subject to change**

| | Installation | | |
|---|---|---|---|
| Model | EB-PQ2010W | EB-PQ2010B | EB-PU2113W |
| |  |  |  |
| Resolution | 4K (3840 x 2160) ¹ | 4K (3840 x 2160) ¹ | WUXGA (1920 x 1200) |
| Native aspect | 16:9 | 16:9 | 16:10 |
| Colour Light Output (lumens) normal / eco | 10,000 / 7,000 | 10,000 / 7,000 | 13,000 / 9,100 |
| Contrast ratio | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Lightsource | Laser | Laser | Laser |
| Lightsource life (hours) normal / eco | 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 |
| Throw ratio in native aspect | 1.52 - 2.47:1 | 1.52 - 2.47:1 | 1.57 - 2.56:1 |
| Scalable image size (diagonal) | 60 - 1,000" | 60 - 1,000" | 60 - 1,000" |
| Zoom | Optical x1.6 | Optical x1.6 | Optical x1.6 |
| Vertical keystone | Manual ±45° | Manual ±45° | Manual ±45° |
| Horizontal keystone | Manual ±30° | Manual ±30° | Manual ±30° |
| Lens shift | ± 58% Vertical ± 16% Horizontal | ± 58% Vertical ± 16% Horizontal | ± 60% Vertical ± 18% Horizontal |
| Speaker output | N/A | N/A | N/A |
| Connectivity | HDMI in x2, HDMI out, 12G-SDI in, 12G-SDI out, HDBaseT, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC | HDMI in x2, HDMI out, 12G-SDI in, 12G-SDI out, HDBaseT, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC | HDMI in (HDCP 2.3), DVI in, HDBaseT, VGA in, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC |
| Audio connectivity | Stereo mini out | Stereo mini out | Stereo mini out |
| Networking | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool |
| Other features | 4K Crystal Motion, HDR support, Powered zoom, focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, Back up source function, 120Hz support | 4K Crystal Motion, HDR support, Powered zoom, focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, Back up source function, 120Hz support | 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, IP5X certified ² |
| Noise (dB) normal / eco | 40 / 30 | 40 / 30 | 34 / 29 |
| Weight (kg) | Less than 20 | Less than 20 | 23.8 |
| Dimensions exc. feet (W x D x H mm) | 545 x 436 x 164 | 545 x 436 x 164 | 586 x 492 x 185 |
| Power consumption normal / eco | 609W / 440W | 609W / 440W | 864W / 633W |
| Power consumption standby, comm. off | 0.5W | 0.5W | 0.5W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | 3 years | 3 years | 3 years |

¹ Maximum physical resolution using 4K Crystal Motion technology.

² IP5X certified in accordance with IEC Standard 60529. The IP5X certification is applied to the optical engine and light source module. Specifications vary by lens, please refer to lens specifications. **EB-PQ model specifications are preliminary and subject to change**

Installation

EB-PU2213B



| |
|---|
| WUXGA (1920 x 1200) |
| 16:10 |
| 13,000 / 9,100 |
| 2,500,000:1 |
| Laser |
| 20,000 / 30,000 |
| 1.57 - 2.56:1 |
| 60 - 1,000" |
| Optical x1.6 |
| Manual ±45° Manual ±30° |
| ± 60% Vertical ± 18% Horizontal |
| N/A |
| HDMI in (HDCP 2.3), DVI in, HDBaseT, SDI in, SDI out, VGA in, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC |
| Stereo mini out |
| LAN (RJ45) and optional wireless LAN unit |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool |
| 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Mechanical shutter, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, IP5X certified ² |
| 34 / 29 |
| 23.7 |
| 586 x 492 x 185 |
| 864W / 633W |
| 0.5W |
| N/A |
| 3 years |

EB-PQ2213B



| |
|---|
| 4K (3840 x 2160) ¹ |
| 16:9 |
| 13,000 / 9,100 |
| 2,500,000:1 |
| Laser |
| 20,000 / 30,000 |
| 1.52 - 2.47:1 |
| 60 - 1,000" |
| Optical x1.6 |
| Manual ±45° Manual ±30° |
| ± 58% Vertical ± 16% Horizontal |
| N/A |
| HDMI in x2, HDMI out, 12G-SDI in, 12G-SDI out, HDBaseT, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC |
| Stereo mini out |
| LAN (RJ45) and optional wireless LAN unit |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool |
| 4K Crystal Motion, HDR support, Powered zoom, focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, IP5X certified ² , Back up source function, 120Hz support |
| 38 / 34 |
| Less than 30 |
| 586 x 492 x 185 |
| 971W / 701W |
| 0.5W |
| N/A |
| 3 years |

EB-PU2116W



| |
|---|
| WUXGA (1920 x 1200) |
| 16:10 |
| 16,000 / 11,200 |
| 2,500,000:1 |
| Laser |
| 20,000 / 30,000 |
| 1.57 - 2.56:1 |
| 60 - 1,000" |
| Optical x1.6 |
| Manual ±45° Manual ±30° |
| ± 60% Vertical ± 18% Horizontal |
| N/A |
| HDMI in (HDCP 2.3), DVI in, HDBaseT, VGA in, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC |
| Stereo mini out |
| LAN (RJ45) and optional wireless LAN unit |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool |
| 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, IP5X certified ² |
| 38 / 34 |
| 24.3 |
| 586 x 492 x 185 |
| 1083W / 773W |
| 0.5W |
| N/A |
| 3 years |




EB-PU2216B



| |
|---|
| WUXGA (1920 x 1200) |
| 16:10 |
| 16,000 / 11,200 |
| 2,500,000:1 |
| Laser |
| 20,000 / 30,000 |
| 1.57 - 2.56:1 |
| 60 - 1,000" |
| Optical x1.6 |
| Manual ±45° Manual ±30° |
| ± 60% Vertical ± 18% Horizontal |
| N/A |
| HDMI in (HDCP 2.3), DVI in, HDBaseT, SDI in, SDI out, VGA in, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC |
| Stereo mini out |
| LAN (RJ45) and optional wireless LAN unit |
| Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool |
| 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Mechanical shutter, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, IP5X certified ² |
| 38 / 34 |
| 24.2 |
| 586 x 492 x 185 |
| 1083W / 773W |
| 0.5W |
| N/A |
| 3 years |

¹ Maximum physical resolution using 4K Crystal Motion technology.

² IP5X certified in accordance with IEC Standard 60529. The IP5X certification is applied to the optical engine and light source module. Specifications vary by lens, please refer to lens specifications. **EB-PQ model specifications are preliminary and subject to change**

| | Installation | | |
|---|---|---|---|
| Model | EB-PQ2216W | EB-PQ2216B | EB-PU2120W |
| |  |  |  |
| Resolution | 4K (3840 x 2160) ¹ | 4K (3840 x 2160) ¹ | WUXGA (1920 x 1200) |
| Native aspect | 16:9 | 16:9 | 16:10 |
| Colour Light Output (lumens) normal / eco | 16,000 / 11,200 | 16,000 / 11,200 | 20,000 / 14,000 |
| Contrast ratio | 2,500,000:1 | 2,500,000:1 | 2,500,000:1 |
| Lightsource | Laser | Laser | Laser |
| Lightsource life (hours) normal / eco | 20,000 / 30,000 | 20,000 / 30,000 | 20,000 / 30,000 |
| Throw ratio in native aspect | 1.52 - 2.47:1 | 1.52 - 2.47:1 | 1.57 - 2.56:1 |
| Scalable image size (diagonal) | 60 - 1,000" | 60 - 1,000" | 60 - 1,000" |
| Zoom | Optical x1.6 | Optical x1.6 | Optical x1.6 |
| Vertical keystone | Manual ±45° | Manual ±45° | Manual ±45° |
| Horizontal keystone | Manual ±30° | Manual ±30° | Manual ±30° |
| Lens shift | ± 58% Vertical ± 16% Horizontal | ± 58% Vertical ± 16% Horizontal | ± 60% Vertical ± 18% Horizontal |
| Speaker output | N/A | N/A | N/A |
| Connectivity | HDMI in x2, HDMI out, 12G-SDI in, 12G-SDI out, HDBaseT, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC | HDMI in x2, HDMI out, 12G-SDI in, 12G-SDI out, HDBaseT, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC | HDMI in (HDCP 2.3), DVI in, HDBaseT, VGA in, RS-232C, USB Type A x2, USB Type B (Service only), Remote, NFC |
| Audio connectivity | Stereo mini out | Stereo mini out | Stereo mini out |
| Networking | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit | LAN (RJ45) and optional wireless LAN unit |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool | Epson iProjection (Windows/Mac), Epson iProjection App for iOS, Android and Chromebook, Epson Projector Professional Tool, Epson Projector Management, Epson Projector Content Manager, Epson Creative Projection, Epson Projector Config Tool |
| Other features | 4K Crystal Motion, HDR support, Powered zoom, focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, IP5X certified ² , Back up source function, 120Hz support | 4K Crystal Motion, HDR support, Powered zoom, focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Daisy chain multi-projection, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, IP5X certified ² , Back up source function, 120Hz support | 4K enhancement, HDR support, Powered zoom, Focus and lens shift, Lens memory, Interchangeable lens options including zero offset UST lens, Optional camera, Portrait projection, 21:9 display, A/V mute, USB content playback for source-free signage, Edge blending, Point correction, Curved surface and corner wall correction, 360° installation, IP5X certified ² |
| Noise (dB) normal / eco | 45 / 37 | 45 / 37 | 45 / 37 |
| Weight (kg) | Less than 30 | Less than 30 | 24.4 |
| Dimensions exc. feet (W x D x H mm) | 586 x 492 x 185 | 586 x 492 x 185 | 586 x 492 x 185 |
| Power consumption normal / eco | 1145W / 811W | 1145W / 811W | 1301W / 899W |
| Power consumption standby, comm. off | 0.5W | 0.5W | 0.5W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | 3 years | 3 years | 3 years |

¹ Maximum physical resolution using 4K Crystal Motion technology.

² IP5X certified in accordance with IEC Standard 60529. The IP5X certification is applied to the optical engine and light source module. Specifications vary by lens, please refer to lens specifications. **EB-PQ model specifications are preliminary and subject to change**

EB-PU2220B

EB-PQ2220B

EB-L30000U

EH-TW6150



WUXGA (1920 x 1200)

16:10

20,000 / 14,000

2,500,000:1

Laser

20,000 / 30,000

1.57 - 2.56:1

60 - 1,000"

Optical x1.6

Manual ±45°

Manual ±30°

± 60% Vertical
± 18% Horizontal

N/A

HDMI in (HDCP 2.3), DVI
in, HDBaseT, SDI in, SDI
out, VGA in, RS-232C, USB
Type A x2, USB Type B
(Service only), Remote, NFC

Stereo mini out

LAN (RJ45) and optional
wireless LAN unitEpson iProjection
(Windows/Mac), Epson
iProjection App for iOS,
Android and Chromebook,
Epson Projector
Professional Tool, Epson
Projector Management,
Epson Projector Content
Manager, Epson Creative
Projection, Epson Projector
Config Tool4K enhancement, HDR
support, Powered zoom,
Focus and lens shift, Lens
memory, Interchangeable
lens options including zero
offset UST lens, Optional
camera, Daisy chain multi-
projection, Portrait projection,
Mechanical shutter, 21:9
display, A/V mute, USB
content playback for source-
free signage, Edge blending,
Point correction, Curved
surface and corner wall
correction, 360° installation,
IP5X certified²

45 / 37

24.4

586 x 492 x 185

1301W / 899W

0.5W

N/A

3 years

4K (3840 x 2160)¹

16:9

20,000 / 14,000

2,500,000:1

Laser

20,000 / 30,000

1.52 - 2.47:1

60 - 1,000"

Optical x1.6

Manual ±45°

Manual ±30°

± 58% Vertical
± 16% Horizontal

N/A

HDMI in x2, HDMI out,
12G-SDI in, 12G-SDI out,
HDBaseT, RS-232C, USB
Type A x2, USB Type B
(Service only), Remote, NFC

Stereo mini out

LAN (RJ45) and optional
wireless LAN unitEpson iProjection
(Windows/Mac), Epson
iProjection App for iOS,
Android and Chromebook,
Epson Projector
Professional Tool, Epson
Projector Management,
Epson Projector Content
Manager, Epson Creative
Projection, Epson Projector
Config Tool4K Crystal Motion, HDR
support, Powered zoom,
focus and lens shift, Lens
memory, Interchangeable
lens options including zero
offset UST lens, Optional
camera, Daisy chain
multi-projection, Portrait
projection, 21:9 display, A/V
mute, USB content playback
for source-free signage,
Edge blending, Point
correction, Curved surface
and corner wall correction,
360° installation, IP5X
certified², Back up source
function, 120Hz support

48 / 39

Less than 30

586 x 492 x 185

1452W / 1003W

0.5W

N/A

3 years

WUXGA (1920 x 1200)

16:10

30,000 / 21,000

2,500,000:1

Laser

20,000 / 30,000

1.74 - 2.35:1

100 - 1,000"

Optical x1.4

Manual ±45°

Manual ±30°

± 65% Vertical
± 30% Horizontal

N/A

VGA in, VGA out,
DVI in, BNC in, HDBaseT,
HD-SDI, HDMI (HDCP 2.2)

N/A

LAN (RJ45) and optional
wireless LAN unitEpson Projector
Management, Epson
iProjection (Windows/Mac),
Epson iProjection App for
iOS and Android,
Epson Projector
Professional ToolFully sealed optical system,
Interchangeable lens
options, Powered zoom,
Focus and lens shift, Lens
memory, Integrated camera
for colour calibration,
4K enhancement, 360°
installation, Edge blending,
Portrait projection, Epson
Projector Professional Tool.
Also available in white
(EB-L30002U)

49 / 41

63.8

790 x 710 x 299

2,325W / 1,511W

0.5W

N/A

5 years / 20,000hrs

4K PRO-UHD

16:9

2,800 / 1,900

35,000:1

Lamp

4,500 / 7,500

1.32 - 2.15:1

40 - 500"

Optical x1.62

Automatic ±30°

Manual ±30°

Manual ± 60%

10W Mono

USB 2.0 Type B (Service
Only), Jack plug out, HDMI
(HDCP 2.3) (2x), USB 2.0-A

Stereo mini jack

Wireless LAN adapter -
sold separately

N/A

Automatic keystone
correction, Built-in speaker,
Game mode, Horizontal and
vertical keystone correction,
Long lamp life, Quick Corner

36 / 28

4.0




333 x 275 x 131

301W / 231W

0.4W

N/A

Projector - 2 years
Lamp - 3 years / 3,000hrs¹ Maximum physical resolution using 4K Crystal Motion technology.² IP5X certified in accordance with IEC Standard 60529. The IP5X certification is applied to the optical engine and light source module. Specifications vary by lens, please refer to lens specifications. **EB-PQ model specifications are preliminary and subject to change**

| | Home | | |
|---|---|---|---|
| Model | EH-TW6250 | EH-TW7000 | EH-TW7100 |
| |  |  |  |
| Resolution | 4K PRO-UHD | 4K PRO-UHD | 4K PRO-UHD |
| Native aspect | 16:9 | 16:9 | 16:9 |
| Colour Light Output (lumens) normal / eco | 2,800 / 1,900 | 3,000 / 2,000 | 3,000 / 2,000 |
| Contrast ratio | 35,000:1 | 40,000:1 | 100,000:1 |
| Lightsource | Lamp | Lamp | Lamp |
| Lightsource life (hours) normal / eco | 4,500 / 7,500 | 3,500 / 5,000 | 3,500 / 5,000 |
| Throw ratio in native aspect | 1.32 - 2.15:1 | 1.32 - 2.15:1 | 1.32 - 2.15:1 |
| Scalable image size (diagonal) | 40 - 500" | 40 - 500" | 40 - 500" |
| Zoom | Optical x1.62 | Optical x1.6 | Optical x1.6 |
| Vertical keystone Horizontal keystone | Automatic $\pm 30^\circ$ Manual $\pm 30^\circ$ | Manual $\pm 30^\circ$ Manual $\pm 30^\circ$ | Manual $\pm 30^\circ$ Manual $\pm 30^\circ$ |
| Lens shift | Manual $\pm 60\%$ | $\pm 60\%$ Vertical $\pm 24\%$ Horizontal | $\pm 60\%$ Vertical $\pm 24\%$ Horizontal |
| Speaker output | 10W Mono | N/A | 10W |
| Connectivity | USB 2.0 Type B (Service Only), Wireless LAN IEEE 802.11a/b/g/n/ac, Jack plug out, HDMI (HDCP 2.3) | HDMI in (x2), USB 2.0 Type A x2, USB 2.0 Type Mini-B | HDMI in (x2), USB 2.0 Type A x2, USB 2.0 Type Mini-B |
| Audio connectivity | Stereo mini jack | Stereo mini jack, AtpX Bluetooth (SCMS-T) | Stereo mini jack, AtpX Bluetooth (SCMS-T) |
| Networking | Wireless LAN adapter - sold separately | Wireless LAN adapter - sold separately | Wireless LAN adapter - sold separately |
| Epson software solutions | N/A | Epson iProjection (Windows/Mac), Epson iProjection App for iOS and Android | Epson iProjection (Windows/Mac), Epson iProjection App for iOS and Android |
| Other features | Android TV, Automatic keystone correction, Built-in speaker, Game mode, Horizontal and vertical keystone correction, Long lamp life, Quick Corner | 3D depth adjustment, Frame interpolation, Quick Corner, Kensington lock | 3D depth adjustment, Frame interpolation, Quick corner, Kensington lock |
| Noise (dB) normal / eco | 36 / 28 | 32 / 24 | 32 / 24 |
| Weight (kg) | 4.1 | 6.6 | 6.9 |
| Dimensions exc. feet (W x D x H mm) | 333 x 275 x 131 | 410 x 310 x 157 | 410 x 310 x 157 |
| Power consumption normal / eco | 301W / 231W | 368W / 280W | 368W / 280W |
| Power consumption standby, comm. off | 0.4W | 0.2W | 0.5W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | Projector - 2 years Lamp - 3 years / 3,000hrs | 24 months / 3,000hrs carry-in | 24 months / 3,000hrs carry-in |

EH-LS650B

EH-LS650W

EH-LS800W

EH-LS800B



4K PRO-UHD

4K PRO-UHD

4K PRO-UHD

4K PRO-UHD

16:9

16:9

16:9

16:9

3,600 / 1,800

3,600 / 1,800

4,000 / 2,000

4,000 / 2,000

2,500,000:1

2,500,000:1

2,500,000:1

2,500,000:1

Laser

Laser

Laser

Laser

20,000 / 20,000

20,000 / 20,000

20,000 / 20,000

20,000 / 20,000

0.25 - 0.62:1

0.25 - 0.62:1

0.16 - 0.40:1

0.16 - 0.40:1

60 - 120°

60 - 120°

80 - 150°

80 - 150°

Digital x2.5

Digital x2.5

Optical x2.5

Optical x2.5

4 points correction, 8 points correction, 33 x 33 points correction

4 points correction, 8 points correction, 33 x 33 points correction

4 points correction, 8 points correction, 33 x 33 points correction

4 points correction, 8 points correction, 33 x 33 points correction

N/A

N/A

N/A

N/A

Sound by YAMAHA 2.1ch 20W

Sound by YAMAHA 2.1ch 20W

Sound by YAMAHA 2.1ch 20W

Sound by YAMAHA 2.1ch 20W

HDMI x 2 (1 x eARC/ ARC), 1.1 Type A, 2.0 Type Mini-B; Wireless LAN IEEE 802.11a/b/g/n/ac; HDMI (HDCP 2.3)

HDMI x 2 (1 x eARC/ ARC), 1.1 Type A, 2.0 Type Mini-B; Wireless LAN IEEE 802.11a/b/g/n/ac; HDMI (HDCP 2.3)

USB 2.0-A (3x), USB 2.0 Type B (Service Only), Wireless LAN IEEE 802.11a/b/g/n/ac, Jack plug out, Bluetooth, HDMI ARC, HDMI (HDCP 2.3) (3x)

USB 2.0-A (3x), USB 2.0 Type B (Service Only), Wireless LAN IEEE 802.11a/b/g/n/ac, Jack plug out, Bluetooth, HDMI ARC, HDMI (HDCP 2.3) (3x)

HDMI ARC, Stereo mini jack, Bluetooth via Android TV

HDMI ARC, Stereo mini jack, Bluetooth via Android TV

HDMI ARC, Stereo mini jack, Bluetooth via Android TV

HDMI ARC, Stereo mini jack, Bluetooth via Android TV

Via Android TV device

Via Android TV device

Wireless LAN adapter - sold separately

Wireless LAN adapter - sold separately

N/A

N/A

Epson iProjection (Windows/Mac), Epson iProjection App for iOS and Android

Epson iProjection (Windows/Mac), Epson iProjection App for iOS and Android

4K enhancement, Android TV, Auto Power On, Auto source search, Built-in speaker, Chromecast, Digital zoom, Frame interpolation, Long light source life, Quick Corner, Kensington lock, Sound by Yamaha

4K enhancement, Android TV, Auto Power On, Auto source search, Built-in speaker, Chromecast, Digital zoom, Frame interpolation, Long light source life, Quick Corner, Kensington lock, Sound by Yamaha

4K enhancement, Android TV, Auto Power On, Auto source search, Built-in speaker, Chromecast, Digital zoom, Frame interpolation, Long light source life, Quick Corner, Sound by Yamaha

4K enhancement, Android TV, Auto Power On, Auto source search, Built-in speaker, Chromecast, Digital zoom, Frame interpolation, Long light source life, Quick Corner, Sound by Yamaha

36 / 23

36 / 23

32 / 19

32 / 19

7.4

7.4

12.3

12.3

467 x 400 x 153

467 x 400 x 153

695 x 341 x 156

695 x 341 x 156

278W / 186W

278W / 186W

350W / 217W

350W / 217W

2W

2W

2W

2W

N/A

N/A

N/A




N/A

60 months / 12,000hrs carry-in

60 months / 12,000hrs carry-in

60 months / 12,000hrs carry-in

60 months / 12,000hrs carry-in

| | Home | | |
|---|---|--|---|
| Model | EH-TW9400 | EH-LS11000W | EH-LS12000B |
| |  |  |  |
| Resolution | 4K PRO-UHD | 4K (3840 x 2160) | 4K (3840 x 2160) |
| Native aspect | 16:9 | 16:9 | 16:9 |
| Colour Light Output (lumens) normal / eco | 2,600 / N/A | 2,500 / 1,000 | 2,700 / 1,000 |
| Contrast ratio | 1,200,000:1 | 2,500,000:1 | 2,500,000:1 |
| Lightsource | Lamp | Laser | Laser |
| Lightsource life (hours) normal / eco | 3,500 / 5,000 | 20,000 / 20,000 | 20,000 / 20,000 |
| Throw ratio in native aspect | 1.35 - 2.84:1 | 1.35 - 2.84:1 | 1.35 - 2.84:1 |
| Scalable image size (diagonal) | 30 - 300" | 50 - 300" | 50 - 300" |
| Zoom | Motorised optical x2.1 | Motorised optical x2.1 | Motorised optical x2.1 |
| Vertical keystone Horizontal keystone | Manual ±30° N/A | Manual ± 30° Manual ± 30° | Manual ± 30° Manual ± 30° |
| Lens shift | Powered ± 96.3% Vertical Powered ± 47.1% Horizontal | Powered ± 96.3% Vertical Powered ± 47.1% Horizontal | Powered ± 96.3% Vertical Powered ± 47.1% Horizontal |
| Speaker output | N/A | N/A | N/A |
| Connectivity | VGA in, HDMI x2 (HDMI 1 - HDCP2.2 and 1.4), USB Type A, USB Type B, RS-232C, Trigger out | USB 1.1 Type A (2x), USB 2.0 Type Mini-B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Trigger out, HDMI ARC, HDMI (HDCP 2.3) (2x) | USB 1.1 Type A (2x), USB 2.0 Type Mini-B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Trigger out, HDMI ARC, HDMI (HDCP 2.3) (2x) |
| Audio connectivity | N/A | N/A | N/A |
| Networking | Wireless LAN adapter - sold separately | Wireless LAN adapter - sold separately | Wireless LAN adapter - sold separately |
| Epson software solutions | Epson iProjection (Windows/Mac), Epson iProjection App for iOS and Android | N/A | N/A |
| Other features | ISF Calibration, Powered zoom / focus / lens shift, 4K enhancement, HDR and UHD BD support, Lens position memory (x10), Active 3D, Picture-in-picture, Frame interpolation, Super resolution, Detail enhancement, 2D to 3D conversion, Kensington lock, Wireless LAN security | 4K enhancement, A/V mute, Digital zoom, Frame interpolation, Horizontal and vertical keystone correction, Instant on/off, Lens position memory, Long light source life, Super resolution | 4K enhancement, A/V mute, Digital zoom, Frame interpolation, Horizontal and vertical keystone correction, ISF certification, Instant on/off, Lens position memory, Long light source life, Quick Corner, Super resolution |
| Noise (dB) normal / eco | 31 / 20 | 30 / 22 | 30 / 22 |
| Weight (kg) | 11.2 | 12.7 | 12.7 |
| Dimensions exc. feet (W x D x H mm) | 520 x 450 x 193 | 520 x 192.70 x 447 | 520 x 192.70 x 447 |
| Power consumption normal / eco | 355W / 271W | 302W / 198W | 302W / 198W |
| Power consumption standby, comm. off | 0.35W | 0.4W | 0.4W |
| Standard interchangeable lens included | N/A | N/A | N/A |
| Warranty | 24 months / 3,000hrs carry-in | 60 months / 12,000hrs carry-in | 60 months / 12,000hrs carry-in |



Laser projection TV EpiqVision Mini EF-11/EF-12

Project in any direction and on to almost any surface with Epson's smallest laser projectors. These mini laser projectors are sleek and sophisticated in design, are easy to use and come with a range of connectivity solutions.

Epson's smallest consumer laser projector range

Modern and contemporary design

High colour light output of up to 1,000 lumens

Laser light source provides up to 10 years of entertainment¹

Project in any direction

EF-11



EF-12



Remote control to match the stylish look

Smart home entertainment²

Built-in speaker

Premium sound by YAMAHA (EF-12 only)

5 year warranty³

Android TV™ Google, Android, YouTube, Android TV and other marks are trademarks of Google LLC. Subscriptions may be required for certain content providers.

¹ Based on watching content for five hours every day with the projector on Eco mode.

² Miracast built-in (EF-11); Android TV, Google Assistant[®] and Chromecast built-in⁷ (EF-12).

³ 5 years or 12,000 hours, whichever comes first.

Model specific options



Ultra short throw and short throw wall mounts

ELPMB62 for the EB-1485Fi, EB-760W, EB-760Wi, EB-770F, EB-770Fi, EB-775F, EB-800F and EB-805F.

ELPMB45 or ELPMB64 for the EB-L210SW and EB-L210SF.

ELPMB75 for the EB-810E.

ELPMB87 for the EB-815E.



Finger Touch Unit

ELPFT01 for the EB-760Wi and EB-770Fi.



Finger Touch Unit bracket

ELPMB63 for attaching the ELPFT01 directly to the wall - optional usage depending on installation.



Stacking and rigging frames

ELPMB52, ELPMB59, ELPMB76, ELPMB84

Specialist frames designed for the EB-PU, EB-PQ and EB-L3000U products for portrait projection, projector stacking and rigging.

A range of supporting options are also available.



ELPEC01 Camera unit

Optional external camera module designed for the EB-PU and EB-PQ Series and ELPLX Series ultra-short-throw lenses.

Unlock advanced features such as colour calibration, simple stacking, simple blending and the camera assist function for curved surfaces.



ELPAF63 External air filter

Optional external air filter designed for the EB-PU1000 and selected EB-PQ2000 Series models. This filter extends the dust resistance and minimises maintenance intervals, even when used in high dust environments.

Complementary solutions

Wireless presentation systems



ELPWP10 / ELPWP20

Epson's wireless presentation systems make it easy for you to share your screen and increase your productivity.

Automatic start-up


Epson display solutions automatically turn on when the transmitter is plugged into a laptop.

Receiver functionality

The receiver functionality can be integrated with Epson display solutions* reducing your initial costs (ELPWP10 only).

Intuitive design

It's simple enough that anyone can use it without training. Sharing your screen, swapping to a different device or sharing up to four devices simultaneously is as simple as a click of a button.



1 Plug into a laptop



2 Click the button



3 Collaborate on the big screen

*Selected Epson laser products only, alternatively use ELPWP20 for all other HDMI displays.

Document cameras



ELPDC30 Desktop Visualiser

13M pixel camera (4k)
Up to 60 frames per second
A3 shooting area
4K UHD images via HDMI/Miracast
10x optical/23x digital zoom
Kensington lock security
Built-in, easy-to-use carry handle



ELPDC21 Desktop Visualiser

2M pixel camera (1920 x 1080)
Up to 30 frames per second
A3 shooting area
Built-in LED lights
Supports parallel video output and Split screen functionality
1080p images via VGA, HDMI, USB outputs
12x optical/10x digital zoom
Enhanced security with Kensington lock and security bar



ELPDC13 Desktop Visualiser

2M pixel camera (1920 x 1080)
Up to 30 frames per second
A3 shooting area
Built-in LED lights
Supports parallel video output and Split screen functionality
1080p images via VGA, HDMI, USB outputs
16x digital zoom
Enhanced security with Kensington lock and security bar



ELPDC07 Portable Visualiser

2M pixel camera (1920 x 1080)
Up to 30 frames per second
A3 shooting area
Built-in LED lights
USB powered
8x digital zoom

Options



ELPAP10/ELPAP11 Wireless LAN adapter

Upgrade the connectivity of your compatible Epson display solution with this easy-to-install wireless LAN adapter (please check product specifications for compatibility).



ELPCB03 Control and Connection Box

Epson's tailor-made Control and Connection Box is designed to meet the needs of education users. It offers a neat and tidy cable management solution, and is compatible with the Epson education classroom projectors that feature up to 3 x HDMI inputs and an RS232C connection. With large, clearly marked buttons to match those on Epson's projectors, ease of use is assured, allowing presenters to quickly power on and adjust source and volume. Compatible with Epson's 3-in-1 USB Display, the USB signal is also boosted to extend up to 10m.



ELPSP02 External speakers

An optional extra fully compatible with Epson's Control and Connection Box, the ELPSP02 speakers offer powerful 2 x 15W stereo audio support, for perfect clarity even in larger rooms.



ELPSC21

80" Mobile screen

16:9 aspect ratio perfect for 1080p gaming and movies

80 inch portable screen

Less than 4kg, with included carry case

Easy set up



ELPSC32


50" Desktop screen

50 inch pull out screen

4:3 aspect ratio for presentations - ideal for SVGA and XGA projectors

Quick set up for desktop usage

Perfect for travelling presenters – weighs just 3kg



ELPSC36

120" Static ALR screen

ALR (ambient light reflecting) screens reflect and direct all projected light towards the viewer while absorbing ambient light, improving black levels and contrast

120" screen for fixed installation

16:9 aspect ratio perfect for modern hybrid working environments

Designed to be wall mounted in meeting rooms

EB-PU1000 Series lens options

| Lens type | Ultra-short-throw | Short throw | Short throw | Wide throw | Mid throw | Mid throw | Mid throw | Mid throw | Long throw |
|---------------------------|---------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Model name | ELPLX01S/LX01WS | ELPLU03S | ELPLU04 | ELPLW05 | ELPLM08 | ELPLM15 | ELPLM10 | ELPLM11 | ELPLL08 |
| Part code | V12H004X0A/ V12H004Y0A | V12H004JA3 | V12H004U04 | V12H004W05 | V12H004M08 | V12H004M0F | V12H004M0A | V12H004M0B | V12H004L08 |
| Focus / zoom type | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised |
| Zoom ratio (optical) | N/A | 1.2x | 1.2x | 1.4x | 1.6x | 1.6x | 1.5x | 1.5x | 1.4x |
| Throw ratio | | | | | | | | | |
| Aspect ratio | | | | | | | | | |
| WUXGA models | 0.35:1 | 0.65 - 0.78:1 | 0.87 - 1.05:1 | 1.04 - 1.46:1 | 1.44 - 2.32:1 | 2.16 - 3.48:1 | 3.32 - 5.06:1 | 4.85 - 7.38:1 | 7.21 - 10.11:1 |
| F number | 1.9 | 2.0 - 2.26 | 2.0 - 2.1 | 2.0 - 2.22 | 1.65 - 2.27 | 1.8 - 2.51 | 1.84 - 2.4 | 1.81 - 2.34 | 1.8 - 2.45 |
| Focal length | 5.8mm | 11.1 - 13.1mm | 14.8 x 17.7mm | 17.6 - 24.3mm | 24.0 - 38.2mm | 36 - 57.4mm | 55.4 - 83.3mm | 80.6 - 121.1mm | 119 - 165.4mm |
| Screen size range | | | | | | | | | |
| All models | 100 - 1000 inch | 80 - 1000 inch | 50 - 1000 inch | 50 - 1000 inch | 50 - 1000 inch | 50 - 1000 inch | 50 - 1000 inch | 50 - 1000 inch | 50 - 1000 inch |
| Powered lens shift | | | | | | | | | |
| WUXGA models | +17% / ± 10% max | ±67% / ±30% max | ±67% / ±30% max | ±67% / ±30% max | ±67% / ±30% max | ±67% / ±30% max | ±67% / ±30% max | ±67% / ±30% max | ±67% / ±30% max |
| Weight | 3.5 Kg | 2.3 Kg | 3.1 Kg | 1.45 Kg | 1.2 Kg | 1.9 Kg | 2.2 Kg | 2.2 Kg | 2.2 Kg |

Epson's throw distance simulator can help you determine the optimal projector distance and screen size, visit support.epson-europe.com/TDS

EB-PU2000 & EB-PQ2000 Series lens options

| Lens type | Ultra-short-throw | Short throw | Short throw | Wide throw | Wide throw | Wide throw | Wide throw | Mid throw | Mid throw | Mid throw | Mid throw | Long throw |
|--------------------------|---------------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| Model name | ELPLX02S/LX02WS | ELPLU03S | ELPLU04 | ELPLW05 | ELPLW08 | ELPLW06 | ELPLM15 | ELPLM10 | ELPLM11 | ELPLM10 | ELPLM11 | ELPLL08 |
| Part code | V12H004X0B/ V12H004Y0B | V12H004U03 | V12H004U04 | V12H004W05 | V12H004W08 | V12H004W06 | V12H004M0F | V12H004M0A | V12H004M0B | V12H004M0A | V12H004M0B | V12H004L08 |
| Focus / zoom type | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised |
| Zoom ratio (optical) | N/A | 1.2x | 1.2x | 1.4x | 1.4x | 1.37x | 1.6x | 1.5x | 1.5x | 1.5x | 1.5x | 1.4x |
| Throw ratio | | | | | | | | | | | | |
| Aspect ratio | | | | | | | | | | | | |
| WUXGA models | 16:10, 16:9 | 0.35:1 | 0.48 – 0.57:1 | 0.64 – 0.77:1 | 0.77 – 1.07:1 | 0.86 – 1.2:1 | 1.57 – 2.56:1 | 2.42 – 3.71:1 | 3.54 – 5.41:1 | 2.42 – 3.71:1 | 3.54 – 5.41:1 | 5.27 – 7.41:1 |
| 4K models | 16:9 | 0.34:1 | 0.46 – 0.56:1 | 0.62 – 0.75:1 | 0.74 – 1.04:1 | 0.83 – 1.17:1 | 1.52 – 2.47:1 | 2.34 – 3.59:1 | 3.42 – 5.23:1 | 2.34 – 3.59:1 | 3.42 – 5.23:1 | 5.09 – 7.16:1 |
| F number | | 1.9 | 2.0 – 2.26 | 2.0 – 2.1 | 2.0 – 2.22 | 2.0 – 2.22 | 1.8 – 2.35 | 1.81 – 2.4 | 1.81 – 2.34 | 1.81 – 2.4 | 1.81 – 2.34 | 1.8 – 2.45 |
| Focal length | | 8.0mm | 11.1 – 13.1mm | 14.8 – 17.7mm | 17.6 – 24.3mm | 19.7 – 27.5mm | 36 – 57.4mm | 55.4 – 83.3mm | 80.6 – 121.1mm | 55.4 – 83.3mm | 80.6 – 121.1mm | 119 – 165.4mm |
| Screen size range | | | | | | | | | | | | |
| All models | 100 – 1000 inch | 80 – 1000 inch | 60 – 1000 inch | 60 – 1000 inch | 60 – 1000 inch | 60 – 1000 inch | 60 – 1000 inch | 60 – 1000 inch | 60 – 1000 inch | 60 – 1000 inch | 60 – 1000 inch | 60 – 1000 inch |
| Lens shift | | | | | | | | | | | | |
| WUXGA models | Vertical/Horizontal | +25% / ±15% | ±24% / ±10% | ±60% / ±18% | ±24% / ±10% | ±60% / ±18% | ±60% / ±18% | ±60% / ±18% | ±60% / ±18% | ±60% / ±18% | ±60% / ±18% | ±60% / ±18% |
| 4K models | Vertical/Horizontal | +23% / ±10% | ±18% / ±6% | ±58% / ±16% | ±18% / ±6% | ±58% / ±16% | ±58% / ±16% | ±58% / ±16% | ±58% / ±16% | ±58% / ±16% | ±58% / ±16% | ±58% / ±16% |
| Weight | | 5.0 Kg | 2.3 Kg | 3.1 Kg | 1.45 Kg | 3.1 Kg | 1.9 Kg | 2.2 Kg | 2.2 Kg | 2.2 Kg | 2.2 Kg | 2.2 Kg |

Epson's throw distance simulator can help you determine the optimal projector distance and screen size, visit support.epson-europe.com/TDS
 ELPW05 brightness is limited to maximum 12,000 lumens. **4K specs are preliminary and subject to change.**

EB-L30000U lens options

| Lens type | Ultra-short-throw | Rear projection | Wide throw | Wide throw | Mid throw | Mid throw | Mid throw | Long throw | Long throw |
|--------------------------|-------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Model name | ELPLX03 | ELPLR05 | ELPLU05 | ELPLW07 | ELPLM12 | ELPLM13 | ELPLM14 | ELPLL09 | ELPLL10 |
| Part code | V12H004X03 | V12H004R05 | V12H004U05 | V12H004W07 | V12H004M0C | V12H004M0D | V12H004M0E | V12H004L09 | V12H004L0A |
| Focus / zoom type | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised | Motorised |
| Zoom ratio (optical) | N/A | N/A | 1.21x | 1.37x | 1.35x | 1.52x | 1.50x | 1.50x | 1.50x |
| Throw ratio | | | | | | | | | |
| Aspect ratio | | | | | | | | | |
| WUXGA | 16:10, 16:9 | 0.63:1 | 0.90 - 1.09:1 | 1.29 - 1.76:1 | 1.74 - 2.35:1 | 2.28 - 3.46:1 | 3.41 - 5.12:1 | 4.79 - 7.20:1 | 6.96 - 10.45:1 |
| F number | 2.2 | 2.2 | 2.4 - 2.6 | 2.2 - 2.5 | 1.9 - 2.1 | 1.9 - 2.4 | 1.9 - 2.4 | 2.1 - 2.5 | 2.2 - 2.6 |
| Focal length | 11.16mm | 19.1mm | 28.4 - 34.0mm | 40.6 - 55.2mm | 54.7 - 73.0mm | 71.6 - 107.3mm | 104.8 - 156.9mm | 149.7 - 225.0mm | 216.6 - 326.8mm |
| Screen size range | | | | | | | | | |
| All models | 120 - 1000 inch | 100 - 1000 inch | 100 - 1000 inch | 100 - 1000 inch | 100 - 1000 inch | 100 - 1000 inch | 100 - 1000 inch | 100 - 1000 inch | 100 - 1000 inch |
| Lens shift | | | | | | | | | |
| WUXGA | ±25% / ±15% max | ±15% / ±5% max | ±55% / ±25% max | ±65% / ±30% max | ±65% / ±30% max | ±65% / ±30% max | ±65% / ±30% max | ±55% / ±25% max | ±55% / ±25% max |
| Weight | 13 Kg | 9.4 Kg | 9.7 Kg | 9.4 Kg | 7.2 Kg | 9.5 Kg | 9.5 Kg | 9.2 Kg | 10.5 Kg |

Epson's throw distance simulator can help you determine the optimal projector distance and screen size, visit support.epson-europe.com/TDS

Glossary and features

Look out for additional features that further improve the user experience. Features are specific to particular models – please check individual product specifications for details.

Auto calibration

Epson's interactive projectors offer the ability to automatically calibrate the interactive surface area. With just a couple of clicks an interactive workspace can be calibrated without needing to perform a lengthy manual process.

Auto lamp dimming

This feature automatically adjusts the brightness of the projector according to either the ambient light conditions or the content of the projected image.

Auto screen fit

This feature allows a projector to be roughly set up in front of a framed screen, and with a simple press of the 'Screen Fit' button, the image is aligned perfectly to the screen borders for quick and easy set up.

Colour calibration

Keep images consistent and maintenance to a minimum using the built-in or optional camera. The camera detects image colours that have become uneven over time, detects subtle inconsistencies between multiple projectors and enables automatic colour correction.

Constant brightness mode

The constant brightness mode maintains the projector's brightness at a specified level for up to 97,000 hours, helping to ensure the longevity of the light source.

Contrast ratio

The degree of difference between the lightest and darkest areas of the projected image. A high contrast ratio is particularly important for home cinema projectors.

Copy OSD settings

A feature that allows the cloning of the projectors OSD menu settings like user logo and colour mode via a USB thumb drive or USB-B cable, to transfer to other compatible projectors in the environment.

Curved surface and corner wall correction

Enhanced geometric correction capability allowing large images to be wrapped around curved surfaces or corners, creating engaging displays in innovative spaces.

Detail enhancement

Improve perceived detail with processing that enhances the contrast and texture of content.

DICOM simulation

This dedicated colour mode is designed to show off the best greyscale range – perfect for viewing medical images such as X-rays (cannot be used for diagnostic purposes).

Edge blending

Built-in ability to use multiple projectors vertically or horizontally for one giant image. Edge blending manages the overlaps between projectors to produce seamless large scale images.

Focus help

An easy to use built-in test pattern that enables the focus to be perfectly adjusted in seconds.

Frame interpolation

Video processing technology that inserts additional frames between the original ones to produce a smoother and sharper playback – particularly important for fast-moving action sequences in high definition movie content.

High dynamic range (HDR)

HDR presents the optimal visual experience by increasing the contrast ratio to deliver a far greater range between the darkest and lightest areas of the screen. It gives images more depth and allows you to see incredible detail that's previously not been possible. It enriches colours making images feel more natural yet intense, and ultimately, more immersive.

Keystone correction

A digital image adjustment used to realign the image when projected at an angle to the screen, producing a rectangular image rather than a 'keystone' shape. On some models this is available for horizontal correction as well as vertical, while more advanced models have the ability to make these corrections automatically.

Lens position memory

Specific lens positions can be stored in the projector memory, including lens shift positions, focus and projection sizes, allowing you to quickly adjust the projector depending on the aspect ratio of the content.

Lens shift

A feature of high-end products, this is a physical adjustment of the lens position to allow an image to be moved horizontally or vertically with no loss of image quality, perfect for easy installation.

MHL

Mobile High-Definition Link is a connectivity technology that enables you to easily share your content directly from a compatible smartphone or tablet and is capable of charging the device at the same time.

Multi location interactivity

This feature allows up to four projectors to be connected using iProjection for PCs, with content and interactivity shared across all users. This means that people in different locations can collaborate on the same content remotely.

PC-free presentation

Display files from USB memory without the need for a laptop and cables. Compatible file formats vary by projector.

Picture-in-picture

Display one source in full screen, whilst showing a secondary source as a smaller inset picture.

Point and arc correction

Geometric correction that enables small corrections to be made for screens that are uneven in places or slightly curved – perfect for large scale installations.

Portrait projection

Allows projection of portrait orientated images by placing the projector on its side.

QR code function

Display an on-screen QR code to easily connect wirelessly via iProjection.

Real time keystone correction

Keeps the image perfectly aligned by constantly monitoring the projector's positioning and maintaining a rectangular image in real time.

Resolution and aspect ratio

The native resolution is the number of distinct pixels in each dimension that can be displayed. This is stated as the number of columns and rows of pixels creating the display e.g. 1920 x 1080 (1080p). The greater the resolution, the greater the detail and sharpness of the projected image. The ratio of horizontal to vertical lines also gives the native aspect ratio. In this instance 1920 x 1080 equates to a native aspect ratio of 16:9. It is best to match the input signal resolution to the projector's output resolution where possible to achieve the best image.

Schedule function

Built-in schedule management that allows timer setting of many projector functions, without the need to be connected to a PC or network – perfect for events and staging.

Screen Mirroring (Miracast)

Easy wireless transmission of Full HD (1080p) video and sound from compatible smartphones, tablets or PCs.

Screen sharing

Content can be shared between displays on the same network, promoting higher engagement and collaboration without the need for additional software.

Up to four projectors can be connected, with everyone viewing the content at the same time as other Epson displays (selected models only).

Split screen

This feature enables content from two different sources to be played simultaneously, with one image larger than the other or both of equal size.

Super resolution

Image processing that upscales standard definition content to produce a sharper and more detailed output image.

Throw distance calculator

Easily work out image sizes and projection distance dimensions across our entire projector range. Simply select your desired screen size or the projection distance, and the smart online tool will automatically calculate all the necessary installation dimensions.

Throw ratio

The projection distance divided by the width of the projected image. A smaller throw ratio will enable large projection sizes from a shorter distance. The range of throw ratios for any given projector will also depend on the range of its zoom capability.

USB display

3-in-1 USB display enables simple plug-and-play capability. One USB cable can be used for image, audio and control. This saves time when making a connection, as the computer image should automatically be displayed, and prevents the need for multiple cables.

Warranty

To ensure customer satisfaction and complete peace of mind, Epson boast a market leading service organisation. All business and home cinema projectors in this guide are covered by a minimum of two years hardware and one year lamp warranty. For exact details of each model and to see options for warranty extension please visit www.epson.eu/warranty

Web-based control (with smart device support)

Use a computer web browser or smart device to adjust projector settings. The newly designed OSD Control Pad function allows control of the OSD menu and shows a representation of the lens-shift range that is available.

For further information please contact your local Epson office or visit www.epson.eu/contact-us

Algeria +213 770 938 617 **Austria** 01 253 49 78 333
Belgium +32 (0)2 792 04 47 **Czech** +420 246 037 281
Denmark 44 50 85 85 **Ethiopia** +254700760366 **Finland** 09-3158 3267
France 09 74 75 04 04 (Cost of local call, operator charges may apply) **Germany** +49 (0) 2159/92 79 500 **Greece** (0030) 211 198 62 12
Hungary 06800 147 83 **Ireland** 01 436 7742 **Israel** (+972)-3-5751833 **Italy** 02-660321 10 (0,12 €/min)
Kenya +254 207 904 566 **Luxembourg** +352 27860692
Middle East +9714 2677638 **Morocco** +212 520 134 040
Netherlands +31 (0)20 708 5099 **Norway** +47 67 11 37 00 **Poland** +48 22 295 37 25 (0,16 zł/min)
Portugal 707 222 111 **Romania** 0040 214025024
Russia (095) 777-03-55 **Slovakia** +421 232 786 682
Southern Africa +27 (0) 10 109 5320 **Spain** 93 582 15 00
Sweden +46 8 5051 3701 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min) **Switzerland** 022 592 7923
Tanzania +255 080 011 1014 **Tunisia** +216 9811 5564
Turkey (0212) 3360303 **Uganda** +256 205 491 148
United Kingdom 0871 42 37766 (+10p per minute plus network extras)
West Africa +2349046648285



Please recycle responsibly



Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

¹ 2001 to 2022, 500-lumen and above, excluding screenless TVs, Futuresource Consulting – Quarterly Projector Market Insights – Worldwide Analyzer CY22Q4.

² Colour brightness (colour light output) in brightest mode, measured by a third-party lab in accordance with IDMS 15.4. Colour brightness will vary depending on usage conditions. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP projectors based on NPD sales data for January 2022 to December 2022.

³ Depending on product, please check specifications on pages 9-33.

⁴ Epson achieved certification by TCO Certified for selected families of projectors. TCO Certified is the world's most comprehensive sustainability certification for IT products, which must meet life cycle criteria for social and environmental sustainability. For more information, please visit <https://tcocertified.com>.

⁵ 4K Enhancement Technology shifts each pixel diagonally to double Full HD resolution. Resolution is Full HD in 3D Mode.

⁶ Google Search function is worldwide. Google Search cannot communicate the Smart solution with Google Home. Google Assistant is not available in certain languages and countries.

⁷ Casting optimised for selected services only. Streaming quality for other content may vary. Supported operating systems and devices: Android 2.3 and higher iOS® 7 and higher, Windows® 7 and higher, Mac OS® 7 and higher and Chrome OS (version 38 or higher).

EPSON®