

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	EPSON	Logo
Company name *	Seiko Epson Corporation	EDOON
Contact information *	EPSON Europe B.V.	EPSON
e-mail address	environment@epson.eu	
Internet site *	http://www.epson.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms					
to the statements given in t	his declaration.				
Type of product *	Other				
Commercial name *	PP-50II				
Model number *	FF-3011				
Issue date *	2024/12/11				
Intended market *	☐ Global	Europe	🔲 Asia, Pacific & Japan	Americas	Other
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution

P12.1-P12.2 Ergonomic requirements.

Model number *	PP-50II	Logo	
Issue date *	2024/12/11		EPSON

Product environmental attributes - Legal requirements					
Item	<u> </u>	Yes	No	n.a.	
P1	Hazardous substances and preparations				
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)	X			
P1.2*	Products do not contain Asbestos (see legal reference).	X			
	Comment: Legal reference has no maximum concentration value.				
	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons	X			
P1.3*	(HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide				
1 1.5	(see legal reference). Comment: Legal reference has no maximum concentration values.				
	(555 logar role on 65). Germmont: Logar role on 65 maximum contestituation values.				
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl	X			
1 1.4	(PCT) in preparations (see legal reference).				
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the	X			
. 1.0	chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).				
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 mg/cm²/week			\times	
	(see legal reference).				
	Comment: Max limit in legal reference when tested according to EN1811:2011-5.				
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):	\boxtimes			
	http://www.epson.com				
P2	Batteries				
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal	X	П	П	
	symbol. Information on proper disposal is provided in user manual. (See legal reference) Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal				
P2.2*	reference)	\boxtimes			
P2.3*	Batteries and accumulators are readily removable. (See legal reference)		П	X	
P3	Conformity verification & Eco design (ErP)				
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference).	X			
	The Declaration of Conformity can be requested at (add link or e-mail address): https://www.epson.eu/c	onformity	, _		
P3.2*	The product complies with the Eco design Requirements for Energy-Related Products,			X	
	(see legal reference).				
	Required information is; given in item P15 or added to this document,			X	
	available at (add URL): http://www.epson.com				
P4	Consumable materials				
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium at a level greater			×	
1 7.1	than 0,01% (see legal reference and NOTE B1).				
P4.2*	If ink/toner is used in the product, it does not contain cadmium at a level greater than 0,1% by weight (see	X			
	legal reference) If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there are				
	Community workplace exposure limits, the product/packaging is adequately labeled according to applicable	\boxtimes			
P4.3*	regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal				
	reference).				
P5	Product packaging				
	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and	N			
P5.1*	hexavalent chromium by weight of these together.	\boxtimes			
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s)		X	П	
F J.Z	used (see legal reference).			Ш	
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol	\boxtimes			
	(see legal reference).				
P6	Comment: Legal reference has no maximum concentration values. Treatment information				
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes			
1.0.1	information for rooystors/treatment facilities is available (see legal reference).				

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	PP-50II	Logo	FDCCN
Issue date *	2024/12/11		EPSON

Temporal conscious design	Produc	t environmental attributes - Market requirements (See General Note GN below)			
Disassembly, recycling P7.1° Parts that have to be treated separately are easily separable P7.2° Plastic materials in covers/housing have no surface coating. P7.3° Plastic parts > 100 g consist of one material or of easily separable materials. P7.4° Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5° Labels are easily separable. P7.6° Labels are eavile labels are easily easily easily to safety/regulatory labels. P7.7° P7.7° Upgrading can be done using commonly available tools P7.8° P7.8° Spare parts are available after end of production for: S years P7.10 Spare parts are available after end of production for: S years P7.10 P7.			Requ	iireme	nt met
P7.1* Parts that have to be treated separately are easily separable	Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P7.1* Parts that have to be treated separately are easily separable P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts > 100 g consist of one material or of easily separable materials. P7.4* Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10* Service is available after end of production for: 5 years	P7	Design			
P7.3° Plastic parts > 100 g consist of one material or of easily separable materials. P7.4° Plastic parts > 25 g bave material condes according to ISO 11469 referring ISO 1043-4. P7.5° Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.8° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.11° Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.12 Insulation materials of external electrical cables are PVC free. External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorinate flame retardants, containing more than 25% post-consumer recycled content. P7.14 P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: D8. Driving a cover of the circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B2) P7.18 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: D8. Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: D8.		Disassembly, recycling			
P7.3* Plastic parts > 100 g consist of one material or of easily separable materials.	P7.1*	Parts that have to be treated separately are easily separable	X		
P7.4* Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Sparding can be done using commonly available tools P7.9* Spard parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are PCBs	P7.2*	Plastic materials in covers/housing have no surface coating.	X		
P7.6 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11 Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.11 Insulation materials of external electrical cables are PVC free. External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs ≥ 25 g are low ladgen as defined in IEC 61249-2-21. (See NOTE B3). P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:	P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	X		
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free. External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine atributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are Walting according in parts of the product of the p	P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	X		
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives		Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.			
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: Material type: Material type: P7.12	P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	X		
P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) Chemical name: , CAS #: " Alt. 2: Chemical name: , CAS #: " Alt. 2: Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: Insulation materials of internal electrical plastic parts > 25 g according ISO 1043-4: Insulation materials of internal electrical plastic parts > 25 g according ISO 1043-4: Insulation material type: Material type: Mate		Product lifetime			
P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: Material type: Material type:	P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	X		
P7.10 Service is available after end of production for: 5 years Material and substance requirements	P7.8*	Upgrading can be done using commonly available tools	X		
P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free.	P7.9.	Spare parts are available after end of production for: 5 years			
P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: Material type: Material type: P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are without components are low halogen: all PCBs > 25 g are without components are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4. Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are us	P7.10	Service is available after end of production for: 5 years			
Material type: ABS		Material and substance requirements			
P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " Alt. 2: Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: " 1. In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been	P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):			
P7.13 Insulation materials of internal electrical cables are PVC free. External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:		Material type: ABS Material type: Material type:			
External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-2-1. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:	P7.12	Insulation materials of external electrical cables are PVC free.		X	
P7.14 weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:	P7.13	Insulation materials of internal electrical cables are PVC free.		X	
polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:		External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1%			
polywinyl chloride or 0,3% weight (3000 ppm) profilme and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:	D7 44	weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and		_	
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:	P7.14	polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts		Ш	Ш
Iow halogen as defined in IEC 61249-2-21. (See NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:		containing more than 25% post-consumer recycled content.			
P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking:	P7.15	Printed circuit boards, PCBs (without components) are low halogen: all 🔀 PCBs > 25 g 📋 are		\boxtimes	
Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4)		low halogen as defined in IEC 61249-2-21. (See NOTE B2)			
P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4)	P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:			X
TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:		Marking:			
Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: 3. Chemical name: 4. CAS #: 4. CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been	P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):			
according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4)		TBBPA (additive) ☐ , TBBPA (reactive) ☐ (See NOTE B3), Other; chemical name: , CAS #:			
according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4)					
P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4)		Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g			
concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #:					
concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been	P7 18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in			
2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4. Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been	7.10	·			
3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been □ □ □		, ,			
Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:					
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been		3. Chemical name: , CAS #: "			
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been		Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4			
•	P7.19				
G					
The source(s) for these classifications is/are found at (add URL(s)): (See NOTE B5)			5)		

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-internationl.org/publications/standards/Ecma-370.htm.

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

Model number *	PP-50II	Logo	
Issue date *	2024/12/11		EPSON

Product	environmental attribu	tes - Market requiren	nents (continued)			Requ	iiremer	nt met
Item		•	·			Yes	No	n.a.
	Material and substa	nce requirements (co	ontinued)					
P7.20*			tent is used in the prod	duct (See NOTE B6)	:		X	
	If YES: at least one o	f the two alternatives b	pelow shall be answere	ed:				
	·		postconsumer recycle	·	ntent			
	,	ercentage of total plas		%.				
	or	oroomago or total plac	2)g,					
	b) The weight of recy	vcled material is	0.0 g.					
	-, ···- ··-·g··· -·	,	3.					
P7.21*	Biobased plastic mate	erial content is used in	the product (See NOT	ΓΕ B7):			X	
	If YES; at least one of	f the two alternatives b	pelow shall be answere	ed;				
a) Of total plastic parts' weight > 25 g, the biobased plastic material content								
		ercentage of total plas	stic by weight) is	%.				
	or							
D7.00*		biobased plastic mate						
P7.22*	-	from mercury, i.e. les	• .					\boxtimes
DO		ecify: Number of lamps	s: and maxin	num mercury content	t per lamp: mg			
P8	Batteries Battery chemical com	position: Lithiu	200					
P8.1*			III					
P9 P9.1	Energy consumption		r operav consumption	a are reported:				
		Power level at	r energy consumption Power level at	Power level at	Reference/Standard for	or operav	modos	and tost
Energy m	ode *	100 V AC	115 V AC	230 V AC	method *	or energy	moues	and lest
Sleen mo	de for ENERGY STAR		III V AC	230 V AC	mourou			
	ional Mode (OM)	w	w	0.0	w			\boxtimes
products	ionai modo (Om)			0.0				
Standby/o	off mode for ENERGY							
	erational Mode (OM)	W	W	0.0	w			\boxtimes
products	,							
TEC valu	e for ENERGY STAR							
TEC prod	lucts (TEC= Typical	kWh/week	kWh/week	0.00 kWh/we	ek			\boxtimes
	onsumption)							
TEC valu	e (OM product)	kWh/week	kWh/week	0.00 kWh/we	ek			X
		W	W		W			
		W	W		W			
		W	W		W			
		W			W			
		W			W			
	Power Supply Efficiency			tocol)* :				X
	n Speed * :	images per minu						X
	me to enter energy save		minutes					X
P9.2*	Information about the	energy save function	is provided with the pr	oduct.			\boxtimes	

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

Model number *	PP-50II	Logo	
Issue date *	2024/12/11		EPSON

Product	environmental attr	ributes - Market requi	rements (cor	ntinued)				Requ	uireme	nt met
Item								Yes	No	n.a.
P10	Emissions									
	Noise emission -	- Declared according	to ISO 9296	(See NOTE B9)						
P10.1	Mode	Mode description		Statistic	cal uppe	er limit A-weig	hted sound power le	evel,		
				L _{WA,c} (B)					
	Idle	* Idoling		*	Inaudib	ole				X
	Operation	* Operation		*		5.4				
	Other mode									
	Measured accord	ing to: 📋 ISO 77	79	□ ECMA-74						
		Other	only if not co	vered by ECMA-	-74)					
		ions from printing pro								
P10.2*	Test performed a	ccording to ECMA-328	Determinatio	n of Chemical Er	nission	Rates from			X	
	Electronic Equipm	nent (ISO/IEC 28360)	☐ , othe	er specify:						
P10.3	Typical emission	rate (operation phase)	is (mg/h):							
	Electrophotograpl	hic devices: Ozone	Dust	Styrene	I	Benzene	TVOC			
	Ink devices:		Dust	Styrene	I	Benzene	TVOC			
	NOTE: compliance	e with maximum emiss	ion rates in e	co labels to be d	eclared	in P14.				
P11		terials for printing pro								
P11.1*	A Safety Data Sh	eet (SDS) is available f	or the ink/ton	er preparation, e	ven if no	ot legally requ	uired (see P4.3).	X		
P11.2*		post-consumer recycle	d fibers can b	e used, provided	d that it i	meets the red	quirements of EN			X
	12281.							Ш		
P11.3*	2-sided (duplex) p	orinting/copying is an in	tegrated proc	luct function.						$\boldsymbol{\times}$
P11.4*	The product is de	livered to end-user with	n default auto	-duplex enabled.						X
P13	Packaging and d									
P13.1*	Product packagin	g material type(s):		Fibreboard wei	ght (kg):					
		g material type(s):	Foamed PS		ght (kg):					
		g material type(s):	PP	wei	ght (kg):	0.060				
P13.2*		imary packaging is free						X		
P13.3*	•	ary corrugated fiberboar			ained pe	ercentage of				
		nsumer recovered fiber		80 %						
P13.4*		user and product docu	•	ck box):						
			ther							
P13.5	•	plete this item if paper		,						
	•	documentation on pap	er media is cl	hlorine-free:						
	If Yes, please spe	•								
	Totally chlorine-fr									
	Elemental chloring									
D44	Processed chlorin									
P14	Voluntary progra			1 1	()					
P14.1		ts the requirements of t	-		٠,,	1				
	ENERGY STAR®			Date:		duct category				
	Eco-label:	Criteria versior		Date:		duct category				
<u> </u>	Eco-label:	Criteria versior	n:	Date:	Prod	duct category	:			

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm. NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

Model number *	PP-50II	Logo	
Issue date *	2024/12/11		EPSON

Product e	Product environmental attributes - Market requirements (concluded) Requirement met			
P15	P15 Additional information (See NOTE B11)			

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) *	P1.1, P4.1, P3.1
* Specific exemptions apply for certain products and applications.	
Commission Regulation (EC) 1907/2006 (REACH Regulation), annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Commission Regulation (EC) 1907/2006 (REACH Regulation), annex VII	P1.10
Commission Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Commission Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2006/66/EC (Battery and accumulators Directive), as amended.*	P2.1, P2.2, P2.3, P8.1
* These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	
Directive 2014/35/EU (Low Voltage Directive)	P3.1
Directive 2014/30/EU (EMC Directive)	P3.1
Directive 2014/53/EU (RE Directive)	P3.1
Commission Regulation (EC) No 1275/2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off mode electric power consumption of electrical and electronic household and office equipment (Standby Regulation)	P3.1, P3.2, P9.1
Commission Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	
Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies	P3.1, P3.2, P9.1
Commission Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2

Directive 2012/19/EU (WEEE directive) Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register. Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in		
reporting of producers of electrical and electronic equipment to the register. Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in	Directive 2012/19/EU (WEEE directive)	P6.1
the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in		
Agch Mamhar Stata	the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of	