

## Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand *                | EPSON                   | Logo  |
|------------------------|-------------------------|-------|
| Company name *         | Seiko Epson Corporation | FROOM |
| Contact information *  | EPSON Europe B.V.       | EPSON |
| e-mail address         | environment@epson.eu    |       |
| Internet site *        | http://www.epson.com    |       |
| Additional information |                         |       |

| The company declares (based on product specification or test results based obtained from sample testing), that the<br>product conforms to the statements given in this declaration. |  |  |  |  |  |  |
|---|--|--|--|--|--|--|
| Type of product *   | Large Format Printer (Ink-Jet)                               |  |  |  |  |  |
| Commercial name *   | :C-F9500   |  |  |  |  |  |
| Model number *  | 36-F3300   |  |  |  |  |  |
| Issue date *  | 10/2/2024  |  |  |  |  |  |
| Intended market *   | 🗌 Global 🛛 Europe 🔲 Asia, Pacific & Japan 🗌 Americas 🔛 Other |  |  |  |  |  |
| Additional information  |  |  |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

## About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template: P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

| Model r      | number *         | SC-F9500   | Logo       |          |                |      | 167          |
|--------------|------------------|--|------------|----------|----------------|------|--------------|
| Issue date * |                  | 10/2/2024  | -          | E        | PS             | ON   |              |
|              |                  |  |            |          |                |      |              |
| Broduct      | tonvironmontal   | attributes - Legal requirements  |            | P        | equire         | mont | mot          |
| Item         | tenvironmentai   | attibutes - Legai requirements   |            | N        | Yes            | No   | n.a.         |
|              | lazardous subst  | ances and preparations   |            |          | 103            | NO   | n.a.         |
| P1.1*        |                  | mply with the current European RoHS Directive. (See legal reference  | e and NO   | TF B1)   | X              |      |              |
| P1.2*        |                  | t contain Asbestos (see legal reference).  |            | 12 01)   | X              |      |              |
| l <u>–</u>   |                  | al reference has no maximum concentration value.   |            |          | <u>17 - 11</u> |      |              |
|              |                  | t contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),   |            |          | X              |      |              |
| -            |                  | procarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbo   | ntetrachlo | oride,   |                |      |              |
| P1.3*        |                  | thane, methyl bromide (see legal reference). Comment: Legal refere   |            |          |                |      |              |
|              | maximum conc     | entration values.  |            |          |                |      |              |
|              | Products do no   | t contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005%   | 6          |          | X              |      |              |
| P1.4*        | polychlorinated  | terphenyl (PCT) in preparations (see legal reference).   |            |          | <u>17 - 11</u> |      |              |
|              | Products do no   | t contain more than 0,1% short chain chloroparaffins (SCCP) with 10  | )-13 carbo | n        | X              |      |              |
| P1.5*        |                  | ain containing at least 48% per mass of chlorine in the SCCP (see le   |            |          |                |      |              |
|              |                  |  | -          |          |                |      |              |
| P1.6*        | •                | and prolonged skin contact do not release nickel in concentrations   | above 0,   | 2        |                |      | $\mathbf{X}$ |
|              | 0                | see legal reference).  |            |          |                |      |              |
| P1.7*        |                  | I limit in legal reference when tested according to EN1811:2011-5.<br>33 information about substances in articles is available at (add URL   | or mail or | ontaat): | X              | _    |              |
| P1.7         |                  | -epson.com   | or mail co | Jilaci). |                |      |              |
| P2           | Batteries        |  |            |          |                |      |              |
|              |                  | and the set of the maximum and the set of th |            |          |                |      |              |
| P2.1*        |                  | ontains a battery or an accumulator, the battery/accumulator is labeled  |            |          | X              |      |              |
|              | uisposai symbo   | I. Information on proper disposal is provided in user manual. (See le  | yai reiere |          |                |      |              |
| P2.2*        | Batteries or acc | cumulators do not contain more than 0,0005% of mercury or 0,002%   | of cadmi   | um.      | X              |      |              |
|              | (See legal refer | •  |            |          |                |      |              |
| P2.3*        | Batteries and a  | ccumulators are readily removable. (See legal reference)   |            |          |                |      | $\mathbf{X}$ |
| P3           |                  | rification & Eco design (ErP)  |            |          | _              |      |              |
| P3.1*        | -                | CE-marked to show conformance with applicable legal requirements   |            |          |                |      |              |
|              |                  | n of Conformity can be requested at (add link or e-mail addres https://  |            | son.eu/o | confor         | mity |              |
| P3.2*        | -                | mplies with the Eco design Requirements for Energy-Related Produc  | cts,       |          |                |      |              |
|              | (see legal refer |  |            |          |                |      |              |
|              | Required inform  |  |            |          |                |      |              |
| <b>D</b> 4   | Comerciable      | available at (add URL): http://www.epson.com   |            |          |                |      |              |
| P4           | Consumable n     |  |            |          |                |      |              |
| P4.1*        |                  | uctor (drum, belt etc.) is used in the product, it does not contain cadr   | nium at a  | level    |                |      | $\mathbf{X}$ |
|              | -                | 01% (see legal reference and NOTE B1).   | 0.40/ 1    |          |                |      |              |
| P4.2*        | weight (see leg  | sed in the product, it does not contain cadmium at a level greater tha   | IN U, 1% D | У        | X              |      |              |
| <u> </u>     |                  | · ·  | tonoo for  | which    | 8.4            |      |              |
|              |                  | formulation/preparation is classified as hazardous or contains a subs<br>nunity workplace exposure limits, the product/packaging is adequate   |            |          | $\mathbf{X}$   |      |              |
| P4.3*        |                  | plicable regulations and a Safety Data Sheet (SDS) in accordance w   |            |          |                |      |              |
|              |                  | available (see legal reference).   |            |          |                |      |              |
| P5           | Product packa    | aging  |            |          |                |      |              |
|              |                  | packaging components do not contain more than 0,01% lead, mercu  | ury, cadm  | ium      | X              |      |              |
| P5.1*        | and hexavalent   | chromium by weight of these together.  | -          |          |                |      |              |
| P5.2*        | The packaging    | materials are marked with abbreviations and numbers indicating the   | nature of  | the      |                | X    |              |
| F J.Z        |                  | d (see legal reference).   |            |          |                |      |              |
| P5.3*        |                  | ckaging material is free from ozone depleting substances as specifie   | ed in the  |          | X              |      |              |
|              |                  | col (see legal reference).   |            |          |                |      |              |
| De           |                  | al reference has no maximum concentration values.  |            |          |                |      |              |
| P6 1*        | Treatment info   | recyclers/treatment facilities is available (see legal reference).   |            |          |                | -    | _            |
| P6.1*        | mormation for    | recyclerative autient racinites is available (see legal reletence).  |            |          | X              |      |              |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model n  | number *   | SC-F9500               |   |                         | Logo              |              |              |              |
|----------|--|------------------------|---|-------------------------|-------------------|--------------|--------------|--------------|
| Issue da | ate *  | 10/2/2024              |   |                         |                   | EPS          | ON           |              |
|          |  |                        |   |                         |                   |              |              |              |
|          |  |                        |   |                         |                   |              |              |              |
| Product  | t environmental                                      | attributes - Marke     | et requirements (See                          | General Note GN be      | low)              |              |              |              |
| - Env    | vironmental con                                      | scious design          |   |                         |                   | Requ         | uireme       | ent met      |
| Item     | *=mandatory to                                       | fill in. Additional ir | nformation regarding ea                       | ach item may be found   | d under P14.      | Yes          | No           | n.a.         |
| P7       | Design   |                        |   |                         |                   |              |              |              |
|          | Disassembly,   | recycling              |   |                         |                   |              |              |              |
| P7.1*    | Parts that have                                      | to be treated sepa     | arately are easily sepa                       | able                    |                   | $\mathbf{X}$ |              |              |
| P7.2*    | Plastic material                                     | ls in covers/housin    | ng have no surface coa                        | ting.                   |                   | $\mathbf{X}$ |              |              |
| P7.3*    | Plastic parts >                                      | 100 g consist of or    | ne material or of easily                      | separable materials.    |                   | $\mathbf{X}$ |              |              |
| P7.4*    | Plastic parts > 2                                    | 25 g have material     | I codes according to IS                       | O 11469 referring ISC   | ) 1043-4.         | $\mathbf{X}$ |              |              |
| P7.5     | Plastic parts ar                                     | e free from metal i    | inlays or have inlays th                      | at can be removed wi    | th commonly avail | able toc 📋   |              |              |
| P7.6*    | Labels are easi                                      | ily separable. (This   | s requirement does not                        | apply to safety/regula  | atory labels).    | X            |              |              |
|          | <b>Product lifetin</b>                               | ne                     |   |                         |                   |              |              |              |
| P7.7*    | Upgrading can  | be done e.g. with      | processor, memory, ca                         | rds or drives           |                   | X            |              |              |
| P7.8*    | Upgrading can  | be done using con      | mmonly available tools                        |                         |                   | $\mathbf{X}$ |              |              |
| P7.9.    | Spare parts are                                      | e available after en   | nd of production for: 7                       | years                   |                   |              |              |              |
| P7.10    | Service is avail                                     | able after end of p    | production for: 7                             | years                   |                   |              |              |              |
|          | Material and s                                       | ubstance require       | ements  |                         |                   |              |              |              |
| P7.11*   | Product cover/h                                      | nousing material ty    | /pe (e.g. plastics, meta                      | l, aluminum):           |                   |              |              |              |
|          | Material type:                                       | ABS                    | Material type:                                | m-PPE                   | Material type: P  | С            |              |              |
| P7.12    | Insulation mate                                      | rials of external ele  | ectrical cables are PVC                       | C free.                 |                   |              | X            |              |
| P7.13    | Insulation mate                                      | rials of internal ele  | ectrical cables are PVC                       | free.                   |                   |              | X            |              |
|          | External plastic                                     | casing/cover part      | ts > 25 g contain no mo                       | ve than 0.1% weight (   | (1000 ppm) bromi  |              |              |              |
|          |  | 0 1                    | prine attributable to bro                     | , 0 (                   | · · · · /         | ame          |              |              |
| P7.14    |  | · · · /                | or 0,3% weight (3000                          |                         |                   |              |              |              |
|          |  |                        | than 25% post-consum                          |                         | 5 (****1          | ,            |              |              |
| D7.45    | Data da da circa da la                               |                        |   |                         |                   |              | 57           |              |
| P7.15    |  |                        | nout components) are l                        |                         | 3s > 25 gaı       | e 🗌          | $\mathbf{X}$ |              |
| D7.40    |  |                        | 249-2-21. (See NOTE<br>g in covers / housings |                         | a ISO 1042 4:     |              |              |              |
| P7.16    |  | plastic parts > 25     | g in covers / nousings                        |                         | J 130 1043-4.     |              |              | $\mathbf{X}$ |
| P7.17    | Marking:   |                        | flama natandanta in min                       |                         | <b>F</b> = (      |              |              |              |
| P7.17    |  | •                      | flame retardants in prir                      |                         |                   | ,            |              |              |
|          | I BBPA (additiv                                      | 🤨 📋 , TBBPA (rea       | active) 📋 (See NOTE                           | B3), Other; chemical    | name , CAS ;      | #: 🗌         |              |              |
|          |  |                        | flama natandanta in min                       |                         | 41                | <b>`</b>     |              |              |
|          |  | •                      | flame retardants in prir                      | neu circuit boards (WI  | nout components   | )            |              |              |
|          | according ISO  |                        | ts > 25 g contain the fo                      | llowing flome reterder  |                   |              |              |              |
| P7.18    |  |                        | entrations above 0,1%:                        | •                       | n.                |              |              |              |
|          | 1. Chemical na                                       | •                      | , CAS #:                                      | (See NOTE E             | 24)               | _            | _            | _            |
|          | 2. Chemical na                                       |                        | , CAS #:<br>, CAS #:                          | (See NUTE E             | )+)               |              |              |              |
|          | <ol> <li>Chemical na</li> <li>Chemical na</li> </ol> |                        | , CAS #:<br>. CAS #:                          | "                       |                   |              |              |              |
|          | 5. Chemical ha                                       | me.                    | , CAO #.                                      |                         |                   |              |              |              |
|          |  | l ana sifications of   | flame retardants in pla                       | stic parts > 25 g accor | rdina ISO 10      |              |              |              |
|          | Alt. 2: Chemica                                      | i specifications of .  | name retaruants in pia                        |                         |                   |              |              |              |
| P7.19    |  |                        | rdant substances/prepa                        |                         | <u> </u>          | ve been 🗌    |              |              |
| P7.19    | In plastic parts                                     |                        | rdant substances/prepa                        |                         | <u> </u>          | ve been 🗌    |              |              |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-internationl.org/publications/standards/Ecma-370.htm.

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

| Model n  | number *   | SC-F9500                  |                        |                    | Logo         |                   |     |       |              |
|--|--|---------------------------|------------------------|--------------------|--------------|-------------------|-----|-------|--------------|
| Issue da   | ate *  | 10/2/2024                 |                        |                    |              | EF                | 26  | 50    | Ν            |
| Due du et  |  |                           | uinen ente (e entire   |                    | •            |                   |     |       |              |
|  | t environmental a  | ttributes - Market req    | uirements (continu     | iea)               |              |                   |     |       | ent met      |
| Item   | Metaviel and av  |                           | e (e e setis ce el)    |                    |              | Ye                | es  | No    | n.a.         |
| P7.20*   |  | ostance requirement       | · · ·                  | a maduat (Cas NO   |              |                   | Я   |       | _            |
| P7.20"   | Postconsumer re  | cycled plastic material   | content is used in tr  | ie product (See NO | IE B0):      | ×                 | 4   |       |              |
|  | If VES: at least o   | ne of the two alternativ  | ves below shall be a   | nswered:           |              |                   |     |       |              |
|  |  |                           |                        |                    | rial content |                   |     |       |              |
| <sup>a)</sup> Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content<br>(calculated as a percentage of total plastic by weight) <sup>70</sup> |  |                           |                        |                    |              |                   |     |       |              |
| or   |  |                           |                        |                    |              |                   |     |       |              |
|  |  | recycled material is 18,0 | <sup>383.0</sup> g.    |                    |              |                   |     |       |              |
|  | s) the height e  |                           | 9.                     |                    |              |                   |     |       |              |
| P7.21*   | P7.21* Biobased plastic material content is used in the product (See NOTE B7): |                           |                        |                    |              |                   |     |       |              |
|  |  |                           |                        |                    |              |                   |     |       |              |
|  | If YES; at least of  | ne of the two alternativ  | es below shall be a    | nswered;           |              |                   |     |       |              |
|  | a) Of total plasti   | c parts' weight > 25 g,   | the biobased plastic   | material content   |              |                   |     |       |              |
|  | (calculated as   | a percentage of total     | plastic by weight)     | %.                 |              |                   |     |       |              |
|  | or   |                           |                        |                    |              |                   |     |       |              |
|  | , -  | the biobased plastic n    |                        |                    |              |                   |     |       |              |
| P7.22*   | Light sources are  | free from mercury, i.e    | e. less than 0,1 mg/la | amp.               |              | $\mathbf{\Sigma}$ | 3   |       |              |
|  | If mercury is use  | d specify: Number of la   | amp and maxi           | mum mercury conte  | nt per lam   | mg                |     |       |              |
| P8   | Batteries  |                           |                        |                    |              |                   |     |       |              |
| P8.1*  | Battery chemical   |                           |                        |                    |              |                   |     |       |              |
| P9   |  | ption (See NOTE B8)       |                        |                    |              |                   |     |       |              |
| P9.1   | For the product t  | ne following power leve   |                        |                    |              |                   |     |       |              |
| Energy r   | mode *   | Power level at            | Power level at         | Power level at     |              | tandard for e     | ner | gy mo | odes         |
| 0  |  | 100 V AC                  | 115 V AC               | 230 V AC           | and test met | 100               |     |       |              |
|  | ode for ENERGY<br>Operational Mode   |                           |                        | 3.2 W              |              |                   |     |       | _            |
| (OM) pro   | •  | w                         | w                      | 3.2 W              |              |                   |     |       |              |
|  | /off mode for  |                           |                        |                    |              |                   |     |       |              |
| -  | Y STAR Operation   | al w                      | w                      | 0.3 W              |              |                   |     |       | _            |
|  | DM) products   |                           |                        | 0.0                |              |                   |     |       |              |
|  |  |                           |                        |                    |              |                   |     |       |              |
|  | EC products (TEC   | = kWh/week                | kWh/week               | kWh/week           |              |                   |     |       |              |
| Typical I  |  |                           |                        |                    |              |                   |     |       |              |
| Consum<br>TEC val  | ue (OM product)  | kWh/week                  | kWh/week               | kWh/week           |              |                   |     |       |              |
|  | · · ·  | W                         | W                      | W                  |              |                   |     |       |              |
|  |  | W                         | w                      | W                  |              |                   |     |       |              |
|  |  | W                         | w                      | W                  |              |                   |     |       |              |
|  |  | W                         | w                      | w                  |              |                   |     |       |              |
|  |  | W                         | W                      | W                  |              |                   |     |       |              |
| External   | Power Supply Effi  | ciency Level (Internation | onal Efficiency Mark   | ing Protoc         |              |                   |     |       | $\mathbf{X}$ |
| Print/Sc   | an Speed * :   | 21 images per min         | iute mono              | chrome             |              |                   |     |       |              |
| Default t  | time to enter energ  |                           | minutes                |                    |              |                   |     |       | X            |
| P9.2*  | Information about  | t the energy save func    | tion is provided with  | the product.       |              | ×                 | 1   |       |              |

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

| Model number * | SC-F9500  | Logo |       |
|----------------|-----------|------|-------|
| Issue date *   | 10/2/2024 |      | EPSON |

| Produc | t environmental  | attributes - Market r  | requirement    | s (continued)     |                   |                | Req         | uirem        | ent met |
|--------|--|------------------------|----------------|-------------------|-------------------|----------------|-------------|--------------|---------|
| ltem   |  |                        |                |                   |                   |                | Yes         | No           | n.a.    |
| P10    | Emissions  |                        |                |                   |                   |                |             |              |         |
|        | Noise emissio  | n – Declared accord    | ling to ISO    |                   |                   |                |             |              |         |
| P10.1  | Mode   | Mode description       |                | Statist           | cal upper limit A | weighted sound | power level | l,           |         |
|        |  |                        |                | L <sub>WA,c</sub> | (B)               |                |             |              |         |
|        | Idle   | * Idoling              |                | *                 | -                 |                |             |              |         |
|        | Operation  | * Operation            |                | *                 | 7                 | .8             |             |              |         |
|        | Other mode   |                        |                |                   |                   |                |             |              |         |
|        | Measured acco  | rding to: 🛛 🔀 ISO 77   | 779            | ECMA-74           |                   |                |             |              |         |
|        |  | Other                  | (only if not o | covered by EC     | MA-74)            |                |             |              |         |
|        | Chemical emis  | sions from printing    | products (     | See NOTE B1       | 0)                |                |             |              |         |
| P10.2* | Test performed   | according to ECMA-     | 328 Determi    | nation of Chen    | nical Emission Ra | ates from      |             | X            |         |
|        | Electronic Equipment (ISO/IEC 28360) 📋 , other specify:  |                        |                |                   |                   |                |             |              |         |
| P10.3  |  | n rate (operation pha  |                |                   |                   |                |             |              |         |
|        |  |                        |                |                   |                   |                |             |              |         |
|        | Electrophotogra  | aphic devices: Oz      | Dust           | Styrene           | Benzene           | TVOC           |             |              |         |
|        | Ink devices:   |                        | Dust           | Styrene           | Benzene           | TVOC           |             |              |         |
|        |  |                        |                | 2                 |                   |                |             |              |         |
|        | NOTE: complia  | nce with maximum er    | mission rates  | s in eco labels   | to be declared in | P14.           |             |              |         |
| P11    | Consumable n   | naterials for printing | products       |                   |                   |                |             |              |         |
| P11.1* | A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see Pr 🛛 🗌 |                        |                |                   |                   |                |             |              |         |
|        | Paper containing nost-consumer recycled fibers can be used, provided that it meets the                         |                        |                |                   |                   |                |             |              |         |
| P11.2* | requirements of EN 12281.  |                        |                |                   |                   |                |             | $\mathbf{X}$ |         |
| P11.3* | 2-sided (duplex) printing/copying is an integrated product function.   |                        |                |                   |                   | X              |             |              |         |
| P11.4* |  |                        |                |                   |                   |                | X           |              |         |
| P13    | <u> </u>   | d documentation        |                |                   |                   |                |             |              |         |
| P13.1* |  | ing material type(s):  | Corrugated     | Fibreboard we     | aht (ka): 20.96   |                |             |              |         |
| -      |  | ing material type(s):  |                |                   | ght (kg): 1.84    |                |             |              |         |
|        |  | ing material type(s):  |                |                   | ght (kg): 1.49    |                |             |              |         |
| P13.2* |  | primary packaging is   |                |                   | 5 ( 5/            |                | X           |              |         |
| P13.3* |  | nary corrugated fiber  |                |                   | e contained perc  | centage of     |             |              |         |
|        | minimum post-o   | consumer recovered f   | fiber conte    | 80 %              | ·                 | Ū              |             |              |         |
| P13.4* |  | or user and product o  |                | on (tick box):    |                   |                |             |              |         |
|        | Electronic X, Paper X, Other   |                        |                |                   |                   |                |             |              |         |
| P13.5  |  | mplete this item if pa |                | ntation used)     |                   |                |             |              |         |
|        |  | ct documentation on    |                | ,                 | e:                |                |             |              |         |
|        | If Yes, please s   |                        |                |                   |                   |                |             |              |         |
|        | Totally chlorine-free  |                        |                |                   |                   |                |             |              |         |
|        | Elemental chlorine-free  |                        |                |                   |                   |                |             |              |         |
|        | Processed chlorine-free  |                        |                |                   |                   |                |             |              |         |
| P14    | Voluntary proc   |                        |                |                   |                   |                |             |              |         |
| P14.1  |  | ets the requirements   | of the follow  | ving voluntary    | program(s):       |                |             |              |         |
|        | ENERGY STAF  |                        |                | Date:             | Product cate      | orv:           |             |              |         |
|        | Eco-label:   | Criteria versi         |                | Date:             | Product cate      |                |             |              |         |
|        | Eco-label:   | Criteria versi         |                | Date:             | Product cate      |                |             |              |         |

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm. NOTE B10 A Guidance document on Chemical Emissions is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

| Model number *        | SC-F9500   | Logo | FROON |  |  |  |  |  |  |
|-----------------------|--|------|-------|--|--|--|--|--|--|
| Issue date *          | 10/2/2024  |      | EPSON |  |  |  |  |  |  |
|                       |  |      |       |  |  |  |  |  |  |
| Product environmental | Product environmental attributes - Market requirements (concluded) Requirement met |      |       |  |  |  |  |  |  |
| P15 Additional inf    | ormation (See NOTE B11)  |      |       |  |  |  |  |  |  |
|                       |  |      |       |  |  |  |  |  |  |
|                       |  |      |       |  |  |  |  |  |  |
|                       |  |      |       |  |  |  |  |  |  |

## Legal references Europe Annex B1

| Reference  | Declaration item             |
|--|------------------------------|
| Directive 2011/65/EU (RoHS Directive) *  | P1.1, P4.1, P3.1             |
| * Specific exemptions apply for certain products and applications.   |                              |
| Commission Regulation (EC) 1907/2006 (REACH Regulation), annex XVII  | P1.2, P1.4, P1.6, P1.7, P4.2 |
| Commission Regulation (EC) 1907/2006 (REACH Regulation), annex VII   | P1.10                        |
| Commission Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex   | P4.3                         |
| Commission Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)  | P1.3, 5.3                    |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002   | P1.5                         |
| Directive 2006/66/EC (Battery and accumulators Directive), as amended.*<br>* These provisions shall not apply where, for safety, performance, medical or<br>data integrity reasons, continuity of power supply is necessary and requires a<br>permanent connection between the appliance and the battery or accumulator.                 | P2.1, P2.2, P2.3, P8.1       |
| Directive 2014/35/EU (Low Voltage Directive)   | P3.1                         |
| Directive 2014/30/EU (EMC Directive)   | P3.1                         |
| Directive 2014/53/EU (RE Directive)  | P3.1                         |
| Commission Regulation (EC) No 1275/2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off mode electric power consumption of electrical and electronic household and office equipment (Standby Regulation)                                       | P3.1, P3.2, P9.1             |
| Commission Regulation (EC) 801/2013 amending Regulation (EC)<br>No 1275/2008 with regard to ecodesign requirements for standby, off mode<br>electric power consumption of electrical and electronic household and office<br>equipment, and amending Regulation (EC) No 642/2009 with regard to<br>ecodesign requirements for televisions |                              |
| Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing<br>Directive 2005/32/EC of the European Parliament and of the Council with regard<br>to ecodesign requirements for no-load condition electric power demand and<br>average active efficiency of external power supplies   | P3.1, P3.2, P9.1             |
| Commission Regulation (EC) 1272/2008 (CLP Regulation)  | P4.3, P7.19                  |
| Directive 2004/12/EC (Packaging Directive)   | P5.1                         |
| Decision 97/129/EC (Secondary packaging legislation)   | P5.2                         |

| Directive 2012/19/EU (WEEE directive)  | P6.1 |
|--|------|
| Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register.  |      |
| Commission Implementing Regulation 2017/699 establishing a common<br>methodology for the calculation of the weight of electrical and electronic<br>equipment (EEE) placed on the national market in each Member State and a<br>common methodology for the calculation of the quantity of waste electrical and<br>electronic equipment (WEEE) generated by weight in each Member State. |      |