

## Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	EPSON	Logo
Company name *	Seiko Epson Corporation	EDCON
Contact information *	EPSON Europe B.V. environment@epson.eu	EPSON EXCEED YOUR VISION
Internet site *	http://www.epson.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.

Type of product *	arge Format Printer (Ink-Jet)				
Commercial name *	SC-R5000, SC-R5010, SC-R5010L				
Model number *					
Issue date *	ebruary 15, 2021				
Intended market *	🗆 Global 🗹 Europe 🗋 Asia,Pacific 👘 Americas 📋 Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality of	Quality control		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	7	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	1	

Model number *	SC-R5000, SC-R5010, SC-R5010L		
Issue date *	February 15, 2021	Logo	<b>EPSON</b> EXCEED YOUR VISION

	t environmental attributes - Legal requirements	Require		
em		Yes	No	n.a.
1	Hazardous substances and preparations			
91.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)	7		
1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	1		
'1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.	7		
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	7		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	7		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).			7
P1.7*	Comment: Legal reference has no maximum concentration values. Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			7
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			7
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm2/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			7
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):	7		
-	http://www.epson.com/			
2 2.1*	<b>Batteries</b> If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)	<b>v</b>		
2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	7		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical	7		
23	or data integrity reasons do not have to be "easily removable". (See legal reference) Safety, EMC connection to the telephone network and labeling			
• 93.1*	The product complies with legally required safety standards as specified (see legal reference).	7		
°3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	- -		
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			7
°3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	7		
24	Consumable materials			
94.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			7
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	4		
94.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).	7		
95	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	7		
°5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).		1	
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	7		
lote 1 E	Restriction applies to the homogeneous material, unless other specified and expressed in weight %.			
	a of ECMA 370.4 <sup>th</sup> adition Amonded. Entry 2010			e 2 (f

Annex B of ECMA-370 4<sup>th</sup> edition Amended, February 2010

Model number *	SC-R5000, SC-R5010, SC-R5010L		
Issue date *	February 15, 2021	Logo	<b>EPSON</b> EXCEED YOUR VISION

Produc	oduct environmental attributes - Market requirements - Environmental conscious design						
em	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a			
6	Treatment information						
6.1*	Information for recyclers/treatment facilities is available (see legal reference).	1					
•	Design Disassembly, recycling						
7.1*	Parts that have to be treated separately are easily separable.	1					
7.2*	Plastic materials in covers/housing have no surface coating.	7					
7.3*	Plastic parts >100g consist of one material or of easily separable materials.	1					
′.4 <b>*</b>	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.	1					
7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.						
7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	1					
	Product lifetime						
′.7 <b>*</b>	Upgrading can be done e.g. with processor, memory, cards or drives.			1			
7.8*	Upgrading can be done using commonly available tools.			7			
7.9.	Spare parts are available after end of production for: years						
7.10	Service is available after end of production for: years						
	Material and substance requirements						
7.11*	Product cover/housing material type:						
	Material type: PS-HI Material type: ABS Material type: PC-ABS						
7.12	Electrical cable insulation materials of power cables are PVC free.						
7.13	Electrical cable insulation materials of signal cables are PVC free.						
.14	All cover/housing plastic parts >25g are free from chlorine and bromine.						
	All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B						
'.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:	-/ 🗆					
	Marking:						
7.17	Alt. 1						
	Chemical specifications of flame retardants in printed circuit boards >25g (without components):						
	TBBPA (additive)  TBBPA  Other; chemical CAS #:						
	Alt. 2						
	Chemical specifications of flame retardants in printed circuit boards (without components) >25g according						
	ISO 1043-4:						
7.18	Alt. 1						
	Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in						
	concentrations above 0.1%:						
	Comment: No legal limits exist, this is a market requirement.						
	1. Chemical name: CAS #:						
	2. Chemical name: CAS #:						
	3. Chemical name: CAS #:						
	Alt. 2						
	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:						
7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40,						
	R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)						
7.20	Of total plastic parts weight >25g, recycled material content is %						
7.21	Of total plastic parts weight >25g, biobased material content is %						
7.22	Light sources are free from mercury.						
	If mercury is used specify: Number of lamps: and max. mercury content per lamp mg						
B	Batteries						
3.1*	Battery chemical composition: Li						
3.2	Batteries meet the requirements of the following voluntary program/s:						

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	SC-R5000, SC-R5010, SC-R5010L				
Issue date *	February 15, 2021	Logo	EPSON EXCEED YOUR VISION		

Part       Energy consumption         P3.1       For the product the following power levels or energy consumptions have been measured:         Energy mode*       Power level at 100 V AC       115 V AC       230 V AC       Reference / Standard for energy modes and test method*         Con-normal       W       W       4600 W       SEC Original       Image: SEC Origina	Product	t environmental attrib	outes - Market require	ments (continued)		Requirement	met
P9.1         Exit the product the following power levels at 100 V AC         Power level at 115 V AC         Reference / Standard for energy modes and test method ''           Save 1         W         W         4600 W         SEC Original         I           Save 1         W         W         4400 W         SEC Original         I           Off 1         W         W         W         SEC Original         I         I           Off 1         W         W         W         W         I	tem					Yes No	n.a.
Energy mode *         Power level at 100 V AC         Power level at 115 V AC         Power level at 230 V AC         Reference ? Standard for energy modes and test method *         Reference ? Standard for energy modes         It           On-normal         W         W         4600 W         SEC Original         It         It         It         It         Sec Original         It	<b>9</b>						
Intervent         Intervent <thintervent< th="">         Intervent         <thintervent< th="">         Intervent         <thintervent< th=""> <thintervent< th=""> <thint< td=""><td>P9.1</td><td>For the product the f</td><td>ollowing power levels o</td><td>r energy consumpti</td><td>ons have been meas</td><td>sured:</td><td></td></thint<></thintervent<></thintervent<></thintervent<></thintervent<>	P9.1	For the product the f	ollowing power levels o	r energy consumpti	ons have been meas	sured:	
W         W         4600 W         Sec Original         Image: Constraint of the constont of the constraint of the conston of the conston of the constr	Energy m	ode *					
W         W         44 W         -         L           Off 1         W         W         1 W         SEC Original         C           W         W         W         W         W         C         C           W         W         W         W         W         C         C         C           EPS No-load         W         W         W         W         W         C         C           EPS No-load         EEC and a power supply / charge plugged in the wall outlet but disconceted from the product.)         W         W         W         W         W         C	Dn-norma	al	w	W	4600 W	SEC Original	
W         W	Save 1		w	W	44 W	SEC Original	
Image: Non-Section of the specific of t	Off 1		w	W	1 W	SEC Original	
Noise			w	w	W		
CPS No-load (External power supply / charger plugged in the wall outle but disconnected from the product.)       W       W       W       W       W       W       W       I       I         PTEC * Typical Energy Consumption the product.)       W       W       W       W       I			w	w	W		
(External power supply / charger plugged in the wall outle but disconnected from the product.)       W       W       W       W       I			w	w	w		
Typical Energy Consumption       W	EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)		W	w	w		
TEC * Typical Energy Consumption       kWh/week       kWh/week <th< td=""><td></td><td>nergy Consumption</td><td>w</td><td>w</td><td>w</td><td></td><td>7</td></th<>		nergy Consumption	w	w	w		7
ETEC * Annual Energy Consumption       kWh/year       kWh/year       kWh/year       kWh/year       kWh/year         Display resolution * :       Megapixels       Images per minute       Images per minu	FEC *		kWh/week	kWh/weel	k kWh/wee	ek	7
Print Speed*       :       31       Image particular       Image partitular       Image particular	TEC *		kWh/year	kWh/yea	r kWh/yea	ar	7
Default time to enter energy save mode:       minutes         P9.2*       Information about the energy save function is provided with the product       Image: Constraint of the following voluntary program/s:         P9.3*       The product meets the energy requirements of the following voluntary program/s:       Image: Constraint of the following voluntary program/s:         P9.3*       The product meets the energy requirements of the following voluntary program/s:       Image: Constraint of the following voluntary program/s:         P10       Emissions       Image: Constraint of the following to ISO 9296         P10.1       Mode       Mode description       Declared A-weighted sound pressure level L <sub>pAm</sub> (dB)         Intervention       Declared A-weighted sound pressure level L <sub>pAm</sub> (dB)       Image: Constraint of the product is not or Deskside         Intervention       *       B       dB       Image: Constraint of the product is not or Deskside         Intervention       *       B       dB       Image: Constraint of the product is not or Deskside         Intervention       *       B       dB       Image: Constraint of the product is not or Deskside       Image: Constraint of the product is not or Deskside         Intervention       *       B       dB       Image: Constraint of the product is not or Deskside       Image: Constraint of the product is not or Deskside         Operation       *       *			Megapixels				7
P9.2*       Information about the energy save function is provided with the product       Image: Constraint of the following voluntary program/s: ENERGY STAR® version Ver1.1 Tier: Product category:       Image: Constraint of the following voluntary program/s: ENERGY STAR® version Ver1.1 Tier: Product category:       Image: Constraint of the following voluntary program/s: Energy stars for the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s: Product category:       Image: Constraint of the following voluntary program/s:       Image: Constraint of the following voluntary program/s:       Image: Constraint of the following voluntary program/s:       Image: Constraintery program/s:       Image: Constra	Print Spe	ed * :	31 Images per m	inute			
P9.3*       The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version Ver1.1 Tier: Product category: □       □	Default tir	me to enter energy sav	/e mode:	minutes			
ENERGY STAR®       version       Ver1.1       Tier:       Product category:       Image: Constraint of the specify:         P10       Emissions         Noise emission – Declared according to ISO 9296         P10.1       Mode       Mode description       Declared A-weighted sound power level L <sub>pAm</sub> (dB)         P10.1       Mode       Mode description       Declared A-weighted sound power level L <sub>wAd</sub> (B)       Operator position         Idle       * Idoling       *       B       dB       Image: Constraint of the specified of the	P9.2*	Information about the	e energy save function	is provided with the	product		
Others specify:       Image: Constraint of the system of the	P9.3*	The product meets the	ne energy requirements	s of the following vo	luntary program/s:		
P10       Emissions         Noise emission – Declared according to ISO 9296         P10.1       Mode       Mode description       Declared       A-weighted       sound pressure level L <sub>pAm</sub> (dB)         P10.1       Mode       Mode description       Declared       A-weighted       sound pressure level L <sub>pAm</sub> (dB)         P10.1       Mode       Mode description       Declared A-weighted       sound pressure level L <sub>pAm</sub> (dB)         Idle       * Idoling       *       B       dB       (only if product is not operator attended)         Idle       * Idoling       *       B       dB       [or Deskside ]       [or Deskside ]         Operation       * Operation       *       B       dB       [or Deskside ]       [or Deskside ]         Other mode       B       dB       [or Deskide ]       [or Deskide ]       [or Deskide ]       [or Deskide ]         Measured according to:       [J ISO7779 ]       ECMA-74       [or Outler ]       [only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance       m)		ENERGY STAR®	version Ver1.1	Tier:	Product categ	lory:	
Noise emission – Declared according to ISO 9296         P10.1       Mode       Mode description       Declared A-weighted sound power level L <sub>WAd</sub> (B)       Declared A-weighted sound pressure level L <sub>pAm</sub> (dB)         Idle       * Idoling       * B       dB       (only if product is not operator attended)         Idle       * Idoling       * B       66.1 dB       [         Other mode       B       dB       [         Other       (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance       m)		Others specify:					
P10.1       Mode       Mode description       Declared       Declared       Declared A-weighted         A-weighted       sound power       level L <sub>WAd</sub> (B)       Image: Declared A-weighted       Sound pressure level L <sub>pAm</sub> (dB)       Image: Declared A-weighted         Idle       * Idoling       *       B       dB       Image: Operation A and the comparison operator attended       Image: Operator A and the comparison and the comparison operator attended       Im	P10	Emissions					
A-weighted sound power level L <sub>WAd</sub> (B)       Sound pressure level L <sub>pAm</sub> (dB)         Operator position       Bystander positions         Idle       * Idoling       * B         Operation       * Operation         Operation       * Operation         Operation       * B         Other mode       B         Measured according to:       ISO7779         ECMA-74       Other         Other       Other		Noise emission – D	eclared according to IS	O 9296			
Idle       * Idoling       *       B       dB       (only if product is not operator attended)         Idle       * Idoling       *       B       dB       [only if product is not operator attended]         Operation       *       B       dB       [only if product is not operator attended]         Operation       *       B       66.1 dB       [only if product is not operator attended]         Other mode       B       dB       [only if product is not operator attended]       [only if product is not operator attended]         Measured according to:       ISO7779       ECMA-74       B       dB         Other       (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance       m)	P10.1	Mode M	lode description			s and the second s	
Operation       * Operation       * B       66.1 dB       [         Other mode       B       dB       [         Measured according to:       ISO7779       ECMA-74         Other       (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance       m)					•	Operator position Bystander positions	
Operation       * Operation       * B       66.1 dB       []         Other mode       B       dB       dB         Measured according to:       ISO7779 ECMA-74       B       dB       dB         Other       Only if not covered by ECMA-74 with LpAm measurement distance       m)		Idle *	Idoling	*	B	dB	
Other mode     B     dB       Measured according to:     ISO7779     ECMA-74       Image: Description of the covered by ECMA-74 with LpAm measurement distance     m)		Operation *	Operation	•	B	66.1 dB	
Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)							1
					covered by ECMA 7	I with L moonurement distance	m)
P10.2 The product meets the acoustic noise requirements of the following voluntary program/s:	P10.2	The second of the first					n)

Model number *	SC-R5000, SC-R5010, SC-R5010L		
Issue date *	February 15, 2021	Logo	<b>EPSON</b> EXCEED YOUR VISION

Produc	roduct environmental attributes - Market requirements (continued)						
ltem		Y	′es	No	n.a.		
	Chemical emissions from printing products						
P10.3*	Test performed according to ECMA-328(ISO/IEC28360) standard, other specify:		]	1			
P10.4	Typical emission rate (print phase) is (mg/h):						
	Dust Ozone Styrene Benzene TVOC						
P10.5	Chemical emission requirements of the following voluntary program/s are met for :	[					
	Dust 🗌 Ozone 🗌 Styrene 🗌						
	Benzene 🔲 TVOC 🗌						
	Electromagnetic emissions						
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following volunt	tary					
	program/s:						
P11	Consumable materials for printing products						
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4	.3). 🖸	1				
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of	fГ	7	1			
	EN12281.			_			
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			7			
P12	Ergonomics for computing products						
P12.1* P12.2*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.						
	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.				4		
P13 P13.1*	Packaging and documentation						
P13.1	Product packaging material type(s): Corrugated Fibreboard weight (kg) 19						
	Product packaging material type(s): Foamed PE weight (kg) 0.4						
P13.2*	Product packaging material type(s): PE weight (kg) 0.2		_				
-	Product plastic packaging is free from PVC.		J				
P13.3*	Specify media for user and product documentation (tick box):						
<b>D</b> ( 0, 1 t		<u> </u>					
P13.4*							
	fiber 0 %						
P14	Additional information (See Note B4)						
P7	Product main body is recyclable.       □       <80% ≦ ⊡       Not includes accessories or options. This should not include thermal recycling.						

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use	P1.5
of certain dangerous chemicals 20.12.2002	
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and	P4.3
packaging (CLP)	
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging	P5.1
waste)	
(97/129/EC) (Commission Decision on Identification	P5.2
System for Packaging Materials	
2037/2000/EC Regulation on Substances that Deplete	P5.3
the Ozone Layer	
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and	P7.19
packaging (CLP)	