

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	EPSON	Logo
Company name *	Seiko Epson Corporation	EDCON
Contact information *	EPSON Europe B.V. environment@epson.eu	EPSON EXCEED YOUR VISION
Internet site *	http://www.epson.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *	Scanner					
Commercial name *	sson Perfection V850 Pro					
Model number *	Lpsoff effection vosoffo					
Issue date *	September 9, 2014					
Intended market *	☐ Global ☑ Europe ☐ Asia,Pacific ☐ Americas ☐ Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality of	Quality control		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	<b>✓</b>	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	<b>V</b>	

Model number *	Epson Perfection V850 Pro		
Issue date *	September 9, 2014	Logo	EPSON EXCEED YOUR VISION

Produc	t environmental attributes - Legal requirements	Requirer	nent n	net
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)	<b>V</b>		
P1.2*	Products do not contain Asbestos (see legal reference).  Comment: Legal reference has no maximum concentration value.	<b>V</b>		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.	<b>✓</b>		
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	<b>V</b>		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	<b>V</b>		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).  Comment: Legal reference has no maximum concentration values.			<b>V</b>
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			<b>V</b>
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).  Comment: Legal reference has no maximum concentration values.			<b>V</b>
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm2/week (see legal reference).  Comment: Max limit in legal reference when tested according to EN1811:1998.			<b>V</b>
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.epson.com/	<b>V</b>		
P2.1*	Batteries  If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)  Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or			<b>V</b>
P2.3*	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)  Batteries and accumulators are easily removable by either users or service providers (as dependent on the			✓
	design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)	_		<b>V</b>
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	<b>✓</b>		
P3.2* P3.3*	The product complies with legally required standards for electromagnetic compatibility (see legal If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	<u>√</u> ; □		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	<b>V</b>		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			<b>V</b>
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			<b>7</b>
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			V
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	<b>~</b>		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).		<b>✓</b>	
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference).  Comment: Legal reference has no maximum concentration values.	<b>✓</b>		

Model number *	Epson Perfection V850 Pro		
Issue date *	September 9, 2014	Logo	EPSON EXCEED YOUR VISION

**mandatory to fill in .Additional information regarding each item may be found under P14.	Produc	ct environmental attributes - Market requirements - Environmental conscious design	Require	ement	met
Promission for recyclers/treatment facilities is available (see legal reference):	Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
Disassembly, recycling   Disassembly, recycling   P7.1°   Parts that have to be treated separately are easily separable.   P7.2°   Parts that have to be treated separately are easily separable.   P7.2°   Parts that have to be treated separately are easily separable.   P7.2°   Parts parts 1-700   P7.2°   P7.3°   Parts parts 2-75g have meteral codes according to ISO 11469 referring ISO 1043.   P7.5°   Pastic parts 2-75g have meteral codes according to ISO 11469 referring ISO 1043.   P7.5°   P7.6°   Labels are easily separable. (This requirement does not apply to safety/regulatory labels).   P7.7°   Upgrading can be done e.g. with processor, memory, cards or drives.   P7.7°   Upgrading can be done e.g. with processor, memory, cards or drives.   P7.7°   P7.9°	P6	Treatment information			
P7.1°   Parts that have to be treated separately are easily separable.	P6.1*	Information for recyclers/treatment facilities is available (see legal reference).			
P7.1° Parts that have to be treated separately are easily separable.	P7	Design			
P7.3* Plastic materials in covers/housing have no surface coating P7.3* Plastic parts >100g consist of one material or of easily separable materials.  P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.  P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drives.  P7.8* Upgrading can be done using commonly available tools.  P7.9* Spare parts are available after end of production for:  P7.9* Spare parts are available after end of production for:  P7.10* Service is available after end of production for:  P7.11* Product cover/housing material type:  Material and substance requirements P7.11* Product cover/housing material type:  Material type: PC  Material type: PC  Material type: PC  Material type: PC  All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.14* All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15* All printed circuit boards (without components) >25g, are halogen free, as defined in IEC61249-2-21. (See Note C)  Rakring:  P7.10* All 1.1* Chemical specifications of flame retardants in printed circuit boards >25g (without components):  TBBPA (additive) TBBPA Other, chemical CAS #:  Alt 1.2* Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  Chemical aname:  CAS #:  Chemical name:  CAS #:  Chemical name:  CAS #:  Chemical name:  CAS #:  Alt 10* Chemical name:  CAS #:  Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  Chemical specifications of flame retardants substances/preparations shove 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and an		Disassembly, recycling			
P7.3* Plastic parts >100g consist of one material or of easily separable materials.	P7.1*	Parts that have to be treated separately are easily separable.	<b>✓</b>		
P7.4   Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.   P7.5   Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.   P7.6   Labels are easily separable. (This requirement does not apply to safety/regulatory labels).   P7.7   Plastic parts are available after end of production for:   P7.7   Upgrading can be done using commonly available tools.   P7.8   Upgrading can be done using commonly available tools.   P7.9   Spare parts are available after end of production for:   years   P7.10   Service is available after end of production for:   years   P7.10   Service is available after end of production for:   years   P7.10   Service is available after end of production for:   years   P7.11   Product cover/housing material type:   Material type: SPS   Material type: P7.12   Electrical cable insulation materials of power cables are PVC free.   P7.13   Electrical cable insulation materials of power cables are PVC free.   P7.14   All cover/housing plastic parts >25g are free from chlorine and bromine.   P7.15   All printed circuit boards (without components) >25g are free from chlorine and bromine.   P7.16   Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:   P7.17   All. 1   Chemical specifications of flame retardants in printed circuit boards (without components):   T8BPA (additive)   T8BPA   Other; chemical   CAS #; All. 2   Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:   P7.18   All. 1   Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:   Chemical name:   CAS #;	P7.2*	Plastic materials in covers/housing have no surface coating.		<b>✓</b>	
P7.6 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.      P7.6   Labels are easily separable. (This requirement does not apply to safety/regulatory labels).     P7.8   Upgrading can be done e.g. with processor, memory, cards or drives.     P7.8   Upgrading can be done using commonly available tools.     P7.9   Spare parts are available after end of production for:     Years   Very years	P7.3*	Plastic parts >100g consist of one material or of easily separable materials.	<b>✓</b>		
P7.6" Labels are easily separable. (This requirement does not apply to safety/regulatory labels).   J   Product lifetime   P7.7" Upgrading can be done e.g. with processor, memory, cards or drives.   J   Z   P7.9" Upgrading can be done using commonly available tools.   J   Z   P7.9" Upgrading can be done using commonly available tools.   J   Z   P7.9"   Spare parts are available after end of production for: years   P7.10   Service is available after end of production for: years   P7.11   Product cover/housing material type:   Product cover/housing material type:   P8.5%   Material type: PC   Material type: PP   P7.12   Electrical cable insulation materials of power cables are PVC free.   P7.13   Electrical cable insulation materials of signal cables are PVC free.   P7.14   All cover/housing plastic parts >25g are free from chlorine and bromine.   P7.15   Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:   P7.16   Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:   P7.17   Alt. 1   Chemical specifications of flame retardants in printed circuit boards (without components):   P7.18   Alt. 2   Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:   P8.7   Alt. 2   P7.18   Alt. 1   Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:   Comment. No legal limits exist, this is a market requirement.   CAS #:   Alt. 2   Chemical name:   CAS #:   Alt. 2   Chemical name:   CAS #:   Alt. 2   Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:   P7.19   Plastic parts >25g are free from flame retardant substances/preparations above 0.1%: classified as R45,   R40, R46, R48, R50, R51, R53, R60, R61 and any combination of the	P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.	<b>✓</b>		
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives.	P7.5				
P7.7°   Upgrading can be done e.g. with processor, memory, cards or drives.	P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	<b>✓</b>		
P7.8   Upgrading can be done using commonly available tools.		Product lifetime			
P7.9.   Spare parts are available after end of production for:   years	P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives.			<b>V</b>
P7.10   Service is available after end of production for:   years		Upgrading can be done using commonly available tools.			<b>✓</b>
Material and substance requirements	P7.9.	Spare parts are available after end of production for: years			
P7.11*   Product cover/housing material type:   Material type: PS   Material type: PP   P7.12   Electrical cable insulation materials of signal cables are PVC free.	P7.10	Service is available after end of production for: years			
Material type: PC		Material and substance requirements			
P7.12   Electrical cable insulation materials of power cables are PVC free.	P7.11*	Product cover/housing material type:			
P7.13   Electrical cable insulation materials of signal cables are PVC free.		Material type: PC Material type: SPS Material type:			
P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note   )     P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:       Marking:                             P7.17 Alt. 1		Electrical cable insulation materials of power cables are PVC free.			
P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note		•			
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking:  P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components):  TBBPA (additive)	P7.14	· · · · · ·			
Marking:  P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components):     TBBPA (additive)			ote [□]		
P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)	P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:			
Chemical specifications of flame retardants in printed circuit boards >25g (without components):  TBBPA (additive)		Marking:			
TBBPA (additive)	P7.17				
Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name:					
Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name:					
ISO 1043-4:  P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name:					
P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: CAS #: 2. Chemical name: CAS #: 3. Chemical name: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is P7.21 Of total plastic parts weight >25g, biobased material content is P7.22 Light sources are free from mercury. If mercury is used specify: Number of lamps: and max. mercury content per larr mg  P8 Batteries  P8.1* Battery chemical composition:					
Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:  Comment: No legal limits exist, this is a market requirement.  1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: 4.					
concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement.  1. Chemical name: 2. Chemical name: 3. Chemical name: CAS #: 4. CAS #: 3. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is % P7.21 Of total plastic parts weight >25g, biobased material content is % P7.22 Light sources are free from mercury. If mercury is used specify: Number of lamps: and max. mercury content per lam mg  P8 Batteries  P8.1* Battery chemical composition:	P7.18				
Comment: No legal limits exist, this is a market requirement.  1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: 3. Chemical name: 4. CAS #: 5. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is 7. Cas #: 7. Ca					
1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: 3. Chemical name: 4. CAS #: 4. C					
2. Chemical name: 3. Chemical name: CAS #: 3. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is % P7.21 Of total plastic parts weight >25g, biobased material content is % P7.22 Light sources are free from mercury. If mercury is used specify: Number of lamps: and max. mercury content per larr mg  P8 Batteries  P8.1* Battery chemical composition:					
3. Chemical name: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is  P7.21 Of total plastic parts weight >25g, biobased material content is  P7.22 Light sources are free from mercury. If mercury is used specify: Number of lamps: and max. mercury content per lam  P8 Batteries  P8.1* Battery chemical composition:					
Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is % P7.21 Of total plastic parts weight >25g, biobased material content is % P7.22 Light sources are free from mercury. If mercury is used specify: Number of lamps: and max. mercury content per lam mg  P8 Batteries  P8.1* Battery chemical composition:					
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:  P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is  P7.21 Of total plastic parts weight >25g, biobased material content is  P7.22 Light sources are free from mercury.  If mercury is used specify: Number of lamps: and max. mercury content per lam mg  P8 Batteries  P8.1* Battery chemical composition:					
P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is  W P7.21 Of total plastic parts weight >25g, biobased material content is  W P7.22 Light sources are free from mercury.  If mercury is used specify: Number of lamps: and max. mercury content per lam  P8 Batteries  P8.1* Battery chemical composition:					
R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is %  P7.21 Of total plastic parts weight >25g, biobased material content is %  P7.22 Light sources are free from mercury.  If mercury is used specify: Number of lamps: and max. mercury content per larr mg  P8 Batteries  P8.1* Battery chemical composition:		Offerfical specifications of fiame retainants in plastic parts 725g according 150 1045-4.			
R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)  P7.20 Of total plastic parts weight >25g, recycled material content is %  P7.21 Of total plastic parts weight >25g, biobased material content is %  P7.22 Light sources are free from mercury.  If mercury is used specify: Number of lamps: and max. mercury content per larr mg  P8 Batteries  P8.1* Battery chemical composition:	P7 19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45			
P7.20 Of total plastic parts weight >25g, recycled material content is %  P7.21 Of total plastic parts weight >25g, biobased material content is %  P7.22 Light sources are free from mercury.  If mercury is used specify: Number of lamps: and max. mercury content per lam mg  P8 Batteries  P8.1* Battery chemical composition:	1 7.13	· · ·			
P7.21 Of total plastic parts weight >25g, biobased material content is % P7.22 Light sources are free from mercury.  If mercury is used specify: Number of lamps: and max. mercury content per lam mg  P8 Batteries  P8.1* Battery chemical composition:	D7 20				
P7.22 Light sources are free from mercury.  If mercury is used specify: Number of lamps: and max. mercury content per larr mg  P8 Batteries  P8.1* Battery chemical composition:		2			
If mercury is used specify: Number of lamps: and max. mercury content per larr mg  P8 Batteries  P8.1* Battery chemical composition:					
P8 Batteries P8.1* Battery chemical composition:			Ш	Ш	Ш
P8.1* Battery chemical composition:	P8				
<u> </u>					- J
		•			

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	Epson Perfection V850 Pro		
Issue date *	September 9, 2014	Logo	EPSON EXCEED YOUR VISION

P9	Produc	Product environmental attributes - Market requirements (continued)  Requirement met						
P3.1   For the product the following power levels or energy consumptions have been measured;   Power level at 100 V AC   Power level at 100 V AC   230 V	Item			·			Yes No	n.a.
Power level at 100 V AC   115 V AC   230 V	P9	Energy consumpti	ion					
100 V AC	P9.1	For the product the	following power levels	or energy consum	ptio	ns have been m	easured:	
Off 1	Energy m	ode *						
W W W W W W W W W W W W W W W W W W W	Save 1		W	W		1.5 W	Based on SEIKO EPSON Standar	
W W W W   W   W   W   W   W   W   W   W	Off 1		W	W		0.3 W	Based on SEIKO EPSON Standar	
W W W W W W W W W W W W W W W W W W W			W	W		W		
PS No-load			W	W		W		
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)  PTEC * Typical Energy Consumption			W	W		W		
(External power supply / charger plugged in the wall outlet but disconnected from the product.)  PTEC * Typical Energy Consumption			W	W		W		
Typical Energy Consumption TEC* Typical Energy Consumption ETEC * Annual Energy Consumption ETEC * ET	(External charger p outlet but	power supply / lugged in the wall disconnected from	W	w		W		
Typical Energy Consumption	PTEC * Typical E	nergy Consumption	W	W		W		<b>V</b>
Annual Energy Consumption	TEC * Typical E	nergy Consumption	kWh/week	kWh/wee	ek	kWh/wee	ek	<b>V</b>
Print Speed * : 5 Images per minute	Annual E		kWh/year	kWh/yea	ar	kWh/yea	ar	<b>V</b>
Default time to enter energy save mode: minutes			Megapixels					<b>&gt;</b>
P9.2* Information about the energy save function is provided with the product  P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version Ver2.0 Tier: Product category:				ninute				
P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version Ver2.0 Tier: Product category:  Others specify:   P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared A-weighted sound power level L <sub>WAd</sub> (B)  Idle Idoling Inaudible B Declared Sound prossure level L <sub>pAm</sub> (dB)  Operation Operation Sound power level L <sub>pAm</sub> (only if product is not operator attended)  Other mode B Declared A-weighted sound pressure level L <sub>pAm</sub> (dB)  Operator position Operator attended)  Macaured according to: ISO7779 ECMA-74  Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distanc m)								
ENERGY STAR® version Ver2.0 Tier: Product category:								
Others specify:    Declared   Declared A-weighted   Sound pressure level   L_pAm (dB)	P9.3*	The product meets	the energy requiremen	ts of the following	volu	untary program/s	:	
Noise emission – Declared according to ISO 9296  P10.1  Mode  Mode description  A-weighted sound power level L <sub>WAd</sub> (B)  Desktop or Deskside (only if product is not operator attended)  Idle  * Idoling  Operation  * Operation  Other mode  Measured according to: SO7779 ECMA-74  (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distanc m)			version Ver2.0	Tier:		Product cate	gory:	
P10.1 Mode Mode description Declared A-weighted sound pressure level L <sub>pAm</sub> (dB)    Declared A-weighted sound pressure level L <sub>pAm</sub> (dB)	P10	Emissions						
A-weighted sound pressure level L <sub>pAm</sub> (dB)  Operator position  Desktop (only if product is not operator attended)  Idle		Noise emission –	Declared according to I	ISO 9296				
level L <sub>WAd</sub> (B)	P10.1	Mode	Mode description			A-weighted	sound pressure level $L_{pAm}$ (dB)	
Idle * Idoling * Inaudible B dB  Operation * Operation * 5.9 B dB  Other mode B dB  Measured according to: VISO7779 ECMA-74  Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distanc m)							Desktop (only if product is not	
Operation * Operation * 5.9 B dB Other mode B dB  Measured according to:  ISO7779 ECMA-74  Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distanc m)							or Deskside	
Other mode  B  dB  Measured according to:   ISO7779   ECMA-74  (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distanc m)					*			
Measured according to: ☑ ISO7779 ☐ ECMA-74 ☐ Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distanc m)					*		dB	
Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distanc m)						В	dB	
		Measured according			t cc	vored by ECMA	74 with 1 magguroment distance	
	P10.2	The product meets						<u>'</u>

Model number *	Epson Perfection V850 Pro		
Issue date *	September 9, 2014	Logo	EPSON EXCEED YOUR VISION

Produc	ct environmental attributes - Market requirements (continued)	Require	ement	met		
Item		Yes	No	n.a.		
	Chemical emissions from printing products					
P10.3*	Test performed according to ECMA-328(ISO/IEC28360) standard,other specify: RAL-UZ122			<b>V</b>		
P10.4	Typical emission rate (print phase) is (mg/h):					
	Dust Ozone Styrene Benzene TVOC					
P10.5	Chemical emission requirements of the following voluntary program are met for :					
	Dust ☐ Ozone ☐ Styrene ☐					
	Benzene ☐ TVOC ☐					
	Electromagnetic emissions					
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary					
	program/s:					
P11	Consumable materials for printing products					
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).			<b>✓</b>		
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of			<b>V</b>		
P11.3*	EN12281.					
P12	2-sided (duplex) printing/copying is an integrated product function.					
P12.1*	Ergonomics for computing products  The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			7		
P12.1	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.					
P13	Packaging and documentation					
P13.1*	Product packaging material type(s): Corrugated Fibreboard weight (kg) 1.525					
'0	Product packaging material type(s): Foamed PS weight (kg) 0.2					
	Product packaging material type(s): PE weight (kg) 0.056					
P13.2*	Product plastic packaging is free from PVC.	<b>7</b>		$\overline{}$		
P13.3*	Specify media for user and product documentation (tick box):	<u> </u>				
	Electronic  Paper  Other					
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled	t		$\overline{\Box}$		
	fiber 0 %					
P14	Additional information (See Note B4)					
P7	Product main body is recyclable.  Not includes acc  65% 65%<=   This is the second of	essories	or opti	ons.		
	Consider that the state of the should not the shou	include th	ermal			

## **Legal references Europe Annex B**

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use	P1.5
of certain dangerous chemicals 20.12.2002	
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and	P4.3
packaging (CLP)	
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging	P5.1
waste)	
(97/129/EC) (Commission Decision on Identification	P5.2
System for Packaging Materials	
2037/2000/EC Regulation on Substances that Deplete	P5.3
the Ozone Layer	
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and	P7.19
packaging (CLP)	