

Flexible lamp projectors that suit every size of room and audience



Model	EB-1780W	EB-1795F	EB-2250U	EB-992F	EB-FH52	EB-982W	EB-W49	EB-X49	EB-E20
Resolution	WXGA (1280 x 800)	Full HD (1920 x 1080)	WUXGA (1920 x 1200)	Full HD (1920 x 1080)	Full HD (1920 x 1080)	WXGA (1280 x 800)	WXGA (1280 x 800)	XGA (1024 x 768)	XGA (1024 x 768)
Brightness (normal / eco)	3,000lm / 1,900lm	3,200lm / 1,900lm	5,000lm / 3,800lm	4,000lm / 2,400lm	4,000lm / 2,400lm	4,200lm / 2,600lm	3,800lm / 2,600lm	3,600lm / 2,400lm	3,400lm / 2,200lm
Throw ratio	1.0 - 1.26:1	1.02 - 1.23:1	1.38 - 2.28:1	1.32 - 2.14:1	1.32 - 2.14:1	1.38 - 2.24:1	1.30 - 1.56:1	1.48 - 1.77:1	1.44 - 1.95:1
Dynamic contrast ratio	10,000:1	10,000:1	15,000:1	16,000:1	16,000:1	16,000:1	16,000:1	16,000:1	15,000:1
Scalable image size (diagonal)	30 - 300"	30 - 300"	50 - 300"	30 - 300"	30 - 300"	29 - 280"	33 - 320"	30 - 300"	30 - 350"
Aspect ratio	16:10	16:9	16:10	16:9	16:9	16:10	16:10	4:3	4:3
Networking (LAN)	Wireless LAN	Wireless LAN	Wired & optional wireless	Wired & wireless	Wireless	Wired & optional wireless	Wired & optional wireless	Wired & optional wireless	N/A
Power consumption (normal / eco)	277W / 200W	295W / 208W	405W / 323W	327W / 225W	327W / 225W	327W / 225W	327W / 225W	327W / 225W	327W / 225W
Connectivity	VGA in, Composite RCA, USB Type B, USB Type A, HDMI	VGA in, Composite RCA, USB Type B, USB Type A, HDMI, Screen Mirroring (Miracast)	VGA in x2, VGA out, HDMI x2, Composite RCA, USB Type A, USB Type B, RS-232C, MHL (via HDMI 1)	VGA in x2, VGA out, HDMI in x2, Composite in, Wireless LAN, Screen Mirroring (Miracast), USB 2.0 Type A, USB 2.0 Type B, RS-232C, RJ45	VGA in, HDMI in x2, Composite in, USB 2.0 Type A, USB 2.0 Type B, Wireless LAN, Screen Mirroring (Miracast)	VGA in x2, VGA out, HDMI in x2, Composite in, USB 2.0 Type A, USB 2.0 Type B, RS-232C, RJ45, Wireless LAN (optional)	VGA in x2, VGA out, HDMI in x2, Composite in, USB 2.0 Type A, USB 2.0 Type B, RS-232C, RJ45, Wireless LAN (optional)	VGA in x2, VGA out, HDMI in, Composite in, USB 2.0 Type A, USB 2.0 Type B, RS-232C, RJ45, Wireless LAN (optional)	VGA in x2, VGA out, HDMI in, Composite in, USB 2.0 Type B, RS-232C
Light source life (normal / eco)	4,000h / 7,000h	4,000 / 7,000h	5,000h / 10,000h	6,500h / 17,000h	5,500 / 12,000h	6,500h / 17,000h	8,000h / 17,000h	6,000h / 12,000h	6,000h / 12,000h
Dimensions / weight (W x D x H mm / kg)	292 x 213 x 44mm / 1.8kg	292 x 213 x 44mm / 1.8kg	377 x 291.5 x 110mm / 4.6kg	309 x 282 x 90mm / 3.1kg	309 x 282 x 90mm / 3.1kg	309 x 282 x 90mm / 3.1kg	302 x 249 x 87mm / 2.7kg	302 x 249 x 87mm / 2.7kg	302 x 249 x 87mm / 2.7kg

Versatile laser projectors that offer scalability and ease of use



Model	EB-L770U EB-L775U	EB-L730U EB-L735U	EB-L630SU EB-L635SU	EB-L630U	EB-L570U	EB-L530U	EB-L520U	EB-L210W	EB-L260F
Resolution	4KE WUXGA	WUXGA (1920 x 1200)	WUXGA (1920 x 1200)	WUXGA (1920 x 1200)	4KE WUXGA	WUXGA (1920 x 1200)	WUXGA (1920 x 1200)	WXGA (1280 x 800)	Full HD (1920 x 1080)
Brightness (normal / eco)	7,000lm / 4,900lm	7,000lm / 4,900lm	6,000lm / 4,200lm	6,200lm / 4,340lm	5,200lm / 3,640lm	5,200lm / 3,640lm	5,200lm / 3,640lm	4,500lm / 3,100lm	4,600lm / 3,200lm
Throw ratio	1.35 - 2.20:1	1.35 - 2.20:1	0.80 - 1.07:1	1.35 - 2.20:1	1.35 - 2.20:1	1.35 - 2.20:1	1.35 - 2.20:1	1.41 - 2.26:1	1.32 - 2.12:1
Scalable image size (diagonal)	50 - 500"	50 - 500"	50 - 200"	50 - 500"	50 - 500"	50 - 500"	50 - 500"	30 - 300"	31-310"
Aspect ratio	16:10 (supports 21:9)	16:10 (supports 21:9)	16:10 (supports 21:9)	16:10 (supports 21:9)	16:10 (supports 21:9)	16:10 (supports 21:9)	16:10 (supports 21:9)	16:10	16:9 (supports 21:9)
Connectivity	HDMI in x2, HDMI out, HDBaseT, RS-232C, USB Type A (2A), USB Type B, Optional wireless (ELPAP11)	HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast)	HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast)	HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast)	HDMI in x2, HDMI out, HDBaseT, RS-232C, USB Type A (2A), USB Type B, Optional wireless (ELPAP11)	HDMI in x2, HDMI out, HDBaseT, VGA in x2, VGA out, RS-232C, USB Type A x2, USB Type B, Screen Mirroring (Miracast)	VGA in x2, VGA out, HDMI in x2, HDBa- seT, Miracast (when use ELPAP11), USB Type A, USB Type B, RS-232C, Ethernet, Wireless LAN a/n (5GHz) (optional)	VGA in (2x), VGA out, Composite in, HDMI in x2, USB Type A (2A), USB Type B, RS- 232C, RJ45, Wireless LAN, Screen Mirroring (Miracast)	VGA in (2x), VGA out, Composite in, HDMI in x2, USB Type A (2A), USB Type B, RS- 232C, RJ45, Wireless LAN, Screen Mirroring (Miracast)
Lens shift	Yes	Yes	Yes	Yes	Yes	Yes	—	—	—
Networking	LAN, Optional wire- less	LAN, WiFi (Miracast)	LAN, WiFi (Miracast)	LAN, WiFi (Miracast)	LAN, Optional wire- less	LAN, WiFi (Miracast)	LAN, Optional wire- less	LAN, WiFi (Miracast)	LAN, WiFi (Miracast)
Power consumption (normal / eco)	366W / 268W	345W / 258W	345W / 258W	345W / 258W	312W / 234W	293W / 223W	293W / 223W	260W / 191W	260W / 191W
Dimensions / weight (W x D x H mm / kg)	440 x 304 x 122mm / 8.5kg	440 x 304 x 122mm / 8.4kg	440 x 304 x 122mm / 8.4kg	440 x 304 x 122mm / 8.4kg	440 x 304 x 122mm / 8.3kg	440 x 304 x 122mm / 8.2kg	440 x 304 x 122mm / 7.7kg	325 x 299 x 90mm / 4.2kg	325 x 299 x 90mm / 4.2kg

All lasers have a light source life of 20,000h (normal)/ 30,000h (eco)

All laser "Dynamic contrast ratio" is 2,500,000:1

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EPSON®